

6" Downlight Dimmable

15DL6/END/2700 DIM 120V

Philips 6" Downlight Dimmable LED Lamp provides a soft, diffused level of light and smooth dimming to reduce glare. The sleek, lightweight design is ideal for downlighting.

Product data

• General Characteristics

Cap-Base	E26
Bulb	RDL6
Rated Avg. Life	45000 hr
(Hours)	
Rated Lifetime	41.1 an
(years)	

• Light Technical Characteristics

Color Code	WH
Color Designation	White
Beam Angle	90 D
Correlated Color	2700 K
Temperature CRI Luminous Efficacy Lamp	82 53.33 Lm/W
Color Temp. (Kelvin)	2700 K [CCT 2700K]
Rated Luminous Flux	800 Lm

• Electrical Characteristics

Wattage	15 W
Wattage Technical	15 W
Voltage	120 V
Line Frequency	60 Hz

Warnings and Safety

- Suitable for use in damp locations.
- Do not use in outdoor fixtures.



Power Factor	0.73 -
Lamp Current mA	165 mA
Dimmable	Yes
Wattage Equivalent	75 W
Starting Time	0.5 s

• Measuring Conditions

Switching cycle

• Product Dimensions

Overall Length C	159.3 mm
Diameter D	185.5 mm

• Product Data

423517 Product number 15DL6/END/2700 DIM 120V Full product name Short product name 15DL6/END/2700 DIM 120V Pieces per Sku 1 eop_pck_cfg 2 Skus/Case 2 Bar code on pack 46677423513 Bar code on case 50046677423518 929000207804 Logistics code(s) 0.425 kg eop_net_weight_pp


20000x

- Not for use in totally enclosed luminaires.
- Before replacing, turn off power and let lamp cool to avoid electrical shock or burn.

PHILIPS

6" Downlight Dimmable LED

Dimensional drawing





E26



 $\ensuremath{\mathbb{C}}$ 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting