## SATCO" NUVO

Project Name

Location

Prepared By



## **SATCO S11333**

7.5BR30/LED/927/120V/2PK

Notes

General	
Status	Active
Watts	7.5
Incandescent Equivalent	65
Volts	120V
Shape	BR30
Base	Medium
ANSI Base	E26
Finish	Gray
CCT (Kelvin)	2700
Temperature	Warm White
CRI	90+
Lumens	650
Beam Spread	105
Dimmable	Yes Dimmable
Hours Rated	25000
Lamp Type	Reflector
Technology	LED
Electrical	
Operating Frequency	60 Hz
Operating Frequency Dimming Type	60 Hz forward phase & reverse phase
Dimming Type	forward phase & reverse phase
Dimming Type Power Factor	forward phase & reverse phase 0.92 -25C (-13F) to a maximum of +45C
Dimming Type Power Factor Operating Temperature	forward phase & reverse phase 0.92 -25C (-13F) to a maximum of +45C
Dimming Type Power Factor Operating Temperature Physical	forward phase & reverse phase 0.92 -25C (-13F) to a maximum of +45C (+113F)
Dimming Type Power Factor Operating Temperature Physical MOL	forward phase & reverse phase 0.92 -25C (-13F) to a maximum of +45C (+113F) 5.157
Dimming Type Power Factor Operating Temperature Physical MOL MOD	forward phase & reverse phase 0.92 -25C (-13F) to a maximum of +45C (+113F) 5.157 3.74
Dimming Type Power Factor Operating Temperature Physical MOL MOD Housing Color	forward phase & reverse phase 0.92 -25C (-13F) to a maximum of +45C (+113F) 5.157 3.74 GRAY
Dimming Type Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	forward phase & reverse phase 0.92 -25C (-13F) to a maximum of +45C (+113F) 5.157 3.74 GRAY
Dimming Type Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information	forward phase & reverse phase 0.92 -25C (-13F) to a maximum of +45C (+113F) 5.157 3.74 GRAY 0.194
Dimming Type Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Enclosure Rating	forward phase & reverse phase 0.92 -25C (-13F) to a maximum of +45C (+113F) 5.157 3.74 GRAY 0.194 Enclosed Rated Lamp
Dimming Type Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Enclosure Rating Warranty	forward phase & reverse phase 0.92 -25C (-13F) to a maximum of +45C (+113F) 5.157 3.74 GRAY 0.194 Enclosed Rated Lamp
Dimming Type Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Enclosure Rating Warranty Compliance	forward phase & reverse phase 0.92 -25C (-13F) to a maximum of +45C (+113F) 5.157 3.74 GRAY 0.194 Enclosed Rated Lamp 5 Year Limited - 10 hr per day

For More Information Visit: <u>https://www.satco.com/</u>

