



## S11744

14T8/LED/48-840/BP/DE/347V

### GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	14W
Color Temperature:	4000K
Length:	47.78"
Base:	Medium Bi Pin



### TECHNICAL SPECIFICATIONS

Wattage:	14W	Dimmable:	Non-Dimmable
Volts:	347V	Beam Spread:	210D
Shape:	T8	Power Factor:	0.9
Filament:	LED	Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Base:	Medium Bi Pin	Ballasting Requirements:	Ballast Bypass
ANSI Base:	G13	Bypass / Direct:	Ballast Bypass
Finish:	Gloss White	Ballast Type:	Type B
Housing Color:	White	Single / Dual End:	Double Ended
Hours Rated:	50000H	Tube Guard Use:	Yes
Color Temperature:	4000K	Safety Listing:	cRU - Recognized Component
CRI:	82CRI	Technology:	LED
Lumen Output:	1800L	Material:	Plastic

### DIMENSIONS

MOL:	47.78"
MOD:	1.00"
Weight:	0.44

### LISTINGS

Safety Listing:	cRU - Recognized Component
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-B9E2MP
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	CN - E335148
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes

### PACKAGING

Each UPC:	045923117442	Case UPC:	10045923117449
Each Quantity:	1	Case Quantity:	25
Each Dimensions:	48.00 x 1.10 x 1.10"	Case Dimensions:	58.00 x 6.00 x 6.00"

110 Heartland Blvd.  
Brentwood, NY 11717  
PH 631-243-2022  
FX 631-243-2027

Distribution Centers  
New York, Florida,  
Texas, Washington,  
California, Puerto Rico

National Toll-Free  
800-43-SATCO  
(800-437-2826)  
www.satco.com

Copyright 2022  
Satco Products, Inc.  
All Rights Reserved  
May 22, 2022