



S11761

12T8/LED/36-CCT/DM/BP-DR

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	12W
Color Temperature:	3500K/4000K/5000K
Length:	35.78"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	12W
Volts:	120V-277V
Fluorescent Equivalent:	32W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	White
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	3500K/4000K/5000K
CRI:	83CRI
Lumen Output:	1675L/1700L/1700L

Dimmable:	Yes-Dimmable
Dimming Function:	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Beam Spread:	180D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to +45C (+113F)
Ballasting Requirements:	Ballast required (Type A) or Ballast Bypass (Type B)
Bypass / Direct:	Dual
Ballast Type:	Type A/B
Single / Dual End:	Single Ended, Double Ended
Shatter Proof Type:	PET Coated
Safety Listing:	cULus - Listed; cULus - Classified; cETLus - Listed
Technology:	LED
Material:	Glass / Plastic

DIMENSIONS

MOL:	35.78"
MOD:	1.00"

LISTINGS

Safety Listing:	cULus - Listed; cULus - Classified; cETLus - Listed
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-5FL73B
DLC Primary Use:	Dual Mode Internal Driver (UL Type A and Type B)
UL File Listing:	CN/US - E335148; CN/US - E356817
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes

PACKAGING

Each UPC:	045923117619	Case UPC:	10045923117616
Each Quantity:	1	Case Quantity:	25
Each Dimensions:	36.00 x 1.00 x 1.00	Case Dimensions:	38.20 x 6.50 x 6.70
1 on Centers		Copyright 2023	
Brentwood, NY 11717	New York, Florida,	800-43-SATCO	Satco Products, Inc.
PH 631-243-2022	Texas, Washington,	(800-437-2826)	All Rights Reserved
FX 631-243-2027	California, Puerto Rico	www.satco.com	April 10, 2023