



S11764

9T8/LED/24-5CCT/BP/SE-DE

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	9W
Color Temperature:	3000K/3500K/4000K/5000K/6500K
Length:	23.17"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	9W	Dimmable:	Yes-Dimmable
Volts:	120V-277V	Beam Spread:	210D
Fluorescent Equivalent:	17W	Power Factor:	0.9
Shape:	T8	Operating Temp:	-20C (-4F) to +45C (+113F)
Filament:	LED	Bypass / Direct:	Ballast Bypass
Base:	Medium Bi Pin	Ballast Type:	Type B
ANSI Base:	G13	Single / Dual End:	Single Ended, Double Ended
Finish:	White	Safety Listing:	cULus - Classified; cULus - Certified
Housing Color:	White	Technology:	LED
Hours Rated:	50000H	Material:	Glass / Plastic
Color Temperature:	3000K/3500K/4000K/5000K/6500K		
CRI:	80CRI		
Lumen Output:	1150L/1150L/1250L/1250L/1250L		

DIMENSIONS

MOL:	23.17"
MOD:	1.00"
Weight:	0.25

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified
Location Rating:	Damp
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-N3X0KC
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	CN/US - E335148; CN/US - E356817
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes

PACKAGING

Each UPC:	045923117640	Case UPC:	10045923117647
Each Quantity:	1	Case Quantity:	25
Each Dimensions:	23.78 x 0.94 x 0.94"	Case Dimensions:	24.65 x 5.87 x 5.75"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2023
Satco Products, Inc.
All Rights Reserved
April 10, 2023