



S11765

12T8/LED/36-5CCT/BP/SE-DE

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	12W
Color Temperature:	3000K/3500K/4000K/5000K/6500K
Length:	35.17"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	12W
Volts:	120V-277V
Fluorescent Equivalent:	32W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	White
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	3000K/3500K/4000K/5000K/6500K
CRI:	80CRI
Lumen Output:	1350L/1350L/1450L/1450L/1450L

Dimmable:	Yes-Dimmable
Beam Spread:	210D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to +45C (+113F)
Bypass / Direct:	Ballast Bypass
Ballast Type:	Type B
Single / Dual End:	Single Ended, Double Ended
Safety Listing:	cULus - Classified
Technology:	LED
Material:	Glass / Plastic

DIMENSIONS

MOL:	35.17"
MOD:	1.00"
Weight:	0.35

LISTINGS

Safety Listing:	cULus - Classified
Location Rating:	Damp
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-3REMZ6
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	CN/US - E335148; CN/US - E356817
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes

PACKAGING

Each UPC:	045923117657
Each Quantity:	1
Each Dimensions:	35.83 x 0.94 x 0.94"

Case UPC:	10045923117654
Case Quantity:	25
Case Dimensions:	36.61 x 5.87 x 5.75"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2023
Satco Products, Inc.
All Rights Reserved
April 10, 2023