



# S11911

11.5T8/LED/48-835/FF/BP 120-277V  
 11.5 watt T8 LED; 3500K; Medium Bi Pin base; 50000 Average rated hours; 120-277 Volts; Type B; Ballast Bypass; Double Ended Wiring



## Features

- All glass tube
- Approved for use with tube guards
- NSF Approved
- No ballast or external driver required

\*Existing wiring to both sockets can remain in place  
 \*Will work on both shunted or non-shunted sockets

S11911

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Power Factor	Lamp Shape
S11911	045923119118	120-277	11.5	50/60Hz	32W	0.90	T8
Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Medium Bi-Pin	G13	11.5T8/LED/48-835/FF/BP 120-277V	Non-Dimmable	Frosted	48"	1.00"	1650
Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	THD	Pack
50000	3500	Neutral White	80	180	-25C (-13F) to a maximum of +45C (+113F)		25
CEC Status	DLC ID:	Material	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty	
Lawful for sale in California	DLC ID:PLILPMGNF8VC <a href="#">DLC Search</a>	Glass	Yes	Yes	cULus - Damp Location Rated	<a href="#">5 Year Limited</a>	



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

