



S11932

8T8/LED/24-840/XD
 8W T8 LED; 4000K; 120-277V; Medium Bi Pin base; Type C;
 External Driver required

Features

- All glass tube
- Approved for use with tube guards
- NSF Approved
- Working Voltage: 120-277VAC 30VDC 290mA
- 0-10V Dimming
- Satco External LED driver required for 1 or 2 lamps [S8012](#)
- Satco External LED driver required for 3 or 4 lamps [S8013](#)



S11932

Existing wiring to both sockets can remain in place.
 Will work on both shunted or non-shunted sockets.

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Power Factor	Lamp Shape
S11932	045923119323	120-277	8	50/60HZ	17W	0.90	T8

Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Medium Bi-Pin	G13	8T8/LED/24-840/XD	0-10V Dimming Only	Frosted	24"	1.00"	1200

Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type
50000	4000	Neutral White	82	220	-20C (-4F) to a maximum of +45C (+113F)	25	Sleeve

CEC Status	DLC ID:	Material	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Lawful for sale in California	PL7QH6B0982C	Glass	Yes	Yes	cULus Classified - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

