



# S11940

12T8/LED/48-840/XD  
 12W T8 LED; 4000K; 120-277V; Medium Bi Pin base; Type C;  
 External Driver required

## Features

- All glass tube
- Approved for use with tube guards
- NSF Approved
- Working Voltage: 120-277VAC 45VDC 290mA
- 0-10V Dimming
- Satco External LED driver required for 1 or 2 lamps [S8012](#)
- Satco External LED driver required for 3 or 4 lamps [S8013](#)



S11940

Existing wiring to both sockets can remain in place.  
 Will work on both shunted or non-shunted sockets.

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Power Factor	Lamp Shape
S11940	045923119408	120-277	12	50/60HZ	32W	0.90	T8

  

Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Medium Bi-Pin	G13	12T8/LED/48-840/XD	0-10V Dimming Only	Frosted	48"	1.00"	1800

  

Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type
50000	4000	Cool White	82	220	-20C (-4F) to a maximum of +45C (+113F)	25	Sleeve

  

CEC Status	DLC ID:	Material	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Lawful for sale in California	PLR2T3SDBRJX	Glass	Yes	Yes	cULus Classified - Damp Location Rated	<a href="#">5 Year Limited</a>



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

