



S11958

24T8/LED/96-840/BP/FA8

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	24W
Color Temperature:	4000K
Length:	94.00"
Base:	Single Pin



TECHNICAL SPECIFICATIONS

Wattage:	24W	Dimmable:	Non-Dimmable
Volts:	120V-277V	Beam Spread:	210D
Fluorescent Equivalent:	59W	Power Factor:	0.9
Shape:	T8	Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Filament:	LED	Ballasting Requirements:	Ballast Bypass
Base:	Single Pin	Ballast Type:	Type B
ANSI Base:	FA8	Single / Dual End:	Double Ended
Finish:	White	Shatter Proof Type:	PET Coated
Hours Rated:	50000H	Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Color Temperature:	4000K	Technology:	LED
CRI:	82CRI	Material:	Glass
Lumen Output:	3500L		

DIMENSIONS

MOL:	94.00"
MOD:	1.00"
Weight:	0.88

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLO7K8JCRGBZ
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	US/CN - E356817; US/CN - E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923119583	Case UPC:	10045923119580
Each Quantity:	1	Case Quantity:	10
Each Dimensions:	94.00 x 1.00 x 1.00"	Case Dimensions:	95.87 x 7.56 x 3.86"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2022
Satco Products, Inc.
All Rights Reserved
May 22, 2022