



S11969

12.5T8/LED/48/830-835-840/BP

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	12.5W
Color Temperature:	3000K/3500K/4000K
Length:	48.00"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	12.5W	Dimmable:	Non-Dimmable
Volts:	120V-277V	Beam Spread:	220D
Fluorescent Equivalent:	32W	Power Factor:	0.9
Shape:	T8	Operating Temp:	-20C (-4F) to +45C (+113F)
Filament:	LED	Ballasting Requirements:	Ballast Bypass
Base:	Medium Bi Pin	Bypass / Direct:	Ballast Bypass
ANSI Base:	G13	Ballast Type:	Type B
Finish:	White	Single / Dual End:	Single Ended, Double Ended
Housing Color:	White	Safety Listing:	cULus - Classified
Hours Rated:	50000H	Technology:	LED
Color Temperature:	3000K/3500K/4000K	Material:	Plastic
CRI:	83CRI		
Lumen Output:	1700L/1750L/1800L		

DIMENSIONS

MOL:	48.00"
MOD:	1.00"
Weight:	0.55

LISTINGS

Safety Listing:	cULus - Classified
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-L7RWZ3
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
CEC Terse:	Lawful for sale in California
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923119699	Case UPC:	10045923119696
Each Quantity:	1	Case Quantity:	25
Each Dimensions:	50.00 x 6.50 x 6.70"	Case Dimensions:	50.00 x 6.50 x 6.70"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2022
Satco Products, Inc.
All Rights Reserved
November 1, 2022