



S11983

9T8/LED/24-850/BP/USA

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	9WW
Color Temperature:	5000K
Length:	23.78"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	9W
Volts:	120V-277V
Fluorescent Equivalent:	17W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	Frost
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	5000K
CRI:	82CRI
Lumen Output:	1150L

Dimmable:	Non-Dimmable
Beam Spread:	210D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	BallastBypass
Ballast Type:	Type B
Single / Dual End:	Single Ended, Double Ended
Safety Listing:	cULus Classified; cRUus
Technology:	LED
Material:	Glass; Plastic

DIMENSIONS

MOL:	23.78"
MOD:	1.00"
Weight:	0.24

LISTINGS

Safety Listing:	cULus Classified; cRUus
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLL16UMVG8VL
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	E356871
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923119835
Each Quantity:	1
Each Dimensions:	24.00 x 1.00 x 1.00"

Case UPC:	10045923119832
Case Quantity:	25
Case Dimensions:	24.80 x 6.10 x 6.30"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2021
Satco Products, Inc.
All Rights Reserved
October 24, 2021