



S16435

18T8/LED/HO-SIGN/48-3CCT/BP/SE

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	18W
Color Temperature:	4000K/5000K/6500K
Length:	48.00"
Base:	Recessed Double Contact HO/VHO



TECHNICAL SPECIFICATIONS

Wattage:	18W
Volts:	120V-277V
Fluorescent Equivalent:	60W
Shape:	T8
Filament:	LED
Base:	Recessed Double Contact HO/VHO
ANSI Base:	R17d
Finish:	White
Hours Rated:	50000H
Color Temperature:	4000K/5000K/6500K
CRI:	83CRI
Lumen Output:	2500L/2600L/2450L

Beam Spread:	360D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	Ballast Bypass
Ballast Type:	Type B
Single / Dual End:	Single Ended, Double Ended
Safety Listing:	cULus - Classified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT
Technology:	LED
Material:	Polycarbonate (PC)

DIMENSIONS

MOL:	48.00"
MOD:	1.00"
Weight:	0.61

LISTINGS

Safety Listing:	cULus - Classified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT
Location Rating:	Damp
UL File Listing:	US/CN - E356817; US/CN - E335148; US/CN - E504973
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	ETL Sanitation listed (conforms to NSF)

PACKAGING

Each UPC:	045923164354	Inner UPC:	20045923164358	Case UPC:	10045923164351
Each Quantity:	1	Inner Quantity:	0	Case Quantity:	10
Each Dimensions:	0.00 x 0.00 x 0.00"	Inner Dimensions:	0.00 x 0.00 x 0.00"	Case Dimensions:	0.00 x 0.00 x 0.00"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2023
Satco Products, Inc.
All Rights Reserved
May 10, 2023