





# S16501

FC8T9/LED/CIR/840/BP  
LED Circline; 11W; T9; 4000K; G10Q Base; 120-277V; Type B;  
Ballast Bypass



S16501

## Features

- No ballast or external driver required
- Direct wire 120-277V line voltage\*
- NSF Approved
- Replaces 22W fluorescent Circlines

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Power Factor	Lamp Shape
S16501	045923165016	120-277	11	50/60Hz	22W	0.90	T9
Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Medium Bi-Pin	G10q	FC8T9/LED/CIR/840/BP	Non-Dimmable	White	1"	8.00"	1210
Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	THD	Pack
50000	4000	Cool White	80	135	-25C (-13F) to a maximum of +45C (+113F)		12/1
Package Type	Material	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty		
Box	Plastic	Yes	Yes	cETLus - Damp Location Rated	<a href="#">5 Year Limited</a>		



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

