## SATCO' NUVO

Project Name

Location

Prepared By



## **SATCO S18403**

4.5W/LED/CFL/840/G23/BP

Notes

StatusActiveWatts4.5Fluorescent Equivalent5W/7W/9WVolts120V-277VBallast TypeType BShapePLBaseG23FinishFrostedCCT (Kelvin)4000TemperatureCool WhiteCRI80Lumens450Beam Spread360Hours Rated50000Lamp TypePLBurning PositionUniversalTechnology50/60HzPower Factor0.9Operating Frequency50/60HzPower Factor0.9Operating Temperature525C (-13F) to a maximum of +45CMOL6.56MOD1.28Housing ColorWhiteWeight (b.)0.55Additional InformationStores LampWarranty5 Year Limited - 10 hr per dayComplianceCarlon RatingSafety ListingCETLus - ListedLocation RatingMoEnclosure RatingSamp LocationSafety ListingCarlus - ListedLocation RatingManp LocationEnergy StarNoRoHS CompliantYes	General	
Fluorescent Equivalent     SW/7W/9W       Volts     120V-277V       Ballast Type     Type B       Shape     PL       Base     G23       Finish     Frosted       CCT (Kelvin)     4000       Temperature     Cool White       CRI     80       Lumens     450       Beam Spread     360       Hours Rated     50000       Lamp Type     PL       Burning Position     Universal       Technology     LED       Electrical     Volta       Operating Frequency     50/60Hz       Power Factor     0.9       Operating Trequency     50/60Hz       Power Factor     0.9       Operating Temperature     25C (-13F) to a maximum of +45C (+113F)       Physical     Volta       MOL     6.56       MOD     1.28       Housing Color     White       Weight (lb.)     0.55       Additional Information     Enclosed Lamp       Warranty     5 Year Limited - 10 hr per day	Status	Active
Voits     120V-277V       Ballast Type     Type B       Shape     PL       Base     G23       Finish     Frosted       CCT (Kelvin)     4000       Temperature     Cool White       CRI     80       Lumens     450       Beam Spread     360       Hours Rated     50000       Lamp Type     PL       Burning Position     Universal       Technology     LED       Electrical     20/60Hz       Operating Frequency     50/60Hz       Operating Temperature     -25C (-13F) to a maximum of +45C (+113F)       Operating Temperature     -25C (-13F) to a maximum of +45C (+113F)       Physical     1.28       MOL     6.56       MOD     1.28       Housing Color     White       Weight (lb.)     0.55       Additional Information     5 Year Limited - 10 hr per day       Compliance     Safety Listing       Safety Listing     cETLus - Listed       Location Rating     Damp Location	Watts	4.5
Ballast TypeType BShapePLBaseG23FinishFrostedCCT (Kelvin)4000TemperatureCool WhiteCRI80Lumens450Beam Spread360Hours Rated50000Lamp TypePLBurning PositionUniversalTechnologyLEDElectrical-25C (-13F) to a maximum of +45C (+113F)Operating Temperature-25C (-13F) to a maximum of +45C (+113F)Physical0.9MOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceCamp LocationSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	Fluorescent Equivalent	5W/7W/9W
ShapePLBaseG23FinishFrostedCCT (Kelvin)4000TemperatureCool WhiteCRI80Lumens450Beam Spread360Hours Rated50000Lamp TypePLBurning PositionUniversalTechnology50/60HzPower Factor0.9Operating Temperature-25C (-13F) to a maximum of +45C (+113F)Physical	Volts	120V-277V
BaseG23BaseG23FinishFrostedCCT (Kelvin)4000TemperatureCool WhiteCRI80Lumens450Beam Spread360Hours Rated50000Lamp TypePLBurning PositionUniversalTechnologyEDFlectrical	Ballast Type	Туре В
LitterFirestedFinishFrostedCCT (Kelvin)4000TemperatureCool WhiteCRI80Lumens450Beam Spread360Hours Rated50000Lamp TypePLBurning PositionUniversalTechnologyLEDElectrical0.9Operating Frequency50/60HzPower Factor0.9Operating Temperature-25C (-13F) to a maximum of +45C (+113F)Physical1.28MOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceSafety ListingCation RatingDamp LocationEnergy StarNo	Shape	PL
CCT (Kelvin)4000TemperatureCool WhiteCRI80Lumens450Beam Spread360Hours Rated50000Lamp TypePLBurning PositionUniversalTechnologyLEDElectrical20060HzOperating Frequency50/60HzOperating Temperature-25C (-13F) to a maximum of +45C (+113F)Physical1.28MOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional Information5 Year Limited - 10 hr per dayComplianceSafety ListingSafety ListingCETLus - ListedLocation RatingDamp LocationEnergy StarNo	Base	G23
InterfactCoolTemperatureCoolCRI80Lumens450Beam Spread360Hours Rated50000Lamp TypePLBurning PositionUniversalTechnologyLEDElectricalCoolOperating Frequency50/60HzPower Factor0.9Operating Temperature-25C (-13F) to a maximum of +45C (+113F)PhysicalMOLMOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceSafety ListingSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	Finish	Frosted
CRI80Lumens450Beam Spread360Hours Rated50000Lamp TypePLBurning PositionUniversalTechnologyLEDElectrical50/60HzOperating Frequency50/60HzPower Factor0.9Operating Temperature-25C (-13F) to a maximum of +45C (+113F)MOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceSafety ListingSafety ListingCETLus - ListedLocation RatingDamp LocationEnergy StarNo	CCT (Kelvin)	4000
Lumens450Beam Spread360Hours Rated50000Lamp TypePLBurning PositionUniversalTechnologyLEDElectricalOperating Frequency50/60HzPower Factor0.9Operating Temperature-25C (-13F) to a maximum of +45C (+113F)PhysicalMOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceSafety ListingSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	Temperature	Cool White
Beam Spread360Hours Rated50000Lamp TypePLBurning PositionUniversalTechnologyLEDElectricalOperating Frequency50/60HzPower Factor0.9Operating Temperature-25C (-13F) to a maximum of +45C (+113F)PhysicalMOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosure RatingEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	CRI	80
Hours Rated50000Lamp TypePLBuming PositionUniversalTechnologyLEDElectricalOperating Frequency50/60HzPower Factor0.9Operating Temperature-25C (-13F) to a maximum of +45C (+113F)PhysicalMOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosure RatingEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceSafety ListingListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	Lumens	450
Lamp TypePLBurning PositionUniversalTechnologyLEDElectricalOperating Frequency50/60HzPower Factor0.9Operating Temperature-25C (-13F) to a maximum of +45C (+113F)PhysicalMOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosure RatingEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceSafety ListingLatingDamp LocationEnergy StarNo	Beam Spread	360
Burning PositionUniversalBurning PositionUniversalTechnologyLEDElectricalOperating Frequency50/60HzPower Factor0.9Operating Temperature-25C (-13F) to a maximum of +45C (+113F)PhysicalMOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceCertLus - ListedLocation RatingDamp LocationEnergy StarNo	Hours Rated	50000
TechnologyLEDElectricalOperating Frequency50/60HzPower Factor0.9Operating Temperature-25C (-13F) to a maximum of +45C (+113F)PhysicalMOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosed LampWarranty5 Year Limited - 10 hr per dayCompliancecETLus - ListedSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	Lamp Type	PL
ElectricalOperating Frequency50/60HzPower Factor0.9Operating Temperature-25C (-13F) to a maximum of +45C (+113F)Physical6.56MOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosed LampWarranty5 Year Limited - 10 hr per dayCompliancecETLus - ListedSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	Burning Position	Universal
Operating Frequency50/60HzPower Factor0.9Operating Temperature-25C (-13F) to a maximum of +45C (+113F)PhysicalMOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosed LampWarranty5 Year Limited - 10 hr per daySafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	Technology	LED
Power Factor0.9Operating Temperature-25C (-13F) to a maximum of +45C (+113F)Physical6.56MOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceCETLus - ListedSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	Electrical	
Operating Temperature-25C (-13F) to a maximum of +45C (+113F)Physical	Operating Frequency	50/60Hz
Operating remperature(+113F)Physical6.56MOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosure RatingEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	Power Factor	0.9
MOL6.56MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosure RatingEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceSafety ListingSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	Operating Temperature	
MOD1.28Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosed LampEnclosure RatingEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceSafety ListingSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	Physical	
Housing ColorWhiteWeight (lb.)0.55Additional InformationEnclosure RatingEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceComplianceSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo		
Weight (lb.)0.55Additional InformationEnclosed LampEnclosure RatingEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceEnclosed LampSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	MOL	6.56
Additional Information     Enclosure Rating   Enclosed Lamp     Warranty   5 Year Limited - 10 hr per day     Compliance   Safety Listing     Safety Listing   cETLus - Listed     Location Rating   Damp Location     Energy Star   No		
Enclosure RatingEnclosed LampWarranty5 Year Limited - 10 hr per dayComplianceEnclosed LampSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	MOD	1.28
Warranty5 Year Limited - 10 hr per dayComplianceSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	MOD Housing Color	1.28 White
ComplianceSafety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	MOD Housing Color Weight (lb.)	1.28 White
Safety ListingcETLus - ListedLocation RatingDamp LocationEnergy StarNo	MOD Housing Color Weight (lb.) Additional Information	1.28 White 0.55
Location Rating Damp Location   Energy Star No	MOD Housing Color Weight (lb.) Additional Information Enclosure Rating	1.28 White 0.55 Enclosed Lamp
Location Rating Damp Location   Energy Star No	MOD Housing Color Weight (lb.) Additional Information Enclosure Rating Warranty	1.28 White 0.55 Enclosed Lamp
Energy Star No	MOD Housing Color Weight (lb.) Additional Information Enclosure Rating Warranty Compliance	1.28 White 0.55 Enclosed Lamp 5 Year Limited - 10 hr per day
	MOD Housing Color Weight (lb.) Additional Information Enclosure Rating Warranty Compliance Safety Listing	1.28 White 0.55 Enclosed Lamp 5 Year Limited - 10 hr per day cETLus - Listed
	MOD Housing Color Weight (lb.) Additional Information Enclosure Rating Warranty Compliance Safety Listing Location Rating	1.28 White 0.55 Enclosed Lamp 5 Year Limited - 10 hr per day cETLus - Listed Damp Location

Copyright 2020 Satco Products, Inc. All Rights Reserved For More Information Visit: <u>https://www.satco.com/</u>

