



**S18410**

13T8U6/LED/CCT/DUAL/SE-DE

**GENERAL SPECIFICATIONS**

Shape:	T8
Wattage:	13W
Color Temperature:	3500K/4000K/5000K
Length:	22.60"
Base:	Medium Bi Pin



**TECHNICAL SPECIFICATIONS**

Wattage:	13W
Volts:	120V-277V
Fluorescent Equivalent:	32W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	White
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	3500K/4000K/5000K
CRI:	80CRI
Lumen Output:	1900L/1975L/1950L

Dimmable:	Yes-Dimmable
Dimming Function:	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Beam Spread:	160D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to +45C (+113F)
Ballasting Requirements:	Ballast required (Type A) or Ballast Bypass (Type B)
Bypass / Direct:	Dual
Ballast Type:	Type A/B
Single / Dual End:	Single Ended, Double Ended
Safety Listing:	cULus - Listed; cULus - Classified; cETLus - Listed
Technology:	LED
Material:	Plastic

**DIMENSIONS**

MOL:	22.60"
MOD:	1.00"
Leg Spacing:	6.00

**LISTINGS**

Safety Listing:	cULus - Listed; cULus - Classified; cETLus - Listed
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-R4NQ0V
DLC Primary Use:	Dual Mode Internal Driver (UL Type A and Type B)
UL File Listing:	CN/US - E335148; CN/US - E356817; ETL - 4005203
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes

**PACKAGING**

Each UPC:	045923184109	Case UPC:	10045923184106
Each Quantity:	1	Case Quantity:	12
Each Dimensions:	22.50 x 1.00 x 1.00"	Case Dimensions:	24.41 x 8.27 x 15.16"

110 Heartland Blvd. Brentwood, NY 11717 PH 631-243-2022 FX 631-243-2027	Distribution Centers New York, Florida, Texas, Washington, California, Puerto Rico	National Toll-Free 800-43-SATCO (800-437-2826) www.satco.com	Copyright 2023 Satco Products, Inc. All Rights Reserved April 10, 2023
--	---	---	---