



## S18411

13T8/U1/LED/CCT/DUAL/SE-DE

### GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	13W
Color Temperature:	3500K/4000K/5000K
Length:	22.60"
Base:	Medium Bi Pin



### TECHNICAL SPECIFICATIONS

Wattage:	13W
Volts:	120V-277V
Fluorescent Equivalent:	32W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	White
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	3500K/4000K/5000K
CRI:	80CRI
Lumen Output:	1900L/1975L/1950L

Dimmable:	Yes-Dimmable
Dimming Function:	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Beam Spread:	160D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to +45C (+113F)
Ballasting Requirements:	Ballast required (Type A) or Ballast Bypass (Type B)
Bypass / Direct:	Dual
Ballast Type:	Type A/B
Single / Dual End:	Single Ended, Double Ended
Safety Listing:	cULus - Listed; cULus - Classified; cETLus - Listed
Technology:	LED
Material:	Plastic

### DIMENSIONS

MOL:	22.60"
MOD:	1.00"
Leg Spacing:	1.625

### LISTINGS

Safety Listing:	cULus - Listed; cULus - Classified; cETLus - Listed
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-KA0DXR
DLC Primary Use:	Dual Mode Internal Driver (UL Type A and Type B)
UL File Listing:	CN/US - E335148; CN/US - E356817; ETL - 4005203
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes

### PACKAGING

Each UPC:	045923184116	Case UPC:	10045923184113
Each Quantity:	1	Case Quantity:	24
Each Dimensions:	22.50 x 1.00 x 1.00"	Case Dimensions:	24.02 x 6.30 x 15.16"

110 Heartland Blvd.  
Brentwood, NY 11717  
PH 631-243-2022  
FX 631-243-2027

Distribution Centers  
New York, Florida,  
Texas, Washington,  
California, Puerto Rico

National Toll-Free  
800-43-SATCO  
(800-437-2826)  
www.satco.com

Copyright 2023  
Satco Products, Inc.  
All Rights Reserved  
April 10, 2023