

S21728

4.5W CTC/LED/5K/CL/120V/2CD 4.5W B11 LED; Clear; Candelabra base; 5000K; 120V; Carded

Features

- · LED with a traditional incandescent look and feel
- Omni-directional light source
- Smooth dimming

- Smooth diffilling
 Replaces up to 40 watt lamps
 Long life 15,000 hours
 Damp Location
 UL listed for totally enclosed fixtures



S21728

Item Numbe	r UPC	;	Voltage	Watts		ndescent uivalent			wer ctor	Lam	p Shape	Base
S21728	21728 045923217289 120		120	4.5	40W			>0.90		B10/B11		Candelabra
ANSI Base	Lamp	Code		Dimmab Dimm		Finish		L In hes	MOD Inch		Initial Lumens	Average Rated Hours
E12 4.	5W CTC/LED/	5K/CL/120	V/2CD	Dimm	nable	Clear	37	7/8''	1-3/	8"	350	15000
Kelvin Temp	Color	CRI B	eam Spread Deg	C	Operating 7	Temperatu	re	Pa	ack F	Packaç	ge Type	ENERGY STAR
5000	Natural Light	80	360	-200	-20C (-4F) to a maximur +40C (104F)			12	12/2 CD/2		ENERGY STAR	
CEC Stat	CEC Status RoHS Compliant Fixture Ty		ıre Type	-	or ETL Listed	UL Classifica		ficatio	n	Warranty		
Non-Comp	Ion-Compliant Yes Enclose		Enclosed	Rated L	tated Lamp Yes		cULus - Damp Location Rated				3 Year Limited	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051