

## S21736

4.5G16/LED/CL/27K/E12/120V/2PK 5.5W G16 LED; Clear; Candelabra base; 2700K; 120V; 2-Pack

## **Features**

- LED with a traditional incandescent look and feel
- Omni-directional light source

- Offini-directional light source
  Smooth dimming
  Replaces up to 60 watt lamps
  Long life 15,000 hours
  Damp Location
  UL listed for totally enclosed fixtures



S21736

Item I	Number		UPC	Voltage Watts Incandescent Equival		Equivalen	Power Factor		Lamp Shape		Base		
S2	1736	045	923217364	120		5.5	60W	1	>0.90	G	616	Candelabra	
ANSI Base			Lamp C	ode			nable/Non- mmable	Finish	Initial Lumens	Avera Rated F	J -	Kelvin Temp	Color
E12	4.	4.5G16/LED/CL/27K/E12/120V/2PK		PΚ	Dimmable		Clear	500 15000		00	2700	Warm White	
CRI	Beam S		Operati	ng Temperatu	ıre	Pack	Package Ty	rpe ENER	GY STAR	CEC S	tatus	RoHS (	Compliant
80	36	60	, ,	) to a maximu IOC (104F)	m of	12-2pks	Box	ENER	GY STAR	Non-Cor	npliant Yes		′es
	Fixture Type UL or ETL List			Liste	d	UL Classification				Warranty			
Enclosed Rated Lamp Yes			s		cULus - Damp Location Rated			3	3 Year Limited				



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051