SATCO® | NUVO®

S23143

80W/LED/CCT/100-277V/EX39

GENERAL SPECIFICATIONS

Wattage:	80W/63W/54W
Lumen Output:	11200L/8820L/7560LL
Color Temperature:	3000K/4000K/5000K
Base:	Mogul Extended

50,000 HOURS · ENCLOSED FIXTURE · BALLAST BYPASS · 4KV SURGE PROTECTION · DLC · FC · RoHS COMPLIANT

TECHNICAL SPECIFICATIONS

Wattage:	80W/63W/54W		CRI:	80CRI
Volts:	100V-277V		Lumen Output:	11200L/8820L/7560L
HID Equivalent:	320W/250W/200W		Dimmable:	Yes-Dimmable
Filament:	LED		Dimming Function:	Dimmable only via the wattage/lumen selectable dial included on lamp
Base:	Mogul Extended		Burning Position:	Base Up or Base Down Only
ANSI Base:	EX39		Beam Spread:	300D
Finish:	White		Power Factor:	>0.9
Housing Color:	Dark Gray		Operating Temp:	-40C (-40F) to a maximum of +60C (+140F)
Hours Rated:	50000H		Safety Listing:	cULus - Classified; cULus - Certified; cULus - Listed
Color Temperature:	3000K/4000K/5000K		Technology:	LED

DIMENSIONS

MOL:	9.96"
MOD:	5.11"
Weight:	2.68
Min. Compartment Size:	Length: 9.85 in. Width: 9.85 in. Height: 10.95 in.

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified; cULus - Listed
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-7YQW1Z
DLC Primary Use:	Replacement Lamps for Outdoor Pole/Arm-mounted Decorative Luminaires (Type B)
UL File Listing:	US/CN - E356817; US/CN - E335148
RoHS Compliant:	Yes
FCC Compliant:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923231438	Inner UPC:	20045923231432	Case UPC:	10045923231435
Each Quantity:	1	Inner Quantity:	0	Case Quantity:	4
Each Dimensions:	11.61 x 5.51 x 5.51"	Inner Dimensions:	0.00 x 0.00 x 0.00"	Case Dimensions:	12.01 x 11.61 x 11.81"