

Project Name

Location Prepared By



M	~	•

Physical MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosure Rating Enclosed Lamp Warranty 5 Year Limited - 10 hr per day Compliance	Ctotus	Activo	
Fluorescent Equivalent			
Volts 120V-277V Ballast Type Type B Shape PL Base GX23 Finish Frosted CCT (Kelvin) 4000 Temperature Cool White CRI 80 Lumens 600 Beam Spread 360 Hours Rated 50000 Lamp Type PL 2-Pin Buming Position Universal Technology LED Electrical Operating Frequency 50/60Hz Power Factor 0.9 Operating Temperature -25C (-13F) to a maximum of +45C (+113F) Physical MOL MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosed Lamp 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location		<u>-</u>	
Ballast Type Type B Shape PL Base GX23 Finish Frosted CCT (Kelvin) 4000 Temperature Cool White CRI 80 Lumens 600 Beam Spread 360 Hours Rated 50000 Lamp Type PL 2-Pin Burning Position Universal Technology LED Electrical Operating Frequency 50/60Hz Power Factor 0.9 Operating Temperature -25C (-13F) to a maximum of +45C (+113F) Physical MOL MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosure Rating Enclosed Lamp 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location			
Shape PL Base GX23 Finish Frosted CCT (Kelvin) 4000 Temperature Cool White CRI 80 Lumens 600 Beam Spread 360 Hours Rated 50000 Lamp Type PL 2-Pin Buming Position Universal Technology LED Electrical Operating Frequency Operating Frequency 50/60Hz Power Factor 0.9 Operating Temperature -25C (-13F) to a maximum of +45C (+113F) Physical MOL MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosure Rating Enclosed Lamp 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location			
Sase GX23			
Finish Frosted CCT (Kelvin) 4000 Temperature Cool White CRI 80 Lumens 600 Beam Spread 360 Hours Rated 50000 Lamp Type PL 2-Pin Burning Position Universal Technology LED Electrical Operating Frequency Power Factor 0.9 Operating Temperature -25C (-13F) to a maximum of +45C (+113F) Physical MOL MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosed Lamp Enclosure Rating Enclosed Lamp Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location	•		
CCT (Kelvin) 4000 Temperature Cool White CRI 80 Lumens 600 Beam Spread 360 Hours Rated 50000 Lamp Type PL 2-Pin Burning Position Universal Technology LED Flectrical Operating Frequency 50/60Hz Power Factor 0.9 Operating Temperature 25C (-13F) to a maximum of +45C (+113F) Physical MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosure Rating Enclosed Lamp Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location			
Temperature Cool White CRI 80 Lumens 600 Beam Spread 360 Hours Rated 50000 Lamp Type PL 2-Pin Buming Position Universal Technology LED Electrical Operating Frequency 50/60Hz Power Factor 0.9 Operating Temperature -25C (-13F) to a maximum of +45C (+113F) Physical MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosed Lamp Enclosure Rating Enclosed Lamp Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location		1.00.00	
CRI 80 Lumens 600 Beam Spread 360 Hours Rated 50000 Lamp Type PL 2-Pin Burning Position Universal Technology LED Electrical Operating Frequency 50/60Hz Power Factor 0.9 Operating Temperature -25C (-13F) to a maximum of +45C (+113F) Physical MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosed Lamp Enclosure Rating Enclosed Lamp Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing cETLus - Listed Location Rating Damp Location	,		
Lumens 600 Beam Spread 360 Hours Rated 50000 Lamp Type PL 2-Pin Burning Position Universal Technology LED Electrical Operating Frequency 50/60Hz Power Factor 0.9 Operating Temperature -25C (-13F) to a maximum of +45C (+113F) Physical MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosure Rating Enclosed Lamp Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing cETLus - Listed Location Rating Damp Location	·		
Beam Spread Hours Rated Source Lamp Type Burning Position Technology LED Flectrical Operating Frequency Power Factor Operating Temperature Operating Temperature Physical MOL Housing Color Weight (lb.) Additional Information Enclosure Rating Warranty Compliance Safety Listing LED Additional Information Source Safety Listing Counce PL 2-Pin Universal Universal Varianty 50/60Hz 0.9 -25C (-13F) to a maximum of +45C (+113F) Physical NOL 7.11 NOD 1.28 White 0.82 Additional Information Enclosure Rating Enclosed Lamp S Year Limited - 10 hr per day CETLus - Listed Damp Location			
Hours Rated Lamp Type Burning Position Technology LED Flectrical Operating Frequency Operating Temperature Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Enclosure Rating Warranty Compliance Safety Listing LED 50/60Hz 0.9 -25C (-13F) to a maximum of +45C (+113F) 7.11 MOD 1.28 White 0.82 Additional Information Enclosed Lamp 5 Year Limited - 10 hr per day CETLus - Listed Damp Location			
Lamp Type Burning Position Universal LED Electrical Operating Frequency Power Factor Operating Temperature Operating Temperature Physical MOL MOD 1.28 Housing Color Weight (lb.) Additional Information Enclosure Rating Warranty PL 2-Pin Universal LED 50/60Hz 0.9 -25C (-13F) to a maximum of +45C (+113F) -25C (-13F) to a	·		
Burning Position Technology Electrical Operating Frequency Power Factor Operating Temperature Physical MOL MOD 1.28 Housing Color Weight (lb.) Additional Information Enclosure Rating Warranty Compliance Safety Listing Location Rating Universal Universal LED Universal Universal Universal Universal LED 50/60Hz 0.9 -25C (-13F) to a maximum of +45C (+113F) Physical Waximum of +45C (+113F) 0.9 -25C (-13F) to a maximum of +45C (+113F) 0.9 -25C (-13F) to a maximum of +45C (+113F) 0.9 -25C (-13F) to a maximum of +45C (+113F) 0.9 -25C (-13F) to a maximum of +45C (+113F) 0.9 -25C (-13F) to a maximum of +45C (+113F) 0.9 -25C (-13F) to a maximum of +45C (+113F) 0.9 -25C (-13F) to a maximum of +45C (+113F) 0.9 -25C (-13F) to a maximum of +45C (+113F) 1.28 -25C (-13F) to a maximum of +45C (+113F) 1.28 -25C (-13F) to a maximum of +45C (+113F) 1.28 -25C (-13F) to a maximum of +45C (+113F) 1.28 -25C (-13F) to a maximum of +45C (+113F) 1.28 -25C (-13F) to a maximum of +45C (+113F) 1.28 -25C (-13F) to a maximum of +45C (+113F) 1.28 -25C (-13F) to a maximum of +45C (+113F) 1.28 -25C (-13F) to a maximum of +45C (+113F) 1.28 -25C (-13F) to a maximum of +45C (+113F) 1.28 -25C (-13F) to a maximum of +45C (+113F) 1.28 -25C (-13F) to a maximum of +45C (+113F) 2.8 -25C (-13F) to a maximum of +45C (+113F) 2.8 -25C (-13F) to a maximum of +45C (+113F) 2.8 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to a maximum of +45C (+113F) 3.9 -25C (-13F) to			
Technology Electrical Operating Frequency Power Factor Operating Temperature -25C (-13F) to a maximum of +45C (+113F) Physical MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) Additional Information Enclosure Rating Warranty Enclosed Lamp 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location	, ,,		
Electrical Operating Frequency 50/60Hz Power Factor 0.9 Operating Temperature -25C (-13F) to a maximum of +45C (+113F) Physical MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosure Rating Enclosed Lamp Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location		LED	
Operating Frequency Power Factor Operating Temperature Operating T			
Power Factor Operating Temperature -25C (-13F) to a maximum of +45C (+113F) Physical MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosure Rating Enclosed Lamp 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Damp Location	Electrical		
Operating Temperature -25C (-13F) to a maximum of +45C (+113F) Physical MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosure Rating Enclosed Lamp Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location	Operating Frequency	50/60Hz	
Physical MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosure Rating Enclosed Lamp Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location	Power Factor	0.9	
MOL 7.11 MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosure Rating Enclosed Lamp Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location	Operating Temperature	-25C (-13F) to a maximum of +45C (+113F)	
MOD 1.28 Housing Color White Weight (lb.) 0.82 Additional Information Enclosure Rating Enclosed Lamp Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location	Physical		
Housing Color White Weight (lb.) 0.82 Additional Information Enclosure Rating Enclosed Lamp Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location	MOL	7.11	
Weight (lb.) Additional Information Enclosure Rating Enclosed Lamp 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location	MOD	1.28	
Additional Information Enclosure Rating Enclosed Lamp Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing cETLus - Listed Location Rating Damp Location	Housing Color	White	
Enclosure Rating Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing CETLus - Listed Location Rating Damp Location	Weight (lb.)	0.82	
Warranty 5 Year Limited - 10 hr per day Compliance Safety Listing cETLus - Listed Location Rating Damp Location	Additional Information		
Compliance Safety Listing cETLus - Listed Location Rating Damp Location	Enclosure Rating	Enclosed Lamp	
Safety Listing cETLus - Listed Location Rating Damp Location	Warranty	5 Year Limited - 10 hr per day	
Location Rating Damp Location	Compliance		
Location Rating Damp Location	Safety Listing	cETLus - Listed	
	, ,		
		<u>-</u>	









