



S29397

120W/LED/HID/5000K/100-277V/EX39
 120 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- DLC Listed
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- Built-in surge protection - 5KV
- 5 year limited warranty
- Classified under UL 1598C
- Safety chain included

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in surge protection

Minimum Compartment Size		
Length	Width	Depth
17.3 inch	9.25 inch	9.25 inch

Optional accessory: In-line surge protector [80-929](#)



S29397

Item Number	Product Line	UPC	Input Voltage	Watts	Operating Frequency	Incandescent Equivalent	Fluorescent Equivalent
S29397	Hi-Pro	045923293979	100 - 277	120	50/60Hz	750W	200W
HID Equivalent	Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches

600W	Mogul Extended	EX39	120W/LED/HID/5000K/100- 277V/EX39		Non-Dimmable	White	10-3/8"	5.87"
Initial Lumens	Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Burning Position	Operating Temperature	
16000	50000	5000	Natural Light	80+	300	Up or Down Operation Only	-20C (-4F) to a maximum of +65C (+149F)	
Pack	Package Type	CEC Status	DLC ID:		RoHS Compliant	UL Classification	Warranty	Thermal Management
4	Box	Lawful for sale in California	PLJD99GUMYDD; PLTOPWJ4LI4A DLC Search		Yes	cULus - Wet Location Rated	5 Year Limited	More Details About



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com
 Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico
 Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717
 800.437.2826 631.243.2022
 Fax 631.243.2027

