

## S29674

54W/LED/HID/4000K/100-277V/EX39 54 watt - LED HID Replacement; 4000K; Mogul extended base; 100-277 volts

## Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
  Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
  Damp location IP65 rated
- For outdoor & indoor use
- DLC Listed
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C

## Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V

Minimum Compartment Size							
Length	Width	Depth					
17.3 inch	9.25 inch	9.25 inch					

Optional accessory: In-line surge protector 80-929

This item has been discontinued. Possible replacement:

• S39674



S29674

Item	Product	UPC	Input Watts		Operating	Incandescent	Fluorescent	
Number	Line		Voltage		Frequency	Equivalent	Equivalent	
S29674	Hi-Pro	045923296741	100 - 277	54	50/60Hz	300W	85W	

	IID ivalent	Base	ANSI Base	Lamp Code				ble/Non- mable	Finish	MOL In Inches	MOD In Inches			
25	50W	Mogul Extended	EX39	54W/LED/HID/4000K/100- 277V/EX39			Non-Di	mmable	White	10-3/4"	3.69"			
	tial nens	Average Rated Hours	Kelvii Tem	Color	Color CRI Beam Spread Deg		Burning Position		Operating Temperature					
70	)20	50000	4000	Cool White	80+	30	300		or Down ation Only	-20C (-4F) to a maximum of +65C (+149F)				
Pack	Packaç Type	· CEC Status	s [	DLC ID:	RoH Comp		JL Class	ification	Warranty	Sta	tus	Suggested Substitute		
12	Box	Lawful for sale in California	PLXA <sup>2</sup>	1CFTP1AJ Search	Ye	s l			cULus - Wet Location Rated		5 Year Limited	Discon	tinued	<u>\$39674</u>



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051