



# S29903

9T8/LED/24-850/BP 120-277V  
 9W T8 LED; 5000K; Medium Bi Pin base; 50000 Average rated hours; 1150 Lumens; Type B; Ballast Bypass; Double Ended Wiring

## Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage\*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29903

\*Existing wiring to both sockets can remain in place

\*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S29903	045923299032	120-277	9	50/60Hz	17W	T8	Medium Bi-Pin
ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	9T8/LED/24-850/BP 120-277V	Non-Dimmable	White	24"	1.00"	1150	50000
Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status	DLC ID:
5000	Natural Light	82	210	-20C (-4F) to a maximum of +45C (+113F)	25	Lawful for sale in California	PLNVTKUDZ955 <a href="#">DLC Search</a>
RoHS Compliant	UL or ETL Listed	UL Classification	Warranty				
Yes	Yes	cULus - Damp Location Rated	<a href="#">5 Year Limited</a>				



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

