

S29905

17T8/LED/48-835/BP 120-277V 17 watt T8 LED; 3500K; Medium Bi Pin base; 50000 Average rated hours; 2100 Lumens

Features

- All glass tube
- Approved for use with tube guards
 Direct wire 120-277V line voltage*
 NSF Approved

- No ballast or external driver required
 Built-in shock resistant circuit (not hot until both ends are installed)

S29905

*Existing wiring to both sockets can remain in place *Will work on both shunted or non-shunted sockets

Item Number		PC	Voltage	Watts	Operating Frequency		Fluorescent Equivalent			imp iape	Base	
S29905 0459232		3299056	6 120-277	17	50/60Hz		32W		-	Т8	Medium Bi- Pin	
ANSI Base	Lamp Code			ble/Non- mable	Finish	MOL In Inches		MOD In Inches	Initial Lumer		Average Rated Hours	
G13		17T8/LED/48-835/BP 120-277V		Non-Dimmable		48''		1.00''	2100)	50000	
Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature		ure	Pack	CEC Status			DLC ID:	
3500	Neutral White	82	210	-20C (-4F) to a maximum of +45C (+113F)			25	Lawful for sale in California			PLP3II9OM9ZI DLC Search	
RoHS Compliant		U	UL or ETL Listed		UL Classification						Warranty	
Yes			Yes	С	cULus Classified - Damp Location Rated						5 Year Limited	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051