



S29906

17T8/LED/48-840/BP 120-277V
17 watt T8 LED; 4000K; Medium Bi Pin base; 50000 Average rated hours; 2200 Lumens

Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29906

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S29906	045923299063	120-277	17	50/60Hz	32W	T8	Medium Bi-Pin
ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	17T8/LED/48-840/BP 120-277V	Non-Dimmable	White	48"	1.00"	2200	50000
Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status	DLC ID:
4000	Cool White	82	210	-20C (-4F) to a maximum of +45C (+113F)	25	Lawful for sale in California	PLHFJDKOU1R3 DLC Search
RoHS Compliant	UL or ETL Listed	UL Classification	Warranty				
Yes	Yes	cULus Classified - Damp Location Rated	5 Year Limited				



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

