



# S29928

12T8/LED/36-840/BP 120-277V  
 12W T8 LED; Medium bi-pin base; 4000K; 50000 Average  
 rated hours; 1450 Lumens; Type B; Ballast Bypass; Double  
 Ended Wiring

## Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage\*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29928

\*Existing wiring to both sockets can remain in place

\*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S29928	045923299285	120-277	12	50/60Hz	25W	T8	Medium Bi-Pin
ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	12T8/LED/36-840/BP 120-277V	Non-Dimmable	White	36"	1.00"	1450	50000
Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status
4000	Cool White	82	210	-20C (-4F) to a maximum of +45C (+113F)	25	Box	Lawful for sale in California
DLC ID:		RoHS Compliant	UL or ETL Listed	UL Classification		Warranty	
PLT50YQ026TP <a href="#">DLC Search</a>		Yes	Yes	cULus Classified - Damp Location Rated		<a href="#">5 Year Limited</a>	



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

