



S29936

12T8/LED/48-840/DR
 12W T8 LED; Medium bi-pin base; 4000K; 50000 Average
 rated hours; 1800 Lumens; Type A; Ballast dependent



Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- DLC Listed
- All glass tube

*May not be compatible with every ballast. Refer to the ballast compatibility chart.

S29936

Ballast required.

View:

[Ballast Compatibility Chart](#)

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S29936	045923299360	12	25W-32W	T8	Medium Bi-Pin	G13	12T8/LED/48-840/DR
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
Non-Dimmable	Gloss White	48"	1.00"	1800	50000	4000	Cool White
CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:	RoHS Compliant
82	210	-20C (-4F) to a maximum of +45C (+113F)	10	Box	Lawful for sale in California	PLUWDAGE2QPY DLC Search	Yes
UL or ETL Listed			UL Classification			Warranty	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

