

## S39674

54W/LED/HID/4000K/100-277V/EX39 54 watt - LED HID Replacement; 4000K; Mogul extended base; 100-277 volts

## Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
  Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
  Damp location IP64 rated
- For outdoor & indoor use
- High-bay / Low-bay / Post-top
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

## Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 4KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size								
Length	Width	Depth						
15.75 inch	8 inch	8 inch						

## **Optional Accessories**

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406



S39674

S39674	Hi-Pro (	045923306747		100 - 277	54	50/60Hz		300W		85W		
HID Equivalent	Base	ANSI Base	I amp (Code			Dimmable/Non- Dimmable		Finish	MOL In Inches	MOD Inch		
250W	Mogul Extended	EX39	54W/	LED/HID/40/ 277V/EX3		00-	Non-Dimmable			9-1/32"	3-11/	/32"
Initial Lumens	Average Ra S Hours	N 6	elvin Temp	Color	CRI	Beam Sp Deg		Оре	erating Tem	perature	P	ack
7560	50000		4000	Cool White	80	300		-20C (	-20C (-4F) to a maximu +65C (+149F)			12
Package Type	CEC Status	[	DLC ID:	Materi	al	RoHS Compliant		or Listed	UL Classifi	cation	Warra	nty
Box	Lawful for sale in California	LUH2D	VRZ8XC earch	Alumin	um	Yes	Y	es	cULus - D Location F		5 Yea	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051