

S39675

80W/LED/HID/4000K/100-277V/EX39 80 watt - LED HID Replacement; 4000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
 Damp location IP64 rated
- For outdoor & indoor use
- High-bay / Low-bay / Post-top
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cÚLus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 6KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size						
Length	Width	Depth				
9.25 inch	9.25 inch	17.32 inch				

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406



S39675

Item	Product	UPC	Input	Watts	Operating	Incandescent	Fluorescent
Number	Line		Voltage	vvalls	Frequency	Equivalent	Equivalent

S39675	Hi-Pro	0459233	06754	100 - 277 80		50/60H	0/60Hz 400W		100W			
HID Equivaler	nt Base	ANSI Base		Lamp Code		D	Dimmable/Non- Dimmable		Finish	MOL In Inches	MOD In Inches	
320W	Mogul Extende	E X.39	80W	0W/LED/HID/4000K/100- 277V/EX39			N	Non-Dimmable		White	8"	4-23/32"
Initial Lumens Average Rated Hours Kelvin Te			Celvin Temp	Color	CI	ri E	Beam Spre Deg	eam Spread Operatii Deg		ting Temperature		Pack
11200	11200 50000 40		4000	Cool White 80			300	-500) to a maximum of 5C (+149F)		12
Package Type	CEC Status	DLC I	D: N	Material RoHS Compliant		UL or ETL Listed	UL C	Classification Warran		antv	Thermal inagement	
Box	Lawful for sale in California		ΔΙ	uminum	Ye	S	Yes		us - Damp ation Rated	<u>5 Ye</u> Limit		o <u>re Details</u> About



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051