S39936

12T8/LED/48-840/DR
12W T8 LED; Medium bi-pin base; 4000K; 50000 Average
rated hours; 1800 Lumens; Type A; Ballast dependent

Features
- Direct Replacement - for use on Instant Start and Rapid Start
  ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- All glass tube

*May not be compatible with every ballast. Refer to the ballast
compatibility chart.

Ballast required.

View:
Ballast Compatibility Chart
Dimmable Ballast Compatibility Chart
Emergency Ballast Compatibility Chart

S39936

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S39936	045923399367	12	25W-32W	T8	Medium Bi-Pin	G13	12T8/LED/48-840/DR

Dimmable/Non-Dimmable	Suggested Dimmers	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp
Dimmable* Ballast Dependent	Check Ballast MFG for Dimmer Compatibility	Gloss White	48"	1.00"	1800	50000	4000

Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:
Cool White	82	210	-20C (-4F) to a maximum of +45C (+113F)	25	Sleeve	Lawful for sale in California	PLLZGLTOB8Q5

RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Yes	Yes	cULus - Damp Location Rated	5 Year Limited

National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

SATCO®