



S39976

15T8/LED/48-835/DR
 15W T8 LED; Medium bi-pin base; 3500K; 50000 Average
 rated hours; 2100 Lumens; Type A; Ballast dependent

Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- All glass tube

*May not be compatible with every ballast. Refer to the ballast compatibility chart.

Ballast required.

View:

- [Ballast Compatibility Chart](#)
- [Dimmable Ballast Compatibility Chart](#)
- [Emergency Ballast Compatibility Chart](#)



S39976

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S39976	045923399763	15	25W-32W	T8	Medium Bi-Pin	G13	15T8/LED/48-835/DR

Dimmable/Non-Dimmable	Suggested Dimmers	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp
Dimmable* Ballast Dependent	Check Ballast MFG for Dimmer Compatibility	Gloss White	48"	1.00"	2100	50000	3500

Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:
Neutral White	82	210	-20C (-4F) to a maximum of +45C (+113F)	25	Sleeve	Lawful for sale in California	PL0JA82Q9N49

RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Yes	Yes	cULus - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

