

S39977

15T8/LED/48-840/DR 15W T8 LED; Medium bi-pin base; 4000K; 50000 Average rated hours; 2200 Lumens; Type A; Ballast dependent

Features

- Direct Replacement for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- DLC Listed
- All glass tube

*May not be compatible with every ballast. Refer to the ballast compatibility chart.

Ballast required.

View:

Ballast Compatibility Chart
Dimmable Ballast Compatibility Chart
Emergency Ballast Compatibility Chart



S39977

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S39977	045923399770	15	25W-32W	Т8	Medium Bi- Pin	G13	15T8/LED/48-840/DR

Dimmable/Non- Dimmable	Suggested Dimmers	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp
Dimmable* Ballast Dependent	Check Ballast MFG for Dimmer Compatibility	Gloss White	48"	1.00"	2200	50000	4000

Color CRI Beam Operating Temperature Pack Package CEC Status DLC ID:

Cool -20C (-4F) to a maximum of Lawful for sale in 210 82 10 Box PL3A7LM1DMBQ +45C (+113F) California White UL or ETL Listed **RoHS Compliant UL** Classification Warranty cULus - Damp Location Rated 5 Year Limited Yes Yes



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051