



# S8698

16T5/LED/36-850/BP/HO/120-277V  
16W T5 LED; Miniature bi-pin base; 5000K; 50000 Average  
rated hours; 1900 Lumens; 120-277V; Type B; Ballast Bypass;  
Single Ended Wiring

## Features

- No ballast or external driver required
- All glass tube
- PETa€shatterproof coated
- NSF Approved
- Single ended wiring; Non-shunted socket



S8698

Item Number	UPC	Voltage	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base
S8698	045923086984	120-277	16	50/60Hz	T5	Miniature Bi-Pin	G5
Lamp Code	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
16T5/LED/36-850/BP/HO/120-277V	Frosted	36"	0.88"	1900	50000	5000	Natural Light
CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status	RoHS Compliant	UL or ETL Listed	UL Classification
83	240	-20C (-4F) to a maximum of +45C (+113F)	25	Lawful for sale in California	Yes	Yes	cULus Classified - Damp Location Rated
Warranty							
<a href="#">5 Year Limited</a>							



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
www.satco.com

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

