

## S8710

18W/LED/HID/5000K/277-347V E26 18 watt - LED HID Replacement; 5000K; Medium base; 277-347 volts

## Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
  Ballast by-pass Direct wire only 277 347V
  UL approved for totally enclosed fixtures
  Damp location IP65 rated
  For outdoor & indoor use

- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)5 year limited warranty
- cÚLus listed

## Additional Technical Specifications

- Operating Frequency 50-60HzWorking Voltage AC 250-380V
- Power Factor >0.9

Minimum Compartment Size						
Length Width Depth						
8.5 inch	6 inch	6 inch				

Optional accessory: In-line surge protector 80-935



S8710

Item Number	Product Line	UPC	Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
S8710	Hi-Pro	045923087103	277-347	18	120W	32W	70W
	ANSI			Dimr	nable/Non	MOL In MC	D In Initial

Base	ANSI Base	Lamp Code	Dimmable/Non- Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Medium	E26	18W/LED/HID/5000K/277-347V E26	Non-Dimmable	White	6-7/8"	2-3/4"	2400

Average Rated	Kelvin	Color	CRI	Beam Spread	Operating Temperature	Pack	Package Type
Hours	Temp	00101	OIXI	Deg	Operating remperature	Tack	r ackage rype

50000	5000	Natural Light	80+	300		-20C (-4F) to a maximum of +65C (+149F)		48	Вох
CEC Status	RoHS	S Compliant	Fixture Type			or ETL sted	III (Classification		Warranty
Lawful for sale i California	n	Yes	Enclos	ed Rated	`	Yes	cULus - Damp Locat Rated	ion	5 Year Limited



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051