

S9394

54W/LED/HID/5000K/100-277V

54 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
 UL approved for totally enclosed fixtures
 Damp location IP65 rated

- For outdoor & indoor use
- DLC Listed
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V

Minimum Compartment Size						
Length	Width	Depth				
17.3 inch	9.25 inch	9.25 inch				

Optional accessory: In-line surge protector 80-929

This item has been discontinued. Possible replacement:

• S29394

ltem Number	Product Line	UPC	Input Watts Voltage		Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
S9394	Hi-Pro	045923093944	100 - 277	54	300W	85W	250W



S9394

Base	ANSI Base		Lamp Code			Dimmable/Non- Dimmable		Finish	MOL In Inches	MOD I Inche	
Mogul Extended	EX39	54W/	4W/LED/HID/5000K/100-277V		-277V	Non-Dimmable		White	10-3/4''	3.69'	7200
Average Rate Hours		elvin ēmp	Color	CRI		i Spread Deg	Operat	ing Tempe	erature	Pack	Package Type
50000	5	5000	Natural Light	80+	;	300	-20C (-4F) to a maximum of +65C (+149F)			12	Box
CEC Status	DI	LC ID:	RoHS Complia	nt	UL or ETL Listed	UL Cla	ssification	Warrant	Warranty Sta		Suggested Substitute
Lawful for sale in California	P7RMN PMM9N <u>DLC Se</u>	IX2Z	Yes		Yes		s - Damp on Rated	<u>5 Year</u> Limited	Disco	ntinued	<u>S29394</u>



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051