



# S9768

30W/LED/HID/MB/2700K/100-277V  
 30 watt - LED HID Replacement; 2700K; Medium base;  
 Adjustable beam angle; 100-277 volts

### Features

- Replaces HID, CFL, and Incandescent
- Direct wire range voltage 100-277V
- Approved for totally enclosed fixtures
- Hi bay, low bay and post top
- Light panels lock into place creating 3 separate beam angle options
- IP65 rated
- 5 year limited warranty

Specification note: Power Factor >0.9; Operating temperature range -20°C to 65°C; Operating Frequency 50-60Hz; Working Voltage AC 90-305V

Optional accessory: In-line surge protector [80-929](#)

Width (360°)	Width (270°)	Width (180°)
3.2"	6.8"	7.7"

Minimum Compartment Size		
Length	Width	Depth
11 inch	8 inch	8 inch



S9768

Item Number	Product Line	UPC	Input Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
S9768	Hi-Pro	045923097683	100 - 277	30	200W	55W	150W

Power Factor	Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches
0.90	Medium	E26	30W/LED/HID/MB/2700K/100-277V	Non-Dimmable	White	6-3/8"	3-3/16" (Open 7-11/16")

Initial Lumens	Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack
----------------	---------------------	-------------	-------	-----	-----------------	-----------------------	------

3660	50000	2700	Warm White	83	Adjustable: 360; 270; 180	-20C (-4F) to a maximum of +65C (+149F)	24/6
Package Type	CEC Status	RoHS Compliant	Fixture Type	UL or ETL Listed	UL Classification	Warranty	
Box	Lawful for sale in California	Yes	Enclosed Rated	Yes	cULus - Damp Location Rated	<a href="#">5 Year Limited</a>	



**National Toll-Free:**  
 800.43.SATCO  
 (800.437.2826)  
[www.satco.com](http://www.satco.com)

**Distribution Centers:**  
 New York, Florida, Texas,  
 Washington, California,  
 Puerto Rico

**Corporate Offices:**  
 110 Heartland Blvd.,  
 Brentwood, NY 11717  
 800.437.2826 631.243.2022  
 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051