

## S9821

2W CFC/LED/27K/CL/120V Discontinued - 2 watt CA11 LED; Clear; Candelabra base; 2700K; 190 lumens; 120 volts

## Features

- · LED with a traditional incandescent look and feel

- LED with a traditional incandescent in
  Omni-directional light source
  Smooth dimming
  Replaces up to 25 watt lamps
  Long life 15,000 hours
  Damp Location
  UL listed for totally enclosed fixtures



S9821

| Item Number            |                        | UPC               | Voltage             | e V                       | Watts Incandes  |                    | Equivalent                   | Facto                                     |         | Lamp<br>Shape             |              | Base                    |  |
|------------------------|------------------------|-------------------|---------------------|---------------------------|-----------------|--------------------|------------------------------|-------------------------------------------|---------|---------------------------|--------------|-------------------------|--|
| S9821                  |                        | 045923098215      | 120                 |                           | 2               | 25V                | /                            | >0.7                                      | 0       | CA11                      |              | Candelabra              |  |
| ANSI<br>Base           |                        | Lamp Code         | Di                  | Dimmable/Non-<br>Dimmable |                 |                    | Suggested<br>Dimmers         |                                           |         | MOL In MOD<br>Inches Inch |              | Initial<br>Lumens       |  |
| E12                    | 2W CFC/LED/27K/CL/120V |                   | 120V                | Dimm                      | nable           |                    | Compatible dimmers for S9821 |                                           | 4-11/16 | 4-11/16" 1-3              |              | 8" 190                  |  |
| Average Rated<br>Hours |                        | Kelvin<br>Temp    | Color               | CRI                       | Beam S          | Spread<br>eg       | Operating                    | erating Temperature                       |         |                           | Package Type |                         |  |
| 15000                  |                        | 2700              | Warm<br>White       | 80                        | 36              | 60                 |                              | 20C (-4F) to a maximum of<br>+45C (+113F) |         |                           | Box          |                         |  |
| RoHS Compliant         |                        | Fixture Type      | UL or ETL<br>Listed | ı                         | UL Class        | sification         | Warran                       | ty                                        | Status  | 9                         |              | luggested<br>Substitute |  |
| Yes                    |                        | Enclosed<br>Rated | Yes                 | cUL                       | us - Dan<br>Rat | np Location<br>ted | 3 Year Lim                   | nited Discontinue                         |         | nued                      | <u>S9921</u> |                         |  |



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051