

S9926

12T8/LED/36-830/BP 12 watt T8 LED; Medium bi-pin base; 3000K; 50000 average rated hours; 1400 lumens

Features

- All glass tube

- All glass tube
 Direct wire 120-277V line voltage*
 Double ended wiring
 NSF Approved
 No ballast or external driver required
 Built-in shock resistant circuit (not hot until both ends are installed)

S9926

*Existing wiring to both sockets can remain in place *Will work on both shunted or non-shunted sockets

Item Number UPC		Voltage Watts		;	Operating Frequency		l	Fluorescent Equivalent		Lamp Shape	Base	
S9926	S9926 045923099267		120-277	12	50/60)Hz	25W			Т8	Medium Bi- Pin
ANSI Lamp Code			Dimmable/Non- Dimmable			Finish	MOL Ir Inches				al Lumens	Average Rated Hours
G13 12T8/LED/36-830/BP			Non-Dimmable		١	White	36''		1.00"		1400	50000
Kelvin Temp	Kelvin Temp Color CRI		Beam Spread Deg		Pack	Pac	kage Type	е	CEC Status		F	RoHS Compliant
3000	Soft White	82	82 220		10	Box			Lawful for sale in California		in	Yes
UL or	ETL Listed	UL Classification							Warranty			
	cULus - Damp Location Rated							5 Year Limited				



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051