



# S9929

12T8/LED/36-850/BP  
12 watt T8 LED; Medium bi-pin base; 5000K; 50000 average rated hours; 1450 lumens

### Features

- All glass tube
- Direct wire 120-277V line voltage\*
- Double ended wiring
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S9929

\*Existing wiring to both sockets can remain in place

\*Will work on both shunted or non-shunted sockets

This item has been discontinued.

Possible replacement:

- [S29929](#)

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S9929	045923099298	120-277	12	50/60Hz	25W	T8	Medium Bi-Pin
ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	12T8/LED/36-850/BP	Non-Dimmable	White	36"	1.00"	1450	50000
Kelvin Temp	Color	CRI	Beam Spread Deg	Pack	Package Type	CEC Status	RoHS Compliant
5000	Natural Light	82	220	10	Box	Lawful for sale in California	Yes
UL or ETL Listed	UL Classification	Warranty	Status	Suggested Substitute			
Yes	cULus - Damp Location Rated	<a href="#">5 Year Limited</a>	Discontinued	<a href="#">S29929</a>			



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

