

Fluorescent Sub-Miniature T2 Tubes

Not Shown Actual Size



FM6

FM8

FM11

FM13

6 Watt
Axial Base
S6488 3000K
S2900 3500K
S6489 4100K
Packing:
20/Master

8 Watt
Axial Base
S6490 3000K
S2901 3500K
S6491 4100K
Packing:
20/Master

11 Watt
Axial Base
S6492 3000K
S2902 3500K
S6493 4100K
Packing:
20/Master

13 Watt
Axial Base
S6494 3000K
S2903 3500K
S6495 4100K
Packing:
20/Master

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Kelvin | CRI | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|-------|-----------------|-----------|--------|-----|------------------|----------------|----------------|--------|
| 6 | T2 | Axial | S6488 | FM6/830 | 3000 | 80 | 10,000 | 330 | 8.6" | 20 |
| 6 | T2 | Axial | S2900 | FM6/835 | 3500 | 80 | 10,000 | 330 | 8.6" | 20 |
| 6 | T2 | Axial | S6489 | FM6/841 | 4100 | 80 | 10,000 | 330 | 8.6" | 20 |
| 8 | T2 | Axial | S6490 | FM8/830 | 3000 | 80 | 10,000 | 540 | 12.6" | 20 |
| 8 | T2 | Axial | S2901 | FM8/835 | 3500 | 80 | 10,000 | 540 | 12.6" | 20 |
| 8 | T2 | Axial | S6491 | FM8/841 | 4100 | 80 | 10,000 | 540 | 12.6" | 20 |
| 11 | T2 | Axial | S6492 | FM11/830 | 3000 | 80 | 10,000 | 750 | 16.6" | 20 |
| 11 | T2 | Axial | S2902 | FM11/835 | 3500 | 80 | 10,000 | 750 | 16.6" | 20 |
| 11 | T2 | Axial | S6493 | FM11/841 | 4100 | 80 | 10,000 | 750 | 16.6" | 20 |
| 13 | T2 | Axial | S6494 | FM13/830 | 3000 | 80 | 10,000 | 930 | 20.6" | 20 |
| 13 | T2 | Axial | S2903 | FM13/835 | 3500 | 80 | 10,000 | 930 | 20.6" | 20 |
| 13 | T2 | Axial | S6495 | FM13/841 | 4100 | 80 | 10,000 | 930 | 20.6" | 20 |

fluorescent lamps

Fluorescent High Performance T5 Tubes

Not Shown Actual Size

Tri-Phosphor — Electronic Ballast

Standard Mini Bi Pin Base

14W

S6425 3000K
S6426 3500K
S6427 4100K

21W

S6428 3000K
S6429 3500K
S6430 4100K

28W

S6431 3000K
S6432 3500K
S6433 4100K

35W

S6434 3000K
S6435 3500K
S6436 4100K

40/Master



High Output Mini Bi Pin Base

24W

S6437 3000K
S6438 3500K
S6439 4100K

39W

S6440 3000K
S6441 3500K
S6442 4100K

54W

S6443 3000K
S6444 3500K
S6445 4100K

80W

S6446 3000K
S6447 3500K
S6448 4100K

40/Master

Standard

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Kelvin | CRI | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|-------------|-----------------|-----------|--------|-----|------------------|----------------|----------------|--------|
| 14 | T5 | Mini Bi Pin | S6425 | FP14/830 | 3000 | 82 | 20,000 | 1275 | 24" | 40 |
| 14 | T5 | Mini Bi Pin | S6426 | FP14/835 | 3500 | 82 | 20,000 | 1275 | 24" | 40 |
| 14 | T5 | Mini Bi Pin | S6427 | FP14/841 | 4100 | 82 | 20,000 | 1275 | 24" | 40 |
| 21 | T5 | Mini Bi Pin | S6428 | FP21/830 | 3000 | 82 | 20,000 | 2000 | 36" | 40 |
| 21 | T5 | Mini Bi Pin | S6429 | FP21/835 | 3500 | 82 | 20,000 | 2000 | 36" | 40 |
| 21 | T5 | Mini Bi Pin | S6430 | FP21/841 | 4100 | 82 | 20,000 | 2000 | 36" | 40 |
| 28 | T5 | Mini Bi Pin | S6431 | FP28/830 | 3000 | 82 | 20,000 | 2750 | 48" | 40 |
| 28 | T5 | Mini Bi Pin | S6432 | FP28/835 | 3500 | 82 | 20,000 | 2750 | 48" | 40 |
| 28 | T5 | Mini Bi Pin | S6433 | FP28/841 | 4100 | 82 | 20,000 | 2750 | 48" | 40 |
| 35 | T5 | Mini Bi Pin | S6434 | FP35/830 | 3000 | 82 | 20,000 | 3425 | 60" | 40 |
| 35 | T5 | Mini Bi Pin | S6435 | FP35/835 | 3500 | 82 | 20,000 | 3425 | 60" | 40 |
| 35 | T5 | Mini Bi Pin | S6436 | FP35/841 | 4100 | 82 | 20,000 | 3425 | 60" | 40 |

High Output

| | | | | | | | | | | |
|----|----|-------------|--------------|-------------|------|----|--------|------|-----|----|
| 24 | T5 | Mini Bi Pin | S6437 | FP24/830/HO | 3000 | 82 | 20,000 | 1875 | 24" | 40 |
| 24 | T5 | Mini Bi Pin | S6438 | FP24/835/HO | 3500 | 82 | 20,000 | 1875 | 24" | 40 |
| 24 | T5 | Mini Bi Pin | S6439 | FP24/841/HO | 4100 | 82 | 20,000 | 1875 | 24" | 40 |
| 39 | T5 | Mini Bi Pin | S6440 | FP39/830/HO | 3000 | 82 | 20,000 | 3300 | 36" | 40 |
| 39 | T5 | Mini Bi Pin | S6441 | FP39/835/HO | 3500 | 82 | 20,000 | 3300 | 36" | 40 |
| 39 | T5 | Mini Bi Pin | S6442 | FP39/841/HO | 4100 | 82 | 20,000 | 3300 | 36" | 40 |
| 54 | T5 | Mini Bi Pin | S6443 | FP54/830/HO | 3000 | 82 | 20,000 | 4725 | 48" | 40 |
| 54 | T5 | Mini Bi Pin | S6444 | FP54/835/HO | 3500 | 82 | 20,000 | 4725 | 48" | 40 |
| 54 | T5 | Mini Bi Pin | S6445 | FP54/841/HO | 4100 | 82 | 20,000 | 4725 | 48" | 40 |
| 80 | T5 | Mini Bi Pin | S6446 | FP80/830/HO | 3000 | 82 | 20,000 | 6575 | 60" | 40 |
| 80 | T5 | Mini Bi Pin | S6447 | FP80/835/HO | 3500 | 82 | 20,000 | 6575 | 60" | 40 |
| 80 | T5 | Mini Bi Pin | S6448 | FP80/841/HO | 4100 | 82 | 20,000 | 6575 | 60" | 40 |

fluorescent lamps

Fluorescent T5 Tubes Preheat



5000 Hours

Not Shown Actual Size



Blacklights

F4T5

F6T5

F8T5

F13T5

Blacklight

- S2904 4 Watt
- S2905 6 Watt
- S2906 8 Watt

Blacklight Blue

- S6405 4 Watt
- S2907 6 Watt
- S6406 8 Watt

Packing: 24/Master,
Individually Boxed

4 Watt

- Mini Bi Pin Base
- S1900 Cool White
- S2908 Daylight

Packing: 20/Master,
Individually Boxed

6 Watt

- Mini Bi Pin Base
- S1902 Cool White
- S2909 Daylight

Packing: 20/Master,
Individually Boxed

8 Watt

- Mini Bi Pin Base
- S1904 Cool White
- S1905 Warm White
- S2910 Daylight

Packing: 20/Master,
Individually Boxed

13 Watt

- Mini Bi Pin Base
- S1906 Cool White
- S1907 Warm White
- S2911 Daylight

Packing: 20/Master,
Individually Boxed

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Pack. Type | Carton |
|-------|-----------|-------------|-----------------|-----------|-----------------|------------------|----------------|----------------|------------|--------|
| 4 | T5 | Mini Bi Pin | S1900 | F4T5/CW | Cool White | 5000 | 135 | 6" | Box | 20 |
| 4 | T5 | Mini Bi Pin | S2908 | F4T5/D | Daylight | 5000 | 115 | 6" | Box | 20 |
| 4 | T5 | Mini Bi Pin | S2904 | F4T5/BL | Blacklight | 5000 | n/a | 6" | Sleeve | 20 |
| 4 | T5 | Mini Bi Pin | S6405 | F4T5/BLB | Blacklight Blue | 5000 | n/a | 6" | Sleeve | 20 |
| 6 | T5 | Mini Bi Pin | S1902 | F6T5/CW | Cool White | 5000 | 270 | 9" | Box | 20 |
| 6 | T5 | Mini Bi Pin | S2909 | F6T5/D | Daylight | 5000 | 260 | 9" | Box | 20 |
| 6 | T5 | Mini Bi Pin | S2905 | F6T5/BL | Blacklight | 5000 | n/a | 9" | Sleeve | 20 |
| 6 | T5 | Mini Bi Pin | S2907 | F6T5/BLB | Blacklight Blue | 5000 | n/a | 9" | Sleeve | 20 |
| 8 | T5 | Mini Bi Pin | S1904 | F8T5/CW | Cool White | 5000 | 390 | 12" | Box | 20 |
| 8 | T5 | Mini Bi Pin | S2910 | F8T5/D | Daylight | 5000 | 350 | 12" | Box | 20 |
| 8 | T5 | Mini Bi Pin | S1905 | F8T5/WW | Warm White | 5000 | 400 | 12" | Box | 20 |
| 8 | T5 | Mini Bi Pin | S2906 | F8T5/BL | Blacklight | 5000 | n/a | 12" | Sleeve | 20 |
| 8 | T5 | Mini Bi Pin | S6406 | F8T5/BLB | Blacklight Blue | 5000 | n/a | 12" | Sleeve | 20 |
| 13 | T5 | Mini Bi Pin | S1906 | F13T5/CW | Cool White | 5000 | 860 | 21" | Box | 20 |
| 13 | T5 | Mini Bi Pin | S2911 | F13T5/D | Daylight | 5000 | 780 | 21" | Box | 20 |
| 13 | T5 | Mini Bi Pin | S1907 | F13T5/WW | Warm White | 5000 | 870 | 21" | Box | 20 |

fluorescent lamps

Fluorescent T8 Tubes Preheat



Not Shown Actual Size



F30T8



F18T8



F15T8



F15T8

30 Watt 36"
Medium Bi Pin Base

- S6517** Cool White
- S6518** Daylight
- S6519** Warm White

Packing: 24/Master

T8 Appliance
Medium Bi Pin Base

- S6513** Cool White/24"
- S6514** Cool White/26"
- S6515** Cool White/28"
- S6516** Cool White/30"

Packing: 24/Master

15 Watt 18"
Medium Bi Pin Base

- S6510** Cool White
- S6511** Daylight
- S6512** Warm White
- S6665** Full Spectrum*

Packing: 24/Master
*6/Master

15 Watt 18"
Medium Bi Pin Base

- S6407** Black Light Blue
- S2918** Black Light

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|-------------|-----------------|---------------|------------------|------------------|----------------|----------------|--------|
| 15 | T8 | Med. Bi Pin | S6510 | F15T8/CW | Cool White | 7500 | 850 | 18" | 24 |
| 15 | T8 | Med. Bi Pin | S6511 | F15T8/D | Daylight | 7500 | 750 | 18" | 24 |
| 15 | T8 | Med. Bi Pin | S6512 | F15T8/WW | Warm White | 7500 | 845 | 18" | 24 |
| 15 | T8 | Med. Bi Pin | S6665 | F15T8/SUN | Full Spectrum | 12000 | 600 | 18" | 6 |
| 15 | T8 | Med. Bi Pin | S2918 | F15T8/BL | Black Light | 7500 | n/a | 18" | 25 |
| 15 | T8 | Med. Bi Pin | S6407 | F15T8/BLB | Black Light Blue | 7500 | n/a | 18" | 20 |
| 18 | T8 | Med. Bi Pin | S6513 | F18T8/CW/K/24 | Cool White | 7500 | 1190 | 24" | 24 |
| 18 | T8 | Med. Bi Pin | S6514 | F18T8/CW/K/26 | Cool White | 7500 | 1240 | 26" | 24 |
| 18 | T8 | Med. Bi Pin | S6515 | F18T8/CW/K/28 | Cool White | 7500 | 1240 | 28" | 24 |
| 18 | T8 | Med. Bi Pin | S6516 | F18T8/CW/K/30 | Cool White | 7500 | 1300 | 30" | 24 |
| 30 | T8 | Med. Bi Pin | S6517 | F30T8/CW | Cool White | 7500 | 1380 | 36" | 24 |
| 30 | T8 | Med. Bi Pin | S6518 | F30T8/D | Daylight | 7500 | 2180 | 36" | 24 |
| 30 | T8 | Med. Bi Pin | S6519 | F30T8/WW | Warm White | 7500 | 2150 | 36" | 24 |

fluorescent lamps

T8 Electronic Tubes

20,000 Hours

ENVIRONMENTALLY FRIENDLY SATCO T8 ELECTRONIC

fluorescent lamps are designed to meet the Federal Toxicity Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states*.



- Designed to pass Federal TCLP test*.
- Energy efficient T8 lamp.
- Available in 3000K, 3500K, 4100K, 5000K & 6500K
- 20,000–hours average life time.
- 700 Series lamps equal: 75CRI Good Color Rendition
- 800 Series lamps equal: 80-82 CRI Superior Color Rendition

*Regulations may vary. Check your local and state regulations.

Not Shown Actual Size

700 SERIES

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|-------------|-----------------|---------------|-------------|------------------|----------------|----------------|--------|
| 32 | T8 | Med. Bi Pin | S6617 | F32T8/730/ENV | 3000K 75CRI | 20000 | 2800 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S6618 | F32T8/735/ENV | 3500K 75CRI | 20000 | 2800 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S6619 | F32T8/741/ENV | 4100K 75CRI | 20000 | 2800 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S6694 | F32T8/750/ENV | 5000K 75CRI | 20000 | 2650 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S6695 | F32T6/765/ENV | 6500K 75CRI | 20000 | 2700 | 48" | 30 |

800 SERIES

| | | | | | | | | | |
|----|----|-------------|-------|---------------|-------------|-------|------|-----|----|
| 32 | T8 | Med. Bi Pin | S6401 | F32T8/830/ENV | 3000K 82CRI | 20000 | 2950 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S6402 | F32T8/835/ENV | 3500K 82CRI | 20000 | 2950 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S6403 | F32T8/841/ENV | 4100K 82CRI | 20000 | 2950 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S6404 | F32T8/850/ENV | 5000K 80CRI | 20000 | 2800 | 48" | 30 |

Eco Fluorescent T8 Electronic Tubes



Color Reference Guide:
 730/830 = 3000K Warm White
 735/835 = 3500K Neutral
 741/841 = 4100K Cool White
 750/850 = 5000K Daylight
 765/865 = 6500K Daylight

700 Series lamps equal: 75CRI*
 Good color rendition

800 Series lamps equal: 80-85CRI*
 Superior color rendition

(Color rendering index*)

Not Shown
 Actual Size

| | | |
|-----------------------------------|-----------------------------------|-----------------------------------|
| F32T8 | F25T8 | F17T8 |
| 32 Watt 48" Medium Bi Pin Base | 25 Watt 36" Medium Bi Pin Base | 17 Watt 24" Medium Bi Pin Base |

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Lumens | Length | Carton |
|-------|-----------|-------------|-----------------|----------------|-------------|------------------|--------|--------|--------|
| 17 | T8 | Med. Bi Pin | S6520 | FO17/730/ECO | 3000K 75CRI | 20000 | 1300 | 24" | 30 |
| 17 | T8 | Med. Bi Pin | S6523 | FO17/830/ECO | 3000K 82CRI | 20000 | 1350 | 24" | 30 |
| 17 | T8 | Med. Bi Pin | S6521 | FO17/735/ECO | 3500K 75CRI | 20000 | 1300 | 24" | 30 |
| 17 | T8 | Med. Bi Pin | S6524 | FO17/835/ECO | 3500K 82CRI | 20000 | 1350 | 24" | 30 |
| 17 | T8 | Med. Bi Pin | S6522 | FO17/741/ECO | 4100K 75CRI | 20000 | 1300 | 24" | 30 |
| 17 | T8 | Med. Bi Pin | S6525 | FO17/841/ECO | 4100K 82CRI | 20000 | 1350 | 24" | 30 |
| 17 | T8 | Med. Bi Pin | S2913 | F17T8/SUN | 6280K 95CRI | 14000 | 750 | 24" | 6 |
| 25 | T8 | Med. Bi Pin | S6526 | FO25/730/ECO | 3000K 75CRI | 20000 | 1950 | 36" | 30 |
| 25 | T8 | Med. Bi Pin | S6529 | FO25/830/ECO | 3000K 82CRI | 20000 | 2150 | 36" | 30 |
| 25 | T8 | Med. Bi Pin | S6527 | FO25/735/ECO | 3500K 75CRI | 20000 | 1950 | 36" | 30 |
| 25 | T8 | Med. Bi Pin | S6530 | FO25/835/ECO | 3500K 82CRI | 20000 | 2150 | 36" | 30 |
| 25 | T8 | Med. Bi Pin | S6528 | FO25/741/ECO | 4100K 75CRI | 20000 | 1950 | 36" | 30 |
| 25 | T8 | Med. Bi Pin | S6531 | FO25/841/ECO | 4100K 82CRI | 20000 | 2150 | 36" | 30 |
| 25 | T8 | Med. Bi Pin | S2914 | F25T8/SUN | 6280K 95CRI | 14000 | 1200 | 36" | 6 |
| 32 | T8 | Med. Bi Pin | S6532 | FO32/730/ECO | 3000K 75CRI | 20000 | 2800 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S6535 | FO32/830/ECO | 3000K 82CRI | 20000 | 2950 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S2915 | FO32/830XP/ECO | 3000K 85CRI | 24000 | 3000 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S6533 | FO32/735/ECO | 3500K 75CRI | 20000 | 2800 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S6536 | FO32/835/ECO | 3500K 82CRI | 20000 | 2950 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S2916 | FO32/835XP/ECO | 3500K 85CRI | 24000 | 3000 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S6534 | FO32/741/ECO | 4100K 75CRI | 20000 | 2800 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S6537 | FO32/841/ECO | 4100K 82CRI | 20000 | 2950 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S2917 | FO32/841XP/ECO | 4100K 85CRI | 24000 | 3000 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S2918 | FO32/750/ECO | 5000K 75CRI | 20000 | 2650 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S2919 | FO32/850/ECO | 5000K 80CRI | 20000 | 2800 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S2920 | FO32/850XP/ECO | 5000K 85CRI | 24000 | 3000 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S2921 | FO32/765/ECO | 6500K 75CRI | 20000 | 2700 | 48" | 30 |
| 32 | T8 | Med. Bi Pin | S2922 | F32T8/SUN | 6000K 85CRI | 20000 | 2900 | 48" | 12 |

fluorescent lamps

Fluorescent

T8 Electronic Tubes

700 Series lamps equal: 75CRI*
Good color rendition

800 Series lamps equal: 82CRI*
Superior color rendition

(Color rendering index*)



FO40 5 ft.

40 Watt 60"
Medium Bi Pin Base

"700" Series

S6544 FO40/730

S6545 FO40/735

S6546 FO40/741

"800" Series

S6547 FO40/830

S6548 FO40/835

S6549 FO40/841

Packing: 30/Master

Color Reference Guide:

730/830 = 3000K Warm White

735/835 = 3500K Neutral

741/841 = 4100K Cool White



FO96 8 ft.

59 Watt 96"
Single Pin Base

"700" Series

S6538 FO96/730

S6539 FO96/735

S6540 FO96/741

"800" Series

S6541 FO96/830

S6542 FO96/835

S6543 FO96/841

Packing: 24/Master

Not Shown Actual Size

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|-------------|-----------------|-----------|-------------|------------------|----------------|----------------|--------|
| 40 | T8 | Med. Bi Pin | S6544 | FO40/730 | 3000K 75CRI | 20000 | 3500 | 60" | 30 |
| 40 | T8 | Med. Bi Pin | S6545 | FO40/735 | 3500K 75CRI | 20000 | 3500 | 60" | 30 |
| 40 | T8 | Med. Bi Pin | S6546 | FO40/741 | 4100K 75CRI | 20000 | 3500 | 60" | 30 |
| 40 | T8 | Med. Bi Pin | S6547 | FO40/830 | 3000K 82CRI | 20000 | 3650 | 60" | 30 |
| 40 | T8 | Med. Bi Pin | S6548 | FO40/835 | 3500K 82CRI | 20000 | 3650 | 60" | 30 |
| 40 | T8 | Med. Bi Pin | S6549 | FO40/841 | 4100K 82CRI | 20000 | 3650 | 60" | 30 |
| 59 | T8 | Single Pin | S6538 | FO96/730 | 3000K 75CRI | 15000 | 5700 | 96" | 24 |
| 59 | T8 | Single Pin | S6539 | FO96/735 | 3500K 75CRI | 15000 | 5700 | 96" | 24 |
| 59 | T8 | Single Pin | S6540 | FO96/741 | 4100K 75CRI | 15000 | 5700 | 96" | 24 |
| 59 | T8 | Single Pin | S6541 | FO96/830 | 3000K 82CRI | 15000 | 5900 | 96" | 24 |
| 59 | T8 | Single Pin | S6542 | FO96/835 | 3500K 82CRI | 15000 | 5900 | 96" | 24 |
| 59 | T8 | Single Pin | S6543 | FO96/841 | 4100K 82CRI | 15000 | 5900 | 96" | 24 |

Fluorescent

20,000 Hours **T8 Electronic** U Bend Tubes



700 Series lamps
equal: 75CRI*
Good color
rendition

800 Series lamps
equal: 82CRI*
Superior color
rendition

(Color rendering index*)

Color Reference Guide:

730/830 = 3000K Warm White

735/835 = 3500K Neutral

741/841 = 4100K Cool White



FBO31
1 5/8" Leg Spacing

31 Watt
Medium Bi Pin Base

"800" Series

S6550 FBO31/830

S6551 FBO31/835

S6552 FBO31/841

S2923 FBO31/750

Packing: 15/Master

Not Shown
Actual Size



FBO32/6
6" Leg Spacing

32 Watt
Medium Bi Pin Base

"700" Series

"800" Series

S6553 FBO32/730/6

S6556 FBO32/830/6

S6554 FBO32/735/6

S6557 FBO32/835/6

S6555 FBO32/741/6

S6558 FBO32/841/6

S2924 FBO32/750/6

Packing: 16/Master

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Leg Spacing | Initial Lumens | Nominal Length | Carton |
|-------|-----------|-------------|-----------------|-------------|-------------|------------------|-------------|----------------|----------------|--------|
| 31 | T8 | Med. Bi Pin | S6550 | FBO31/830 | 3000K 82CRI | 20000 | 1 5/8" | 2725 | 22 1/2" | 15 |
| 31 | T8 | Med. Bi Pin | S6551 | FBO31/835 | 3500K 82CRI | 20000 | 1 5/8" | 2725 | 22 1/2" | 15 |
| 31 | T8 | Med. Bi Pin | S6552 | FBO31/841 | 4100K 82CRI | 20000 | 1 5/8" | 2725 | 22 1/2" | 15 |
| 31 | T8 | Med. Bi Pin | S2923 | FBO31/750 | 5000K 75CRI | 20000 | 1 5/8" | 2600 | 22 1/2" | 15 |
| 32 | T8 | Med. Bi Pin | S6553 | FBO32/730/6 | 3000K 75CRI | 20000 | 6" | 2750 | 22 1/2" | 16 |
| 32 | T8 | Med. Bi Pin | S6556 | FBO32/830/6 | 3000K 82CRI | 20000 | 6" | 2850 | 22 1/2" | 16 |
| 32 | T8 | Med. Bi Pin | S6554 | FBO32/735/6 | 3500K 75CRI | 20000 | 6" | 2750 | 22 1/2" | 16 |
| 32 | T8 | Med. Bi Pin | S6557 | FBO32/835/6 | 3500K 82CRI | 20000 | 6" | 2850 | 22 1/2" | 16 |
| 32 | T8 | Med. Bi Pin | S6555 | FBO32/741/6 | 4100K 75CRI | 20000 | 6" | 2750 | 22 1/2" | 16 |
| 32 | T8 | Med. Bi Pin | S6558 | FBO32/841/6 | 4100K 82CRI | 20000 | 6" | 2850 | 22 1/2" | 16 |
| 32 | T8 | Med. Bi Pin | S2924 | FBO32/750/6 | 5000K 75CRI | 20000 | 6" | 2625 | 22 1/2" | 16 |

fluorescent lamps

Fluorescent T12 Tubes Preheat

7500 Hours

fluorescent lamps



F14T12

14 Watt 15"
Medium Bi Pin Base
S6559 Cool White
S6560 Daylight
S6561 Warm White

Packing:
30/Master



F15T12

15 Watt 18"
Medium Bi Pin Base
S6562 Cool White
S6563 Daylight
S6564 Warm White

Packing:
30/Master

Not Shown Actual Size

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|-------------|-----------------|-----------|-------------|------------------|----------------|----------------|--------|
| 14 | T12 | Med. Bi Pin | S6559 | F14T12/CW | Cool White | 7500 | 650 | 15" | 30 |
| 14 | T12 | Med. Bi Pin | S6560 | F14T12/D | Daylight | 7500 | 590 | 15" | 30 |
| 14 | T12 | Med. Bi Pin | S6561 | F14T12/WW | Warm White | 7500 | 660 | 15" | 30 |
| 15 | T12 | Med. Bi Pin | S6562 | F15T12/CW | Cool White | 7500 | 750 | 18" | 30 |
| 15 | T12 | Med. Bi Pin | S6563 | F15T12/D | Daylight | 7500 | 660 | 18" | 30 |
| 15 | T12 | Med. Bi Pin | S6564 | F15T12/WW | Warm White | 7500 | 770 | 18" | 30 |

Fluorescent T12 Tubes

Not Shown Actual Size



F30T12

30 Watt 36"
Rapid Start
Medium Bi Pin Base
S6571 Cool White
S6572 Day Light
S6573 Warm White
S6574 F30T12/D830
S6575 F30T12/D35
S6576 F30T12/D41
S6667 Full Spectrum*
Packing: 30/Master
*6/Master



F25T12

25 Watt
Preheat
Appliance
Medium Bi Pin Base
S6568 Cool White/28"
S6569 Cool White/30"
S6570 Cool White/33"
Packing: 30/Master



F20T12

20 Watt 24"
Preheat
General Purpose
Medium Bi Pin Base
S6565 Cool White
S6566 Daylight
S6567 Warm White
S6666 Full Spectrum*
Packing: 30/Master
6/Master*



**F20T12/F40T12
Blacklights**

20 Watt T12 24"
Preheat
Medium Bi Pin Base
S6408 Blacklight Blue
S2925 Blacklight

40 Watt T12 48"
Rapid Start
Medium Bi Pin Base
S6409 Blacklight Blue*
S2926 Blacklight
Packing: 30/Master
*6/Master

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|-------------|-----------------|----------------|-----------------|------------------|----------------|----------------|--------|
| 20 | T12 | Med. Bi Pin | S6565 | F20T12/CW | Cool White | 9000 | 1220 | 24" | 30 |
| 20 | T12 | Med. Bi Pin | S6566 | F20T12/D | Daylight | 9000 | 1075 | 24" | 30 |
| 20 | T12 | Med. Bi Pin | S6567 | F20T12/WW | Warm White | 9000 | 1250 | 24" | 30 |
| 20 | T12 | Med. Bi Pin | S6666 | F20T12/SUN | Full Spectrum | 14000 | 800 | 24" | 6 |
| 20 | T12 | Med. Bi Pin | S6408 | F20T12/BLB | Blacklight Blue | 9000 | n/a | 24" | 30 |
| 20 | T12 | Med. Bi Pin | S2925 | F20T12/BL | Blacklight | 9000 | n/a | 24" | 30 |
| 25 | T12 | Med. Bi Pin | S6568 | F25T12/CW/28" | Cool White | 7500 | 1670 | 28" | 30 |
| 25 | T12 | Med. Bi Pin | S6569 | F25T12/CW/30" | Cool White | 7500 | 1730 | 30" | 30 |
| 25 | T12 | Med. Bi Pin | S6570 | F25T12/CW/33" | Cool White | 7500 | 1750 | 33" | 30 |
| 30 | T12 | Med. Bi Pin | S6571 | F30T12/CW/RS | Cool White | 18000 | 2200 | 36" | 30 |
| 30 | T12 | Med. Bi Pin | S6572 | F30T12/D/RS | Daylight | 18000 | 1900 | 36" | 30 |
| 30 | T12 | Med. Bi Pin | S6573 | F30T12/WW/RS | Warm White | 18500 | 2275 | 36" | 30 |
| 30 | T12 | Med. Bi Pin | S6574 | F30T12/D830/RS | 3000K 80CRI | 18000 | 2290 | 36" | 30 |
| 30 | T12 | Med. Bi Pin | S6575 | F30T12/D35/RS | 3500K 70CRI | 18000 | 2250 | 36" | 30 |
| 30 | T12 | Med. Bi Pin | S6576 | F30T12/D41/RS | 4100K 70CRI | 18000 | 2250 | 36" | 30 |
| 30 | T12 | Med. Bi Pin | S6667 | F30T12/SUN | Full Spectrum | 22000 | 1650 | 36" | 30 |
| 40 | T12 | Med. Bi Pin | S6409 | F40T12/BLB | Blacklight Blue | 10000 | n/a | 48" | 6 |
| 40 | T12 | Med. Bi Pin | S2926 | F40T12/BL | Blacklight | 10000 | n/a | 48" | 30 |

fluorescent lamps

Fluorescent T12 Tubes

Not Shown Actual Size

F34T12/SS

(Previously F40T12/SS)

34 Watt 48"
Energy Savers
Medium Bi Pin Base

S6600 F34T12/Cool White/SS

S6601 F34T12/Warm White/SS

Designer Series

S6602 F34T12/D30/SS

S6603 F34T12/D35/SS

S6604 F34T12/D41/SS

Designer 800 Series

S6605 F34T12/D830/SS

S6606 F34T12/D835/SS

S6607 F34T12/D841/SS

Color Reference Guide

D30/D830 = 3000K Warm White

D35/D835 = 3500K Neutral

D41/D841 = 4100K Cool White

700 Series lamps equal: 70CRI*
Good color rendition

800 Series lamps equal: 80CRI*
Superior color rendition

(Color rendering index*)

F40T12

40 Watt 48"
Standard Wattage
Medium Bi Pin Base

S2927 F40T12/Cool White Deluxe

S6608 F40T12/Daylight Deluxe

S6609 F40T12/Natural White

S6610 F40T12/Design 50

S6668 F40T12/Full Spectrum

Designer Series

S6611 F40T12/D30

S6612 F40T12/D35

S6613 F40T12/D41

Designer 800 Series

S6614 F40T12/D830

S6615 F40T12/D835

S6616 F40T12/D841

S2928 F40T12/D865

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Lumens | Length | Mst.Ctn./ Inner Pack |
|-------|-----------|-------------|-----------------|-------------|---------------------|------------------|--------|--------|----------------------|
| 34 | T12 | Med. Bi Pin | S6600 | F34/CW/SS | CW 4200K 62CRI | 20000 | 2650 | 48" | 30 |
| 34 | T12 | Med. Bi Pin | S6601 | F34/WW/SS | WW 3000K 52 CRI | 20000 | 2750 | 48" | 30 |
| 34 | T12 | Med. Bi Pin | S6602 | F34/D30/SS | 3000K 70CRI | 20000 | 2800 | 48" | 30 |
| 34 | T12 | Med. Bi Pin | S6605 | F34/D830/SS | 3000K 80CRI | 20000 | 2900 | 48" | 30 |
| 34 | T12 | Med. Bi Pin | S6603 | F34/D35/SS | 3500K 70CRI | 20000 | 2800 | 48" | 30 |
| 34 | T12 | Med. Bi Pin | S6606 | F34/D835/SS | 3500K 80CRI | 20000 | 2900 | 48" | 30 |
| 34 | T12 | Med. Bi Pin | S6604 | F34/D41/SS | 4100K 70CRI | 20000 | 2800 | 48" | 30 |
| 34 | T12 | Med. Bi Pin | S6607 | F34/D841/SS | 4100K 80CRI | 20000 | 2900 | 48" | 30 |
| 40 | T12 | Med. Bi Pin | S2927 | F40CWVX | CW Deluxe 87CRI | 20000 | 2150 | 48" | 30 |
| 40 | T12 | Med. Bi Pin | S6609 | F40N | Natural 3400K 86CRI | 20000 | 2100 | 48" | 30 |
| 40 | T12 | Med. Bi Pin | S6611 | F40/D30 | 3000K 70CRI | 20000 | 3200 | 48" | 30 |
| 40 | T12 | Med. Bi Pin | S6614 | F40/D830 | 3000K 80CRI | 20000 | 3300 | 48" | 30 |
| 40 | T12 | Med. Bi Pin | S6612 | F40/D35 | 3500K 70CRI | 20000 | 3200 | 48" | 30 |
| 40 | T12 | Med. Bi Pin | S6615 | F40/D835 | 3500K 80CRI | 20000 | 3300 | 48" | 30 |
| 40 | T12 | Med. Bi Pin | S6613 | F40/D41 | 4100K 70CRI | 20000 | 3200 | 48" | 30 |
| 40 | T12 | Med. Bi Pin | S6616 | F40/D841 | 4100K 80CRI | 20000 | 3300 | 48" | 30 |
| 40 | T12 | Med. Bi Pin | S6610 | F40/DSGN50 | 5000K 90CRI | 20000 | 2200 | 48" | 30 |
| 40 | T12 | Med. Bi Pin | S6608 | F40/DX | Day 6500K 88CRI | 20000 | 2180 | 48" | 30 |
| 40 | T12 | Med. Bi Pin | S2928 | F40/D865 | 6500K 80CRI | 20000 | 3000 | 48" | 30 |
| 40 | T12 | Med. Bi Pin | S6668 | F40/SUN | Full Spectrum | 26000 | 2100 | 48" | 30 |

Fluorescent

T12 U Bend Tubes

20,000 Hours

FB34/SS

(Previously FB40T12)

34 Watt

Energy Savers
Medium Bi Pin Base

6" Leg Spacing

S6680 FB34/Cool White
S6681 FB34/Warm White

3" Leg Spacing

S6682 FB34/Cool White
S6690 FB34/Warm White

Designer Series

6" Leg Spacing

S6683 FB34/D30/SS
S6684 FB34/D35/SS
S6685 FB34/D41/SS

Packing: 12/Master

Designer series lamps
equal: 70CRI*
Good color rendition
(Color rendering index*)



Not Shown Actual Size

FB40

40 Watt

Standard Wattage
Medium Bi Pin Base

6" Leg Spacing

S6686 FB40/Daylight Deluxe

Designer Series

S6687 FB40/D30/3000K
S6688 FB40/D35/3500K
S6689 FB40/D41/4100K

Packing: 12/Master

Color Reference Guide

D30/D830 = 3000K Warm White
D35/D835 = 3500K Neutral
D41/D841 = 4100K Cool White

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Leg Spacing | Carton |
|-------|-----------|-------------|-----------------|---------------|-----------------|------------------|----------------|----------------|-------------|--------|
| 34 | T12 | Med. Bi Pin | S6680 | FB34/CW/6/SS | Cool White | 18000 | 2600 | 22.5 | 6" | 12 |
| 34 | T12 | Med. Bi Pin | S6681 | FB34/WW/6/SS | Warm White | 18000 | 2650 | 22.5 | 6" | 12 |
| 34 | T12 | Med. Bi Pin | S6683 | FB34/D30/6/SS | 3000K 70CRI | 18000 | 2730 | 22.5 | 6" | 12 |
| 34 | T12 | Med. Bi Pin | S6684 | FB34/D35/6/SS | 3500K 70CRI | 18000 | 2730 | 22.5 | 6" | 12 |
| 34 | T12 | Med. Bi Pin | S6685 | FB34/D41/6/SS | 4100K 70CRI | 18000 | 2730 | 22.5 | 6" | 12 |
| 34 | T12 | Med. Bi Pin | S6682 | FB34/CW/3/EW | Cool White | 18000 | 2350 | 22.5 | 3" | 12 |
| 34 | T12 | Med. Bi Pin | S6690 | FB34/WW/3/EW | Warm White | 18000 | 2425 | 22.5 | 3" | 12 |
| 40 | T12 | Med. Bi Pin | S6686 | FB40/DX/6 | Daylight Deluxe | 18000 | 2300 | 22.5 | 6" | 12 |
| 40 | T12 | Med. Bi Pin | S6687 | FB40/D30/6 | 3000K 70CRI | 18000 | 3050 | 22.5 | 6" | 12 |
| 40 | T12 | Med. Bi Pin | S6688 | FB40/D35/6 | 3500K 70CRI | 18000 | 3050 | 22.5 | 6" | 12 |
| 40 | T12 | Med. Bi Pin | S6689 | FB40/D41/6 | 4100K 70CRI | 18000 | 3050 | 22.5 | 6" | 12 |

Fluorescent *HO T12* Tubes



Not Shown Actual Size

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Inner Pack |
|-------|-----------|---------------|-----------------|------------------|-------------|------------------|----------------|----------------|------------|
| 25 | T12 | Recessed D.C. | S2933 | F18T12/CW/HO | Cool White | 9000 | 1100 | 18" | 30 |
| 25 | T12 | Recessed D.C. | S2934 | F18T12/DSGN50/HO | 5000K 90CRI | 9000 | 850 | 18" | 30 |
| 35 | T12 | Recessed D.C. | S6449 | F24T12/CW/HO | Cool White | 9000 | 1650 | 24" | 30 |
| 35 | T12 | Recessed D.C. | S2935 | F24T12/DSGN50/HO | 5000K 90CRI | 9000 | 1200 | 24" | 30 |
| 35 | T12 | Recessed D.C. | S6450 | F24T12/D/HO | Daylight | 9000 | 1400 | 24" | 30 |
| 42 | T12 | Recessed D.C. | S6451 | F30T12/CW/HO | Cool White | 9000 | 2250 | 30" | 30 |
| 45 | T12 | Recessed D.C. | S6452 | F36T12/CW/HO | Cool White | 9000 | 2850 | 36" | 30 |
| 45 | T12 | Recessed D.C. | S2936 | F36T12/DSGN50/HO | 5000K 90CRI | 9000 | 2100 | 36" | 30 |
| 45 | T12 | Recessed D.C. | S2937 | F36T12/D/HO | Daylight | 9000 | 2500 | 36" | 30 |
| 55 | T12 | Recessed D.C. | S6453 | F42T12/CW/HO | Cool White | 9000 | 3400 | 42" | 30 |
| 55 | T12 | Recessed D.C. | S2938 | F42T12/DSGN50/HO | 5000K 90CRI | 9000 | 2550 | 42" | 30 |
| 55 | T12 | Recessed D.C. | S6454 | F42T12/D/HO | Daylight | 9000 | 3050 | 42" | 30 |
| 60 | T12 | Recessed D.C. | S6670 | F48T12/CW/HO | Cool White | 12000 | 4050 | 48" | 30 |
| 60 | T12 | Recessed D.C. | S2939 | F48T12/DSGN50/HO | 5000K 90CRI | 12000 | 3050 | 48" | 30 |
| 60 | T12 | Recessed D.C. | S2940 | F48T12/D/HO | Daylight | 12000 | 3600 | 48" | 30 |
| 75 | T12 | Recessed D.C. | S6671 | F60T12/CW/HO | Cool White | 12000 | 5200 | 60" | 30 |
| 75 | T12 | Recessed D.C. | S2941 | F60T12/DSGN50/HO | 5000K 90CRI | 12000 | 3850 | 60" | 30 |
| 75 | T12 | Recessed D.C. | S6457 | F60T12/D/HO | Daylight | 12000 | 4600 | 60" | 30 |
| 80 | T12 | Recessed D.C. | S6672 | F64T12/CW/HO | Cool White | 12000 | 5750 | 64" | 30 |
| 80 | T12 | Recessed D.C. | S2942 | F64T12/DSGN50/HO | 5000K 90CRI | 12000 | 4200 | 64" | 30 |
| 80 | T12 | Recessed D.C. | S6458 | F64T12/D/HO | Daylight | 12000 | 4900 | 64" | 30 |

Fluorescent *HO/VHO T12* Tubes



Not Shown Actual Size

fluorescent lamps

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-----------------------------------|-----------|---------------|-----------------|-------------------|-------------|------------------|----------------|----------------|--------|
| High Output (800 MA) | | | | | | | | | |
| 85 | T12 | Recessed D.C. | S6673 | F72T12/CW/HO | Cool White | 12000 | 6250 | 72" | 15 |
| 85 | T12 | Recessed D.C. | S2943 | F72T12/DSGN50/HO | 5000K 90CRI | 12000 | 4600 | 72" | 15 |
| 85 | T12 | Recessed D.C. | S6460 | F72T12/D/HO | Daylight | 12000 | 5550 | 72" | 15 |
| 85 | T12 | Recessed D.C. | S2944 | F72T12/D35/HO | 3500K 70CRI | 12000 | 6650 | 72" | 15 |
| 100 | T12 | Recessed D.C. | S6674 | F84T12/CW/HO | Cool White | 12000 | 7550 | 84" | 15 |
| 100 | T12 | Recessed D.C. | S2945 | F84T12/DSGN50/HO | 5000K 90CRI | 12000 | 5600 | 84" | 15 |
| 100 | T12 | Recessed D.C. | S6461 | F84T12/D/HO | Daylight | 12000 | 6700 | 84" | 15 |
| 95 | T12 | Recessed D.C. | S6675 | F96T12/CW/HO/SS | Cool White | 12000 | 8000 | 96" | 15 |
| 110 | T12 | Recessed D.C. | S6676 | F96T12/CW/HO-COLD | Cool White | 12000 | 8600 | 96" | 15 |
| 110 | T12 | Recessed D.C. | S2946 | F96T12/DSGN50/HO | 5000K 90CRI | 12000 | 6450 | 96" | 15 |
| 110 | T12 | Recessed D.C. | S6462 | F96T12/D/HO-COLD | Daylight | 12000 | 7600 | 96" | 15 |
| 110 | T12 | Recessed D.C. | S2947 | F96T12/D30/HO | 3000K 70CRI | 12000 | 9050 | 96" | 15 |
| 110 | T12 | Recessed D.C. | S2948 | F96T12/D35/HO | 3500K 70CRI | 12000 | 9050 | 96" | 15 |
| 110 | T12 | Recessed D.C. | S2949 | F96T12/D41/HO | 4100K 70CRI | 12000 | 9050 | 96" | 15 |
| Very High Output (1500 MA) | | | | | | | | | |
| 115 | T12 | Recessed D.C. | S6463 | F48T12/CW/VHO | Cool White | 10000 | 6600 | 48" | 30 |
| 135 | T12 | Recessed D.C. | S6465 | F60T12/CW/VHO | Cool White | 10000 | 8700 | 60" | 30 |
| 160 | T12 | Recessed D.C. | S6466 | F72T12/CW/VHO | Cool White | 10000 | 10600 | 72" | 15 |
| 195 | T12 | Recessed D.C. | S6467 | F96T12/CW/VHO/SS | Cool White | 10000 | 13000 | 96" | 15 |
| 215 | T12 | Recessed D.C. | S6677 | F96T12/CW/VHO | Cool White | 10000 | 14000 | 96" | 15 |

Fluorescent *Slimline* Tubes

Slimline Instant Start Lamps



Not Shown Actual Size

| Watts | Bulb Type | Base | Salco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|------------|-----------------|-----------|-------------|------------------|----------------|----------------|--------|
| 25 | T6 | Single Pin | S6471 | F42T6/CW | Cool White | 7500 | 1750 | 42" | 24 |
| 25 | T6 | Single Pin | S2929 | F42T6/D35 | 3500K 70CRI | 7500 | 1830 | 42" | 24 |
| 25 | T6 | Single Pin | S6470 | F42T6/WW | Warm White | 7500 | 1825 | 42" | 24 |
| 38 | T6 | Single Pin | S6475 | F64T6/CW | Cool White | 7500 | 2800 | 64" | 24 |
| 38 | T6 | Single Pin | S6473 | F64T6/WW | Warm White | 7500 | 2900 | 64" | 24 |
| 38 | T8 | Single Pin | S6478 | F72T8/CW | Cool White | 7500 | 3050 | 72" | 24 |
| 38 | T8 | Single Pin | S6477 | F72T8/WW | Warm White | 7500 | 3100 | 72" | 24 |
| 38 | T8 | Single Pin | S6476 | F72T8/D | Daylight | 7500 | 2600 | 72" | 24 |
| 38 | T8 | Single Pin | S2930 | F96T8/CW | Cool White | 7500 | 4000 | 96" | 24 |
| 38 | T8 | Single Pin | S2931 | F96T8/D | Daylight | 7500 | 3550 | 96" | 24 |
| 24 | T12 | Single Pin | S6469 | F24T12/CW | Cool White | 7500 | 1150 | 24" | 30 |
| 30 | T12 | Single Pin | S6472 | F36T12/CW | Cool White | 7500 | 1970 | 36" | 30 |
| 39 | T12 | Single Pin | S6660 | F48T12/CW | Cool White | 9000 | 2875 | 48" | 30 |
| 39 | T12 | Single Pin | S6481 | F48T12/D | Daylight | 9000 | 2450 | 48" | 30 |
| 50 | T12 | Single Pin | S6661 | F60T12/CW | Cool White | 12000 | 3700 | 60" | 30 |
| 50 | T12 | Single Pin | S6483 | F60T12/D | Daylight | 12000 | 3000 | 60" | 30 |
| 52 | T12 | Single Pin | S6662 | F64T12/CW | Cool White | 12000 | 3900 | 64" | 30 |
| 52 | T12 | Single Pin | S6485 | F64T12/D | Daylight | 12000 | 3300 | 64" | 30 |
| 55 | T12 | Single Pin | S6630 | F72T12/CW | Cool White | 12000 | 4500 | 72" | 15 |
| 55 | T12 | Single Pin | S6631 | F72T12/WW | Warm White | 12000 | 4550 | 72" | 15 |
| 55 | T12 | Single Pin | S6632 | F72T12/D | Daylight | 12000 | 3800 | 72" | 15 |
| 70 | T12 | Single Pin | S6663 | F84T12/CW | Cool White | 12000 | 5300 | 84" | 15 |

Fluorescent *Slimline* Tubes



F96T12

Full Wattage
Single Pin Base

S6650 F96T12/Daylight Deluxe

S6651 F96T12/Design 50

Designer Series

S6652 F96T12/D30

S6653 F96T12/D35

S6654 F96T12/D41

Designer 800 Series

S6655 F96T12/D830

S6656 F96T12/D835

S6657 F96T12/D841

S2932 F96T12/D865

Packing: 15/Master

Color Reference Guide
D30/D830 = 3000K Warm White
D35/D835 = 3500K Neutral
D41/D841 = 4100K Cool White

Not Shown Actual Size



F96T12/SS

Energy Savers
Single Pin Base

S6640 F96T12/Cool White/SS

S6641 F96T12/Warm White/SS

Designer Series

S6642 F96T12/D30/SS

S6643 F96T12/D35/SS

S6644 F96T12/D41/SS

Designer 800 Series

S6645 F96T12/D830/SS

S6646 F96T12/D835/SS

S6647 F96T12/D841/SS

700 Series lamps equal: 70CRI*
Good color rendition

800 Series lamps equal: 80CRI*
Superior color rendition

(Color rendering index*)

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|------------|-----------------|----------------|-----------------|------------------|----------------|----------------|--------|
| 60 | T12 | Single Pin | S6640 | F96T12/CW/SS | Cool White | 12000 | 5300 | 96" | 15 |
| 60 | T12 | Single Pin | S6641 | F96T12/WW/SS | Warm White | 12000 | 5500 | 96" | 15 |
| 60 | T12 | Single Pin | S6642 | F96T12/D30/SS | 3000K 70CRI | 12000 | 5600 | 96" | 15 |
| 60 | T12 | Single Pin | S6645 | F96T12/D830/SS | 3000K 80CRI | 12000 | 5800 | 96" | 15 |
| 60 | T12 | Single Pin | S6643 | F96T12/D35/SS | 3500K 70CRI | 12000 | 5600 | 96" | 15 |
| 60 | T12 | Single Pin | S6646 | F96T12/D835/SS | 3500K 80CRI | 12000 | 5800 | 96" | 15 |
| 60 | T12 | Single Pin | S6644 | F96T12/D41/SS | 4100K 70CRI | 12000 | 5600 | 96" | 15 |
| 60 | T12 | Single Pin | S6647 | F96T12/D841/SS | 4100K 80CRI | 12000 | 5800 | 96" | 15 |
| 75 | T12 | Single Pin | S6652 | F96T12/D30 | 3000K 70CRI | 12000 | 6420 | 96" | 15 |
| 75 | T12 | Single Pin | S6655 | F96T12/D830 | 3000K 80CRI | 12000 | 6550 | 96" | 15 |
| 75 | T12 | Single Pin | S6653 | F96T12/D35 | 3500K 70CRI | 12000 | 6420 | 96" | 15 |
| 75 | T12 | Single Pin | S6656 | F96T12/D835 | 3500K 80CRI | 12000 | 6550 | 96" | 15 |
| 75 | T12 | Single Pin | S6654 | F96T12/D41 | 4100K 70CRI | 12000 | 6420 | 96" | 15 |
| 75 | T12 | Single Pin | S6657 | F96T12/D841 | 4100K 80CRI | 12000 | 6550 | 96" | 15 |
| 75 | T12 | Single Pin | S6651 | F96T12/D50 | 5000K 90CRI | 12000 | 4400 | 96" | 15 |
| 75 | T12 | Single Pin | S6650 | F96T12/DX | Daylight Deluxe | 12000 | 4310 | 96" | 15 |
| 75 | T12 | Single Pin | S2932 | F96T12/D865 | 6500K 80CRI | 12000 | 6000 | 96" | 15 |

fluorescent lamps

Fluorescent T9 Circline Tubes



fluorescent lamps



FC6T9/6.5"

20 Watt
4 Pin Base

S6509 Cool White
S2950 Warm White

FC8T9/8"

22 Watt
4 Pin Base

S6500 Cool White
S6501 Daylight
S6502 Warm White

FC12T9/12"

32 Watt
4 Pin Base

S6503 Cool White
S6504 Daylight
S6505 Warm White

FC16T9/16"

40 Watt
4 Pin Base

S6506 Cool White
S2953 Daylight
S2954 Warm White

Packing: 12/Master

Not Shown Actual Size

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Diameter | Carton |
|-------|-----------|-------|-----------------|-----------|-------------|------------------|----------------|----------|--------|
| 20 | T9 | 4 Pin | S6509 | FC6T9/CW | Cool White | 8000 | 750 | 6.5" | 12 |
| 20 | T9 | 4 Pin | S2950 | FC6T9/WW | Warm White | 8000 | 800 | 6.5" | 12 |
| 22 | T9 | 4 Pin | S6500 | FC8T9/CW | Cool White | 11000 | 1050 | 8" | 12 |
| 22 | T9 | 4 Pin | S6501 | FC8T9/D | Daylight | 11000 | 900 | 8" | 12 |
| 22 | T9 | 4 Pin | S6502 | FC8T9/WW | Warm White | 11000 | 1050 | 8" | 12 |
| 32 | T9 | 4 Pin | S6503 | FC12T9/CW | Cool White | 15000 | 1925 | 12" | 12 |
| 32 | T9 | 4 Pin | S6504 | FC12T9/D | Daylight | 15000 | 1650 | 12" | 12 |
| 32 | T9 | 4 Pin | S6505 | FC12T9/WW | Warm White | 15000 | 1950 | 12" | 12 |
| 40 | T9 | 4 Pin | S6506 | FC16T9/CW | Cool White | 18000 | 2750 | 16" | 12 |
| 40 | T9 | 4 Pin | S2953 | FC16T9/D | Daylight | 18000 | 2350 | 16" | 12 |
| 40 | T9 | 4 Pin | S2954 | FC16T9/WW | Warm White | 18000 | 2800 | 16" | 12 |

Fluorescent

Circline T5 Tubes

Tri-Phosphor — Electronic Ballast

12,000 Hours



Not Shown Actual Size

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Color/CRI | Avg. Rated Hours | Initial Lumens | Diameter | Carton |
|-------|-----------|-------|-----------------|--------------|-------------|------------------|----------------|----------|--------|
| 22 | T5 | 2GX13 | S2955 | FPC22/830 | 3000K 82CRI | 12000 | 1800 | 9" | 12 |
| 22 | T5 | 2GX13 | S2956 | FPC22/835 | 3500K 82CRI | 12000 | 1800 | 9" | 12 |
| 22 | T5 | 2GX13 | S2957 | FPC22/841 | 4100K 82CRI | 12000 | 1800 | 9" | 12 |
| 40 | T5 | 2GX13 | S2958 | FPC40/830 | 3000K 82CRI | 12000 | 3200 | 12" | 12 |
| 40 | T5 | 2GX13 | S2959 | FPC40/835 | 3500K 82CRI | 12000 | 3200 | 12" | 12 |
| 40 | T5 | 2GX13 | S2960 | FPC40/841 | 4100K 82CRI | 12000 | 3200 | 12" | 12 |
| 55 | T5 | 2GX13 | S2961 | FPC55/830/HO | 3000K 82CRI | 12000 | 4000 | 12" | 12 |
| 55 | T5 | 2GX13 | S2962 | FPC55/835/HO | 3500K 82CRI | 12000 | 4000 | 12" | 12 |
| 55 | T5 | 2GX13 | S2963 | FPC55/841/HO | 4100K 82CRI | 12000 | 4000 | 12" | 12 |

fluorescent lamps

Shatter Proof Fluorescent Lamps



T6

Single Pin Base
S6591 F42T6/CW/TF
S6692 F64T6/CW/TF
 Packing: 24/Master



T8

Electronic
Medium Bi Pin Base
S6583 FO17/741/TF
S6584 FO25/741/TF
S6585 FO32/741/TF
 Packing: 30/Master



T8

U-Bend
Medium Bi Pin Base
S6594 FBO32/741/6/TF
 Packing: 16/Master

Satco Shatter Proof Lamps feature a special **Kenlon®** coating which effectively contains glass particles should the lamp break. These lamps are perfect in use food storage

preparation, display and sorting tables, hospitals, restaurants and recreation facilities. Special orders are available for large quantities on specific lamp types.

Not Shown Actual Size

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|-------------|-----------------|----------------|-------------|------------------|----------------|----------------|--------|
| 25 | T6 | Single Pin | S6591 | F42T6/CW/TF | Coated | 7500 | 1750 | 42" | 24 |
| 38 | T6 | Single Pin | S6592 | F64T6/CW/TF | Coated | 7500 | 2800 | 64" | 24 |
| 17 | T8 | Med. Bi-Pin | S6583 | FO17/741/TF | Coated | 20000 | 1300 | 24" | 30 |
| 25 | T8 | Med. Bi-Pin | S6584 | FO25/741/TF | Coated | 20000 | 2025 | 36" | 30 |
| 32 | T8 | Med. Bi-Pin | S6585 | FO32/741/TF | Coated | 20000 | 2750 | 48" | 30 |
| 32 | T8 | Med. Bi-Pin | S6594 | FBO32/741/6/TF | Coated | 20000 | 2750 | 22.5" | 16 |

Shatter Proof Fluorescent Lamps



T12

U-Bend Cool White

S6593 FB34CW/6/SS/TF
Packing: 12/Master



T12 Cool White

Medium Bi-Pin Base

S6579 F20T12/CW/TF
S6580 F30T12/CW/TF
S6581 F34/CW/SS/TF
Packing: 30/Master

Single Pin Base

S6586 F48T12/CW/TF
Packing: 30/Master
S6582 F96T12/CW/SS/TF
Packing: 15/Master

Recessed Double Contact Base

S6587 F48T12/CW/HO/TF
S6595 F48T12/CW/VHO/TF
Packing: 30/Master
S6588 F96T12/CW/HO/SS/TF
S6589 F96T12/CW/HO/CT/TF
S6590 F96T12/CW/VHO/TF
Packing: 15/Master

Not Shown Actual Size

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|--------------|-----------------|---------------------------|-------------|------------------|----------------|----------------|--------|
| 20 | T12 | Med. Bi- Pin | S6579 | F20T12/CW/TF | Coated | 9000 | 1220 | 24" | 30 |
| 30 | T12 | Med. Bi- Pin | S6580 | F30T12/CW/TF | Coated | 18000 | 2200 | 36" | 30 |
| 34 | T12 | Med. Bi- Pin | S6581 | F34T12/CW/SS/TF | Coated | 20000 | 2650 | 48" | 30 |
| 39 | T12 | Single Pin | S6586 | F48T12/CW/TF | Coated | 9000 | 2875 | 48" | 30 |
| 60 | T12 | Single Pin | S6587 | F48T12/CW/HO/TF | Coated | 20000 | 4050 | 48" | 30 |
| 115 | T12 | Single Pin | S6595 | F48T12/CW/VHO/LT/TF | Coated | 20000 | 7400 | 48" | 30 |
| 60 | T12 | Single Pin | S6582 | F96T12/CW/SS/TF | Coated | 12000 | 5300 | 96" | 15 |
| 95 | T12 | Rec. D.C. | S6588 | F96T12/CW/HO/SS/TF | Coated | 12000 | 8000 | 96" | 15 |
| 110 | T12 | Rec. D.C. | S6589 | F96T12/CW/HO/COLD TEMP/TF | Coated | 12000 | 8600 | 96" | 15 |
| 215 | T12 | Rec. D.C. | S6590 | F96T12/CW/VHO/TF | Coated | 10000 | 14000 | 96" | 15 |
| 34 | T12 | Med. Bi- Pin | S6593 | FB34/CW/6/SS/TF | Coated | 18000 | 2600 | 22.5" | 12 |

fluorescent lamps

Compact Fluorescent

Twin Tubes **SATCO**[®]

Not Shown Actual Size

10,000 Hours



CFS5

5 Watt
G23 Base

S6300 CFS5W/827

S6301 CFS5W/841

Packing:
50/Master,
Individually Boxed



CFS7

7 Watt
G23 Base

S6302 CFS7W/827

S6303 CFS7W/835

S6304 CFS7W/841

S6305 CFS7W/850

Packing:
50/Master,
Individually Boxed



CFS9

9 Watt
G23 Base

S6306 CFS9W/827

S6307 CFS9W/835

S6308 CFS9W/841

S6309 CFS9W/850

Packing:
50/Master,
Individually Boxed



CFS13

13 Watt
GX23 Base

S6310 CFS13W/827

S6380 CFS13W/830

S6311 CFS13W/835

S6312 CFS13W/841

S6313 CFS13W/850

Packing:
50/Master,
Individually Boxed

SATCO COMPACT FLUORESCENT LAMPS QUALITY • VALUE • PERFORMANCE

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Lumens | Length | Pack. Type | Mst.Ctn./Inner Pack |
|-------|-----------|------|-----------------|------------|-------------|------------------|--------|--------|------------|---------------------|
| 5 | T4 | G23 | S6300 | CFS5W/827 | 2700K 82CRI | 10000 | 230 | 4.2" | Box | 50/5 |
| 5 | T4 | G23 | S6301 | CFS5W/841 | 4100K 82CRI | 10000 | 230 | 4.2" | Box | 50/5 |
| 7 | T4 | G23 | S6302 | CFS7W/827 | 2700K 82CRI | 10000 | 400 | 5.3" | Box | 50/5 |
| 7 | T4 | G23 | S6303 | CFS7W/835 | 3500K 82CRI | 10000 | 400 | 5.3" | Box | 50/5 |
| 7 | T4 | G23 | S6304 | CFS7W/841 | 4100K 82CRI | 10000 | 400 | 5.3" | Box | 50/5 |
| 7 | T4 | G23 | S6305 | CFS7W/850 | 5000K 82CRI | 10000 | 400 | 5.3" | Box | 50/5 |
| 9 | T4 | G23 | S6306 | CFS9W/827 | 2700K 82CRI | 10000 | 580 | 6.5" | Box | 50/5 |
| 9 | T4 | G23 | S6307 | CFS9W/835 | 3500K 82CRI | 10000 | 580 | 6.5" | Box | 50/5 |
| 9 | T4 | G23 | S6308 | CFS9W/841 | 4100K 82CRI | 10000 | 580 | 6.5" | Box | 50/5 |
| 9 | T4 | G23 | S6309 | CFS9W/850 | 5000K 82CRI | 10000 | 580 | 6.5" | Box | 50/5 |
| 13 | T4 | GX23 | S6310 | CFS13W/827 | 2700K 82CRI | 10000 | 800 | 7.1" | Box | 50/5 |
| 13 | T4 | GX23 | S6380 | CFS13W/830 | 3000K 82CRI | 10000 | 800 | 7.1" | Box | 50/5 |
| 13 | T4 | GX23 | S6311 | CFS13W/835 | 3500K 82CRI | 10000 | 800 | 7.1" | Box | 50/5 |
| 13 | T4 | GX23 | S6312 | CFS13W/841 | 4100K 82CRI | 10000 | 800 | 7.1" | Box | 50/5 |
| 13 | T4 | GX23 | S6313 | CFS13W/850 | 5000K 82CRI | 10000 | 800 | 7.1" | Box | 50/5 |

fluorescent lamps



Compact Fluorescent

10000 Hours

Two Pin Quad Tubes

Not Shown
Actual Size



CFD26



CFD18



CFD13



CFD9

26 Watt
G24d-3 2 Pin Base
S6325 CFD26W/827
S6326 CFD26W/830
S6327 CFD26W/835
S6328 CFD26W/841
Packing:
50/Master,
Individually Boxed

18 Watt
G24d-2 2 Pin Base
S6321 CFD18W/827
S6322 CFD18W/830
S6323 CFD18W/835
S6324 CFD18W/841
Packing:
50/Master,
Individually Boxed

13 Watt
GX23-2 2 Pin Base
S6317 CFD13W/827
S6318 CFD13W/830
S6319 CFD13W/835
S6320 CFD13W/841
Packing:
50/Master,
Individually Boxed

9 Watt
G23-2 2 Pin Base
S6314 CFD9W/827
S6315 CFD9W/830
S6316 CFD9W/835
Packing:
50/Master,
Individually Boxed

SATCO COMPACT FLUORESCENT LAMPS QUALITY • VALUE • PERFORMANCE

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Mst.Ctn./ Inner Pack |
|-------|-----------|--------|-----------------|------------|-------------|------------------|----------------|----------------|----------------------|
| 9 | T4 | G23-2 | S6314 | CFD9W/827 | 2700K 82CRI | 10000 | 525 | 4.3" | 50/5 |
| 9 | T4 | G23-2 | S6315 | CFD9W/830 | 3000K 82CRI | 10000 | 525 | 4.3" | 50/5 |
| 9 | T4 | G23-2 | S6316 | CFD9W/835 | 3500K 82CRI | 10000 | 525 | 4.3" | 50/5 |
| 13 | T4 | GX23-2 | S6317 | CFD13W/827 | 2700K 82CRI | 10000 | 780 | 4.6" | 50/5 |
| 13 | T4 | GX23-2 | S6318 | CFD13W/830 | 3000K 82CRI | 10000 | 780 | 4.6" | 50/5 |
| 13 | T4 | GX23-2 | S6319 | CFD13W/835 | 3500K 82CRI | 10000 | 780 | 4.6" | 50/5 |
| 13 | T4 | GX23-2 | S6320 | CFD13W/841 | 4100K 82CRI | 10000 | 780 | 4.6" | 50/5 |
| 18 | T4 | G24D-2 | S6321 | CFD18W/827 | 2700K 82CRI | 10000 | 1250 | 6.0" | 50/5 |
| 18 | T4 | G24D-2 | S6322 | CFD18W/830 | 3000K 82CRI | 10000 | 1250 | 6.0" | 50/5 |
| 18 | T4 | G24D-2 | S6323 | CFD18W/835 | 3500K 82CRI | 10000 | 1250 | 6.0" | 50/5 |
| 18 | T4 | G24D-2 | S6324 | CFD18W/841 | 4100K 82CRI | 10000 | 1250 | 6.0" | 50/5 |
| 26 | T4 | G24D-3 | S6325 | CFD26W/827 | 2700K 82CRI | 10000 | 1825 | 6.8" | 50/5 |
| 26 | T4 | G24D-3 | S6326 | CFD26W/830 | 3000K 82CRI | 10000 | 1825 | 6.8" | 50/5 |
| 26 | T4 | G24D-3 | S6327 | CFD26W/835 | 3500K 82CRI | 10000 | 1825 | 6.8" | 50/5 |
| 26 | T4 | G24D-3 | S6328 | CFD26W/841 | 4100K 82CRI | 10000 | 1825 | 6.8" | 50/5 |

fluorescent lamps

Compact Fluorescent *Four Pin* Electronic



Not Shown Actual Size



CFD13W/4P

13 Watt
G24q-1 4 Pin Base

- S6329** CFD13W/4P/827
- S6330** CFD13W/4P/830
- S6331** CFD13W/4P/835
- S6332** CFD13W/4P/841

Packing:
50/Master,
Individually Boxed



CFD18W/4P

18 Watt
G24q-2 4 Pin Base

- S6333** CFD18W/4P/827
- S6334** CFD18W/4P/830
- S6335** CFD18W/4P/835
- S6336** CFD18W/4P/841

Packing:
50/Master,
Individually Boxed



CFD26W/4P

26 Watt
G24q-3 4 Pin Base

- S6337** CFD26W/4P/827
- S6338** CFD26W/4P/830
- S6339** CFD26W/4P/835
- S6340** CFD26W/4P/841

Packing:
50/Master,
Individually Boxed

SATCO COMPACT FLUORESCENT LAMPS QUALITY • VALUE • PERFORMANCE

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Mst. Ctn./ Inner Pack. |
|-------|-----------|--------|-----------------|---------------|-------------|------------------|----------------|----------------|------------------------|
| 13 | T4 | G24q-1 | S6329 | CFD13W/4P/827 | 2700K 82CRI | 12000 | 900 | 5.2" | 50/5 |
| 13 | T4 | G24q-1 | S6330 | CFD13W/4P/830 | 3000K 82CRI | 12000 | 900 | 5.2" | 50/5 |
| 13 | T4 | G24q-1 | S6331 | CFD13W/4P/835 | 3500K 82CRI | 12000 | 900 | 5.2" | 50/5 |
| 13 | T4 | G24q-1 | S6332 | CFD13W/4P/841 | 4100K 82CRI | 12000 | 900 | 5.2" | 50/5 |
| 18 | T4 | G24q-2 | S6333 | CFD18W/4P/827 | 2700K 82CRI | 12000 | 1250 | 5.8" | 50/5 |
| 18 | T4 | G24q-2 | S6334 | CFD18W/4P/830 | 3000K 82CRI | 12000 | 1250 | 5.8" | 50/5 |
| 18 | T4 | G24q-2 | S6335 | CFD18W/4P/835 | 3500K 82CRI | 12000 | 1250 | 5.8" | 50/5 |
| 18 | T4 | G24q-2 | S6336 | CFD18W/4P/841 | 4100K 82CRI | 12000 | 1250 | 5.8" | 50/5 |
| 26 | T4 | G24q-3 | S6337 | CFD26W/4P/827 | 2700K 82CRI | 12000 | 1825 | 6.5" | 50/5 |
| 26 | T4 | G24q-3 | S6338 | CFD26W/4P/830 | 3000K 82CRI | 12000 | 1825 | 6.5" | 50/5 |
| 26 | T4 | G24q-3 | S6339 | CFD26W/4P/835 | 3500K 82CRI | 12000 | 1825 | 6.5" | 50/5 |
| 26 | T4 | G24q-3 | S6340 | CFD26W/4P/841 | 4100K 82CRI | 12000 | 1825 | 6.5" | 50/5 |

fluorescent lamps



Compact Fluorescent Four Pin Electronic Triple Tube



CFT13W/4P

13 Watt
GX24q-1 4 Pin Base
S6496 CFT13W/4P/830
S6497 CFT13W/4P/835
S6498 CFT13W/4P/841

CFT18W/4P

18 Watt
GX24q-2 4 Pin Base
S6342 CFT18W/4P/830
S6343 CFT18W/4P/835
S6344 CFT18W/4P/841

CFT26W/4P

26 Watt
GX24q-3 4 Pin Base
S6346 CFT26W/4P/830
S6347 CFT26W/4P/835
S6348 CFT26W/4P/841

CFT32W/4P

32 Watt
GX24q-3 4 Pin Base
S6350 CFT32W/4P/830
S6351 CFT32W/4P/835
S6352 CFT32W/4P/841

CFT42W/4P

42 Watt
GX24q-4 4 Pin Base
S6354 CFT42W/4P/830
S6355 CFT42W/4P/835
S6356 CFT42W/4P/841

Not Shown
Actual Size

Packing:
50/Master,
Individually Boxed

SATCO COMPACT FLUORESCENT LAMPS
QUALITY • VALUE • PERFORMANCE

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Lumens | Length | Pack. Type | Mst.Ctn./ Inner Pack |
|-------|-----------|---------|-----------------|---------------|-------------|------------------|--------|--------|------------|----------------------|
| 13 | T4 | GX24Q-1 | S6496 | CFT13W/4P/830 | 3000K 82CRI | 12000 | 900 | 4.2" | Box | 50/5 |
| 13 | T4 | GX24Q-1 | S6497 | CFT13W/4P/835 | 3500K 82CRI | 12000 | 900 | 4.2" | Box | 50/5 |
| 13 | T4 | GX24Q-1 | S6498 | CFT13W/4P/841 | 4100K 82CRI | 12000 | 900 | 4.2" | Box | 50/5 |
| 18 | T4 | GX24q-2 | S6342 | CFT18W/4P/830 | 3000K 82CRI | 12000 | 1200 | 4.4" | Box | 50/5 |
| 18 | T4 | GX24q-2 | S6343 | CFT18W/4P/835 | 3500K 82CRI | 12000 | 1200 | 4.4" | Box | 50/5 |
| 18 | T4 | GX24q-2 | S6344 | CFT18W/4P/841 | 4100K 82CRI | 12000 | 1200 | 4.4" | Box | 50/5 |
| 26 | T4 | GX24q-3 | S6346 | CFT26W/4P/830 | 3000K 82CRI | 12000 | 1800 | 5.0" | Box | 50/5 |
| 26 | T4 | GX24q-3 | S6347 | CFT26W/4P/835 | 3500K 82CRI | 12000 | 1800 | 5.0" | Box | 50/5 |
| 26 | T4 | GX24q-3 | S6348 | CFT26W/4P/841 | 4100K 82CRI | 12000 | 1800 | 5.0" | Box | 50/5 |
| 32 | T4 | GX24q-3 | S6350 | CFT32W/4P/830 | 3000K 82CRI | 12000 | 2400 | 5.6" | Box | 50/5 |
| 32 | T4 | GX24q-3 | S6351 | CFT32W/4P/835 | 3500K 82CRI | 12000 | 2400 | 5.6" | Box | 50/5 |
| 32 | T4 | GX24q-3 | S6352 | CFT32W/4P/841 | 4100K 82CRI | 12000 | 2400 | 5.6" | Box | 50/5 |
| 42 | T4 | GX24q-4 | S6354 | CFT42W/4P/830 | 3000K 82CRI | 12000 | 3200 | 6.5" | Box | 50/5 |
| 42 | T4 | GX24q-4 | S6355 | CFT42W/4P/835 | 3500K 82CRI | 12000 | 3200 | 6.5" | Box | 50/5 |
| 42 | T4 | GX24q-4 | S6356 | CFT42W/4P/841 | 4100K 82CRI | 12000 | 3200 | 6.5" | Box | 50/5 |

fluorescent lamps

Compact Fluorescent *Twin* Tubes

Not Shown Actual Size

10,000 Hours



CF5DS

**5 Watt
G23 Base**

S6700 CF5DS/827
S6701 CF5DS/841

Packing:
50/Master,
Individually Boxed



CF7DS

**7 Watt
G23 Base**

S6702 CF7DS/827
S6703 CF7DS/835
S6704 CF7DS/841
S6705 CF7DS/850

Packing:
50/Master,
Individually Boxed



CF9DS

**9 Watt
G23 Base**

S6706 CF9DS/827
S6707 CF9DS/835
S6708 CF9DS/841
S6709 CF9DS/850

Packing:
50/Master,
Individually Boxed



CF13DS

**13 Watt
GX23 Base**

S6710 CF13DS/827
S6780 CF13DS/830
S6711 CF13DS/835
S6712 CF13DS/841
S6713 CF13DS/850

Packing:
50/Master,
Individually Boxed

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Lumens | Length | Pack. Type | Mst.Ctn./ Inner Pack |
|-------|-----------|------|-----------------|------------|-------------|------------------|--------|--------|------------|----------------------|
| 5 | T4 | G23 | S6700 | CF5DS/827 | 2700K 82CRI | 10000 | 230 | 4.2" | Box | 50 |
| 5 | T4 | G23 | S6701 | CF5DS/841 | 4100K 82CRI | 10000 | 230 | 4.2" | Box | 50 |
| 7 | T4 | G23 | S6702 | CF7DS/827 | 2700K 82CRI | 10000 | 400 | 5.3" | Box | 50 |
| 7 | T4 | G23 | S6703 | CF7DS/835 | 3500K 82CRI | 10000 | 400 | 5.3" | Box | 50 |
| 7 | T4 | G23 | S6704 | CF7DS/841 | 4100K 82CRI | 10000 | 400 | 5.3" | Box | 50 |
| 7 | T4 | G23 | S6705 | CF7DS/850 | 5000K 82CRI | 10000 | 400 | 5.3" | Box | 50 |
| 9 | T4 | G23 | S6706 | CF9DS/827 | 2700K 82CRI | 10000 | 580 | 6.5" | Box | 50 |
| 9 | T4 | G23 | S6707 | CF9DS/835 | 3500K 82CRI | 10000 | 580 | 6.5" | Box | 50 |
| 9 | T4 | G23 | S6708 | CF9DS/841 | 4100K 82CRI | 10000 | 580 | 6.5" | Box | 50 |
| 9 | T4 | G23 | S6709 | CF9DS/850 | 5000K 82CRI | 10000 | 580 | 6.5" | Box | 50 |
| 13 | T4 | GX23 | S6710 | CF13DS/827 | 2700K 82CRI | 10000 | 800 | 7.1" | Box | 50 |
| 13 | T4 | GX23 | S6780 | CF13DS/830 | 3000K 82CRI | 10000 | 800 | 7.1" | Box | 50 |
| 13 | T4 | GX23 | S6711 | CF13DS/835 | 3500K 82CRI | 10000 | 800 | 7.1" | Box | 50 |
| 13 | T4 | GX23 | S6712 | CF13DS/841 | 4100K 82CRI | 10000 | 800 | 7.1" | Box | 50 |
| 13 | T4 | GX23 | S6713 | CF13DS/850 | 5000K 82CRI | 10000 | 800 | 7.1" | Box | 50 |

Compact Fluorescent *Four Pin* Tubes

10,000 Hours

Not Shown Actual Size



CF13DS/E

13 Watt

2G7 4 Pin Base

S6417 CF13DS/E/827

S6418 CF13DS/E/830

S6419 CF13DS/E/841

Packing:

50/Master,

Individually Boxed



CF9DS/E

9 Watt

2G7 4 Pin Base

S6415 CF9DS/E/827

S6416 CF9DS/E/841

Packing:

50/Master,

Individually Boxed



CF7DS/E

7 Watt

2G7 4 Pin Base

S6413 CF7DS/E/827

S6414 CF7DS/E/841

Packing:

50/Master,

Individually Boxed



CF5DS/E

5 Watt

2G7 4 Pin Base

S6411 CF5DS/E/827

S6412 CF5DS/E/841

Packing:

50/Master,

Individually Boxed

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Lumens | Length | Pack. Type | Mst.Ctn./ Inner Pack |
|-------|-----------|------|-----------------|--------------|-------------|------------------|--------|--------|------------|----------------------|
| 5 | T4 | 2G7 | S6411 | CF5DS/E/827 | 2700K 82CRI | 10000 | 230 | 3.4" | Box | 50 |
| 5 | T4 | 2G7 | S6412 | CF5DS/E/841 | 4100K 82CRI | 10000 | 230 | 3.4" | Box | 50 |
| 7 | T4 | 2G7 | S6413 | CF7DS/E/827 | 2700K 82CRI | 10000 | 400 | 4.5" | Box | 50 |
| 7 | T4 | 2G7 | S6414 | CF7DS/E/841 | 4100K 82CRI | 10000 | 400 | 4.5" | Box | 50 |
| 9 | T4 | 2G7 | S6415 | CF9DS/E/827 | 2700K 82CRI | 10000 | 580 | 5.7" | Box | 50 |
| 9 | T4 | 2G7 | S6416 | CF9DS/E/841 | 4100K 82CRI | 10000 | 580 | 5.7" | Box | 50 |
| 13 | T4 | 2GX7 | S6417 | CF13DS/E/827 | 2700K 82CRI | 10000 | 800 | 6.2" | Box | 50 |
| 13 | T4 | 2GX7 | S6418 | CF13DS/E/830 | 3000K 82CRI | 10000 | 800 | 6.2" | Box | 50 |
| 13 | T4 | 2GX7 | S6419 | CF13DS/E/841 | 4100K 82CRI | 10000 | 800 | 6.2" | Box | 50 |

fluorescent lamps

Compact Fluorescent

Two Pin *10,000 Hours* Quad Tubes

Not Shown
Actual Size



CF9DD

9 Watt

G23-2 2 Pin Base

S6714 CF9DD/827

S6715 CF9DD/830

S6716 CF9DD/835

Packing:

50/Master,
Individually Boxed



CF13DD

13 Watt

GX23-2 2 Pin Base

S6717 CF13DD/827

S6718 CF13DD/830

S6719 CF13DD/835

S6720 CF13DD/841

Packing:

50/Master,
Individually Boxed



CF18DD

18 Watt

G24d-2 2 Pin Base

S6721 CF18DD/827

S6722 CF18DD/830

S6723 CF18DD/835

S6724 CF18DD/841

Packing:

50/Master,
Individually Boxed



CF26DD

26 Watt

G24d-3 2 Pin Base

S6725 CF26DD/827

S6726 CF26DD/830

S6727 CF26DD/835

S6728 CF26DD/841

Packing:

50/Master,
Individually Boxed

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|--------|-----------------|------------|-------------|------------------|----------------|----------------|--------|
| 9 | T4 | G23-2 | S6714 | CF9DD/827 | 2700K 82CRI | 10000 | 525 | 4.3" | 50 |
| 9 | T4 | G23-2 | S6715 | CF9DD/830 | 3000K 82CRI | 10000 | 525 | 4.3" | 50 |
| 9 | T4 | G23-2 | S6716 | CF9DD/835 | 3500K 82CRI | 10000 | 525 | 4.3" | 50 |
| 13 | T4 | GX23-2 | S6717 | CF13DD/827 | 2700K 82CRI | 10000 | 780 | 4.6" | 50 |
| 13 | T4 | GX23-2 | S6718 | CF13DD/830 | 3000K 82CRI | 10000 | 780 | 4.6" | 50 |
| 13 | T4 | GX23-2 | S6719 | CF13DD/835 | 3500K 82CRI | 10000 | 780 | 4.6" | 50 |
| 13 | T4 | GX23-2 | S6720 | CF13DD/841 | 4100K 82CRI | 10000 | 780 | 4.6" | 50 |
| 18 | T4 | G24D-2 | S6721 | CF18DD/827 | 2700K 82CRI | 10000 | 1250 | 6.0" | 50 |
| 18 | T4 | G24D-2 | S6722 | CF18DD/830 | 3000K 82CRI | 10000 | 1250 | 6.0" | 50 |
| 18 | T4 | G24D-2 | S6723 | CF18DD/835 | 3500K 82CRI | 10000 | 1250 | 6.0" | 50 |
| 18 | T4 | G24D-2 | S6724 | CF18DD/841 | 4100K 82CRI | 10000 | 1250 | 6.0" | 50 |
| 26 | T4 | G24D-3 | S6725 | CF26DD/827 | 2700K 82CRI | 10000 | 1825 | 6.8" | 50 |
| 26 | T4 | G24D-3 | S6726 | CF26DD/830 | 3000K 82CRI | 10000 | 1825 | 6.8" | 50 |
| 26 | T4 | G24D-3 | S6727 | CF26DD/835 | 3500K 82CRI | 10000 | 1825 | 6.8" | 50 |
| 26 | T4 | G24D-3 | S6728 | CF26DD/841 | 4100K 82CRI | 10000 | 1825 | 6.8" | 50 |

Compact Fluorescent *Four Pin* Electronic

Not Shown Actual Size



CF26DD/E

26 Watt

G24q-3 4 Pin Base

- S6737** CF26DD/E/827
- S6738** CF26DD/E/830
- S6739** CF26DD/E/835
- S6740** CF26DD/E/841

Packing:
50/Master,
Individually Boxed



CF18DD/E

18 Watt

G24q-2 4 Pin Base

- S6733** CF18DD/E/827
- S6734** CF18DD/E/830
- S6735** CF18DD/E/835
- S6736** CF18DD/E/841

Packing:
50/Master,
Individually Boxed



CF13DD/E

13 Watt

G24q-1 4 Pin Base

- S6729** CF13DD/E/827
- S6730** CF13DD/E/830
- S6731** CF13DD/E/835
- S6732** CF13DD/E/841

Packing:
50/Master,
Individually Boxed

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|--------|-----------------|--------------|-------------|------------------|----------------|----------------|--------|
| 13 | T4 | G24q-1 | S6729 | CF13DD/E/827 | 2700K 82CRI | 12000 | 900 | 5.2" | 50 |
| 13 | T4 | G24q-1 | S6730 | CF13DD/E/830 | 3000K 82CRI | 12000 | 900 | 5.2" | 50 |
| 13 | T4 | G24q-1 | S6731 | CF13DD/E/835 | 3500K 82CRI | 12000 | 900 | 5.2" | 50 |
| 13 | T4 | G24q-1 | S6732 | CF13DD/E/841 | 4100K 82CRI | 12000 | 900 | 5.2" | 50 |
| 18 | T4 | G24q-2 | S6733 | CF18DD/E/827 | 2700K 82CRI | 12000 | 1250 | 5.8" | 50 |
| 18 | T4 | G24q-2 | S6734 | CF18DD/E/830 | 3000K 82CRI | 12000 | 1250 | 5.8" | 50 |
| 18 | T4 | G24q-2 | S6735 | CF18DD/E/835 | 3500K 82CRI | 12000 | 1250 | 5.8" | 50 |
| 18 | T4 | G24q-2 | S6736 | CF18DD/E/841 | 4100K 82CRI | 12000 | 1250 | 5.8" | 50 |
| 26 | T4 | G24q-3 | S6737 | CF26DD/E/827 | 2700K 82CRI | 12000 | 1825 | 6.5" | 50 |
| 26 | T4 | G24q-3 | S6738 | CF26DD/E/830 | 3000K 82CRI | 12000 | 1825 | 6.5" | 50 |
| 26 | T4 | G24q-3 | S6739 | CF26DD/E/835 | 3500K 82CRI | 12000 | 1825 | 6.5" | 50 |
| 26 | T4 | G24q-3 | S6740 | CF26DD/E/841 | 4100K 82CRI | 12000 | 1825 | 6.5" | 50 |

fluorescent lamps

Compact Fluorescent

Four Pin Electronic

Triple Tube

Color Reference Guide

827 = 2700K Warm White
 830 = 3000K Soft White
 835 = 3500K Neutral
 841 = 4100K Cool White



CF13DT/E

13 Watt

G24q-1 4 Pin Base

- S4369** CF13DT/E/827
- S4370** CF13DT/E/830
- S4371** CF13DT/E/835
- S4372** CF13DT/E/841

Packing:50/Master,
Individually Boxed



CF18DT/E

18 Watt

GX24q-2 4 Pin Base

- S6741** CF18DT/E/IN/827
- S6742** CF18DT/E/IN/830
- S6743** CF18DT/E/IN/835
- S6744** CF18DT/E/IN/841

Packing:50/Master,
Individually Boxed



CF26DT/E

26 Watt

GX24q-3 4 Pin Base

- S6745** CF26DT/E/IN/827
- S6746** CF26DT/E/IN/830
- S6747** CF26DT/E/IN/835
- S6748** CF26DT/E/IN/841

Packing:50/Master,
Individually Boxed

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|---------|-----------------|-----------------|-------------|------------------|----------------|----------------|--------|
| 13 | T4 | GX24Q-1 | S4369 | CF13DT/E/827 | 2700K 82CRI | 12000 | 900 | 4.2" | 50 |
| 13 | T4 | GX24Q-1 | S4370 | CF13DT/E/830 | 3000K 82CRI | 12000 | 900 | 4.2" | 50 |
| 13 | T4 | GX24Q-1 | S4371 | CF13DT/E/835 | 3500K 82CRI | 12000 | 900 | 4.2" | 50 |
| 13 | T4 | GX24Q-1 | S4372 | CF13DT/E/841 | 4100K 82CRI | 12000 | 900 | 4.2" | 50 |
| 18 | T4 | GX24q-2 | S6741 | CF18DT/E/IN/827 | 2700K 82CRI | 12000 | 1200 | 4.4" | 50 |
| 18 | T4 | GX24q-2 | S6742 | CF18DT/E/IN/830 | 3000K 82CRI | 12000 | 1200 | 4.4" | 50 |
| 18 | T4 | GX24q-2 | S6743 | CF18DT/E/IN/835 | 3500K 82CRI | 12000 | 1200 | 4.4" | 50 |
| 18 | T4 | GX24q-2 | S6744 | CF18DT/E/IN/841 | 4100K 82CRI | 12000 | 1200 | 4.4" | 50 |
| 26 | T4 | GX24q-3 | S6745 | CF26DT/E/IN/827 | 2700K 82CRI | 12000 | 1800 | 5.0" | 50 |
| 26 | T4 | GX24q-3 | S6746 | CF26DT/E/IN/830 | 3000K 82CRI | 12000 | 1800 | 5.0" | 50 |
| 26 | T4 | GX24q-3 | S6747 | CF26DT/E/IN/835 | 3500K 82CRI | 12000 | 1800 | 5.0" | 50 |
| 26 | T4 | GX24q-3 | S6748 | CF26DT/E/IN/841 | 4100K 82CRI | 12000 | 1800 | 5.0" | 50 |

Compact Fluorescent

Four Pin Electronic

Triple Tube

Not Shown Actual Size



CF57DT/E

57 Watt

GX24q-5 4 Pin Base

- S6421** CF57DT/E/IN/827
- S6422** CF57DT/E/IN/830
- S6423** CF57DT/E/IN/835
- S6424** CF57DT/E/IN/841

Packing:
50/Master,
Individually Boxed



CF42DT/E

42 Watt

GX24q-4 4 Pin Base

- S6753** CF42DT/E/IN/827
- S6754** CF42DT/E/IN/830
- S6755** CF42DT/E/IN/835
- S6756** CF42DT/E/IN/841

Packing:
50/Master,
Individually Boxed



CF32DT/E

32 Watt

GX24q-3 4 Pin Base

- S6749** CF32DT/E/IN/827
- S6750** CF32DT/E/IN/830
- S6751** CF32DT/E/IN/835
- S6752** CF32DT/E/IN/841

Packing:
50/Master,
Individually Boxed

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Lumens | Length | Pack. Type | Mst. Ctn./ Inner Pack |
|-------|-----------|---------|-----------------|-----------------|-------------|------------------|--------|--------|------------|-----------------------|
| 32 | T4 | GX24q-3 | S6749 | CF32DT/E/IN/827 | 2700K 82CRI | 12000 | 2400 | 5.6" | Box | 50 |
| 32 | T4 | GX24q-3 | S6750 | CF32DT/E/IN/830 | 3000K 82CRI | 12000 | 2400 | 5.6" | Box | 50 |
| 32 | T4 | GX24q-3 | S6751 | CF32DT/E/IN/835 | 3500K 82CRI | 12000 | 2400 | 5.6" | Box | 50 |
| 32 | T4 | GX24q-3 | S6752 | CF32DT/E/IN/841 | 4100K 82CRI | 12000 | 2400 | 5.6" | Box | 50 |
| 42 | T4 | GX24q-4 | S6753 | CF42DT/E/IN/827 | 2700K 82CRI | 12000 | 3200 | 6.5" | Box | 50 |
| 42 | T4 | GX24q-4 | S6754 | CF42DT/E/IN/830 | 3000K 82CRI | 12000 | 3200 | 6.5" | Box | 50 |
| 42 | T4 | GX24q-4 | S6755 | CF42DT/E/IN/835 | 3500K 82CRI | 12000 | 3200 | 6.5" | Box | 50 |
| 42 | T4 | GX24q-4 | S6756 | CF42DT/E/IN/841 | 4100K 82CRI | 12000 | 3200 | 6.5" | Box | 50 |
| 57 | T4 | GX24q-5 | S6421 | CF57DT/E/IN/827 | 2700K 82CRI | 12000 | 4300 | 7.76" | Box | 50 |
| 57 | T4 | GX24q-5 | S6422 | CF57DT/E/IN/830 | 3000K 82CRI | 12000 | 4300 | 7.76" | Box | 50 |
| 57 | T4 | GX24q-5 | S6423 | CF57DT/E/IN/835 | 3500K 82CRI | 12000 | 4300 | 7.76" | Box | 50 |
| 57 | T4 | GX24q-5 | S6424 | CF57DT/E/IN/841 | 4100K 82CRI | 12000 | 4300 | 7.76" | Box | 50 |

fluorescent lamps

Compact Fluorescent

Long Twin Tube

2G11 Base

fluorescent lamps



18 Watt

S6757 FT18DL/830
S2964 FT18DL/830/RS
S6758 FT18DL/835
S2965 FT18DL/835/RS
S6759 FT18DL/841
S2966 FT18DL/841/RS

40 Watt

S6766 FT40DL/830/RS
S6767 FT40DL/835/RS
S6768 FT40DL/841/RS

24 Watt

S6760 FT24DL/830
S6761 FT24DL/835
S6762 FT24DL/841

50 Watt

S2967 PLL50W/830/RS
S2968 PLL50W/835/RS
S2969 PLL50W/841/RS

36 Watt

S6763 FT36DL/830
S6764 FT36DL/835
S6765 FT36DL/841

55 Watt

S6769 FT55DL/830
S6770 FT55DL/835
S6771 FT55DL/841

Color Reference Guide

830 = 3000K Soft White
 835 = 3500K Neutral
 841 = 4100K Cool White

Not Shown Actual Size

| Watts | Bulb Type | Base | Satco Order No. | Lamp Code | Description | Avg. Rated Hours | Initial Lumens | Nominal Length | Carton |
|-------|-----------|------|-----------------|----------------|-------------|------------------|----------------|----------------|--------|
| 18 | T5 | 2G11 | S6757 | FT18DL/830 | 3000K 82CRI | 12000 | 1250 | 9.0" | 10 |
| 18 | T5 | 2G11 | S2964 | FT18DL/830/RS | 3000K 82CRI | 20000 | 1250 | 10.5" | 10 |
| 18 | T5 | 2G11 | S6758 | FT18DL/835 | 3500K 82CRI | 12000 | 1250 | 9.0" | 10 |
| 18 | T5 | 2G11 | S2965 | FT18DL/835/RS | 3500K 82CRI | 20000 | 1250 | 10.5" | 10 |
| 18 | T5 | 2G11 | S6759 | FT18DL/841 | 4100K 82CRI | 12000 | 1250 | 9.0" | 10 |
| 18 | T5 | 2G11 | S2966 | FT18DL/841/RS | 4100K 82CRI | 20000 | 1250 | 10.5" | 10 |
| 24 | T5 | 2G11 | S6760 | FT24DL/830 | 3000K 82CRI | 12000 | 1800 | 12.9" | 10 |
| 24 | T5 | 2G11 | S6761 | FT24DL/835 | 3500K 82CRI | 12000 | 1800 | 12.9" | 10 |
| 24 | T5 | 2G11 | S6762 | FT24DL/841 | 4100K 82CRI | 12000 | 1800 | 12.9" | 10 |
| 36 | T5 | 2G11 | S6763 | FT36DL/830 | 3000K 82CRI | 12000 | 2900 | 16.6" | 10 |
| 36 | T5 | 2G11 | S6764 | FT36DL/835 | 3500K 82CRI | 12000 | 2900 | 16.6" | 10 |
| 36 | T5 | 2G11 | S6765 | FT36DL/841 | 4100K 82CRI | 12000 | 2900 | 16.6" | 10 |
| 40 | T5 | 2G11 | S6766 | FT40DL/830/RS | 3000K 82CRI | 20000 | 3150 | 22.6" | 10 |
| 40 | T5 | 2G11 | S6767 | FT40DL/835/RS | 3500K 82CRI | 20000 | 3150 | 22.6" | 10 |
| 40 | T5 | 2G11 | S6768 | FT40DL/841/RS | 4100K 82CRI | 20000 | 3150 | 22.6" | 10 |
| 50 | T5 | 2G11 | S2967 | PLL 50W/830/RS | 3000K 82CRI | 14000 | 4300 | 22.5" | 25 |
| 50 | T5 | 2G11 | S2968 | PLL 50W/835/RS | 3500K 82CRI | 14000 | 4300 | 22.5" | 25 |
| 50 | T5 | 2G11 | S2969 | PLL 50W/841/RS | 4100K 82CRI | 14000 | 4300 | 22.5" | 25 |
| 55 | T5 | 2G11 | S6769 | FT55DL/830 | 3000K 82CRI | 12000 | 4800 | 21.1" | 10 |
| 55 | T5 | 2G11 | S6770 | FT55DL/835 | 3500K 82CRI | 12000 | 4800 | 21.1" | 10 |
| 55 | T5 | 2G11 | S6771 | FT55DL/841 | 4100K 82CRI | 12000 | 4800 | 21.1" | 10 |

Compact Fluorescent *Specialty* Tubes



Dulux-T

18 Watt

S4367 CF18DT/827

26 Watt

S4368 CF26DT/827

Packing: 50/Master,
Individually Sleeved

Quad

22 Watt

S6020 FDL22LE/D

S6021 FDL22EX/D

28 Watt

S6022 FDL28LE/D

S6023 FDL28EX/D

Packing: 50/Master,
Individually Sleeved

Dulux-L

18 Watt

S6772 CF18DF/830

S6773 CF18DF/841

24 Watt

S6774 CF24DF/830

S6775 CF24DF/841

36 Watt

S6776 CF36DF/830

S6777 CF36DF/841

Packing: 10/Master,
Individually Sleeved

Color Reference Guide

830 = 3000K Soft White

835 = 3500K Neutral

841 = 4100K Cool White

Not Shown Actual Size

| Watts | Bulb Type | Base | Salco Order No. | Lamp Code | Description | Avg. Rated Hours | Lumens | Length | Pack. Type | Mst. Ctn./ Inner Pack |
|-------|-----------|---------|-----------------|------------|-------------|------------------|--------|--------|------------|-----------------------|
| 22 | T5 | GX32D-2 | S6020 | FDL22LE/D | 2800K 84CRI | 10000 | 1200 | 6.0" | Sleeve | 50 |
| 22 | T5 | GX32D-2 | S6021 | FDL22EX/D | 5000K 84CRI | 10000 | 1200 | 6.0" | Sleeve | 50 |
| 28 | T5 | GX32D-3 | S6022 | FDL28LE/D | 2800K 84CRI | 10000 | 1600 | 6.8" | Sleeve | 50 |
| 28 | T5 | GX32D-3 | S6023 | FDL28EX/D | 5000K 84CRI | 10000 | 1600 | 6.8" | Sleeve | 50 |
| 18 | T4 | GX24D-2 | S4367 | CF18DT/827 | 2700K 82CRI | 12000 | 1200 | 4.8" | Box | 50 |
| 26 | T4 | GX24D-3 | S4368 | CF26DT/827 | 2700K 82CRI | 12000 | 1800 | 5.4" | Box | 50 |
| 18 | T5 | 2G10 | S6772 | CF18DF/830 | 3000K 82CRI | 10000 | 1100 | 4.8" | Sleeve | 10 |
| 18 | T5 | 2G10 | S6773 | CF18DF/841 | 4100K 82CRI | 10000 | 1100 | 4.8" | Sleeve | 10 |
| 24 | T5 | 2G10 | S6774 | CF24DF/830 | 3000K 82CRI | 10000 | 1700 | 6.7" | Sleeve | 10 |
| 24 | T5 | 2G10 | S6775 | CF24DF/841 | 4100K 82CRI | 10000 | 1700 | 6.7" | Sleeve | 10 |
| 36 | T5 | 2G10 | S6776 | CF36DF/830 | 3000K 82CRI | 10000 | 2800 | 8.5" | Sleeve | 10 |
| 36 | T5 | 2G10 | S6777 | CF36DF/841 | 4100K 82CRI | 10000 | 2800 | 8.5" | Sleeve | 10 |

Compact Fluorescent



Mini Spirals

Not Shown Actual Size



Mini Spiral



Mini Spiral
(Candelabra Base)

MINI SPIRALS Their petite size and high lumen output have made this series the CFL of choice. These minis are suitable for many applications such as, table lamps, wall sconces, chandeliers with shades and task lighting with reflectors.

- 2700K, 3000K & 5000K Color Temperatures
- 6000 Hours Lamp Life
- Energy Star Certified*

| Watts | Base | Satco Order No. | Lamp Code | Color Temp. | Avg. Rated Hours | Volts | Lumens | CRI | Length | Mst.Ctn./ Inner Pack |
|-------------|-----------|-----------------|------------|-------------|------------------|-------|--------|-----|--------|----------------------|
| 5 | E26/Med. | S6298 | EFMSP5/27 | 2700K | 10000 | 120 | 250 | 82 | 4.06" | 6/24 Box |
| 9 | E26/Med. | S6200* | EFMSP9/30 | 3000K | 10000 | 120 | 500 | 82 | 4.45" | 6/24 Blister |
| 11 | E26/Med. | S6201* | EFMSP11/30 | 3000K | 6000 | 120 | 550 | 82 | 4.76" | 6/24 Blister |
| 13 | E26/Med. | S6202* | EFMSP13/30 | 3000K | 10000 | 120 | 800 | 82 | 4.96" | 6/24 Blister |
| 15 | E26/Med. | S6203* | EFMSP15/30 | 3000K | 10000 | 120 | 900 | 82 | 4.80" | 6/24 Blister |
| 18 | E26/Med. | S6243* | EFMSP18/30 | 3000K | 10000 | 120 | 1100 | 82 | 5.28" | 6/24 Blister |
| 26 | E26/Med. | S6204 | EFMSP26/30 | 3000K | 10000 | 120 | 1600 | 82 | 5.94" | 6/24 Blister |
| 13 | E26/Med. | S6223 | EFMSP13/50 | 5000K | 10000 | 120 | 800 | 82 | 4.96" | 6/24 Blister |
| 15 | E26/Med. | S6224 | EFMSP15/50 | 5000K | 10000 | 120 | 900 | 82 | 4.80" | 6/24 Blister |
| 26 | E26/Med. | S6225 | EFMSP26/50 | 5000K | 10000 | 120 | 1600 | 82 | 5.94" | 6/24 Blister |
| 5 | E12/Cand. | S6297 | EFMSP5/27 | 2700K | 10000 | 120 | 250 | 82 | 4.13" | 6/24 Box |
| 9 | E12/Cand. | S6251 | EFMSP9/30 | 3000K | 10000 | 120 | 500 | 82 | 4.45" | 6/24 Blister |
| 11 | E12/Cand. | S6252 | EFMSP11/30 | 3000K | 6000 | 120 | 550 | 82 | 4.76" | 6/24 Blister |
| 13 | E12/Cand. | S6253 | EFMSP13/30 | 3000K | 10000 | 120 | 800 | 82 | 4.96" | 6/24 Blister |
| 230V | | | | | | | | | | |
| 13 | E27/Med. | S6247 | EFMSP13/50 | 5000K | 10000 | 230 | 800 | 82 | 4.96" | 6/24 Blister |
| 26 | E27/Med. | S6248 | EFMSP26/50 | 5000K | 10000 | 230 | 1600 | 82 | 5.94" | 6/24 Blister |

*Energy Star Certified



3-Way Spiral



Dimmable Spiral



Standard Spiral

- Dimmable & 3-Way Models
- 3000K & 5000K Color Temperatures
- 6000 Hours Lamp Life
- Energy Star Certified*



STANDARD SPIRALS Our new line of full size spiral lamps now feature a 23 watt dimmable model and our new 12/20/26 watt 3-way CFL. Other choices include lamps available in wattages from 15 to 32 watts in two color temperatures.

| Watts | Base | Satco Order No. | Lamp Code | Color Temp. | Avg. Rated Hours | Volts | Lumens | CRI | Length | Mst.Ctn./ Inner Pack |
|----------|----------|-----------------|-------------------|-------------|------------------|-------|---------------|-----|--------|----------------------|
| 15 | E26/Med. | S6205* | EFSP15/30 | 3000K | 6000 | 120 | 900 | 82 | 5.35" | 6/24 Blister |
| 20 | E26/Med. | S6206* | EFSP20/30 | 3000K | 6000 | 120 | 1200 | 82 | 5.67" | 6/24 Blister |
| 23 | E26/Med. | S6207* | EFSP23/30 | 3000K | 6000 | 120 | 1380 | 82 | 6.02" | 6/24 Blister |
| 26 | E26/Med. | S6209* | EFSP26/30 | 3000K | 6000 | 120 | 1600 | 82 | 6.14" | 6/24 Blister |
| 32 | E26/Med. | S6210* | EFSP32/30 | 3000K | 6000 | 120 | 1920 | 82 | 6.73" | 6/24 Blister |
| 15 | E26/Med. | S6226 | EFSP15/50 | 5000K | 6000 | 120 | 900 | 82 | 5.35" | 6/24 Blister |
| 20 | E26/Med. | S6227 | EFSP20/50 | 5000K | 6000 | 120 | 1200 | 82 | 5.67" | 6/24 Blister |
| 23 | E26/Med. | S6228 | EFSP23/50 | 5000K | 6000 | 120 | 1380 | 82 | 6.02" | 6/24 Blister |
| 26 | E26/Med. | S6229 | EFSP26/50 | 5000K | 6000 | 120 | 1600 | 82 | 6.14" | 6/24 Blister |
| 32 | E26/Med. | S6240 | EFSP32/50 | 5000K | 6000 | 120 | 1920 | 82 | 6.73" | 6/24 Blister |
| 12/20/26 | E26/Med. | S6211* | EFSP12-26/30/3WAY | 3000K | 6000 | 120 | 660/1200/1600 | 82 | 6.02" | 6/24 Blister |
| 23 | E26/Med. | S6212* | EFSP23/30/DIM | 3000K | 6000 | 120 | 1380 | 82 | 6.02" | 6/24 Blister |

*Energy Star Certified

Compact Fluorescent R20 Reflectors



6000 Hours

Not Shown Actual Size



R20

Reflector



R20

Reflector
(Long)

R E F L E C T O R S
Compact, sleek and efficient describe this latest series of energy saving reflectors. Technology has enabled us to develop these 21st century products; their performance and appearance rival their incandescent counterparts.

- 3000K & 5000K Color Temperatures
- 6000 Hours Lamp Life
- Energy Star Certified*



| Watts | Base | Salco Order No. | Lamp Code | Color Temp. | Avg. Rated Hours | Volts | Lumens | CRI | Length | Mst.Ctn./ Inner Pack |
|-------------|----------|-----------------|-------------|-------------|------------------|-------|--------|-----|--------|----------------------|
| 5 | E26/Med. | S6244* | EFR205/30 | 3000K | 6000 | 120 | 260 | 82 | 4.21" | 6/24 Blister |
| 11 | E26/Med. | S6245 | EFR20L11/30 | 3000K | 6000 | 120 | 330 | 82 | 4.96" | 6/24 Blister |
| 230V | | | | | | | | | | |
| 11 | E27/Med. | S6249 | EFR20L11/50 | 5000K | 6000 | 230 | 330 | 82 | 4.96" | 6/24 Blister |

fluorescent lamps



Compact Fluorescent **R30 & BR38** Reflectors

6000 Hours



Not Shown Actual Size

| | | | |
|---------------------|--------------------------|---------------------------|------------------|
| WET LOCATION | BR38 | R30 | R30 |
| | Outdoor Reflector | Dimmable Reflector | Reflector |

REFLECTORS Our new 23 watt PAR38 reflector delivers a high lumen punch of light while being Energy Star certified and U.L. listed for wet location applications. Also new is our "Dimmable" R30 reflector.

- 3000K & 5000K Color Temperatures
- 6000 Hours Lamp Life
- Energy Star Certified*



| Watts | Base | Satco Order No. | Lamp Code | Color Temp. | Avg. Rated Hours | Volts | Lumens | CRI | Length | Mst.Ctn./ Inner Pack |
|-------|----------|-----------------|----------------|-------------|------------------|-------|--------|-----|--------|----------------------|
| 15 | E26/Med. | S6213* | EFR3015/30 | 3000K | 6000 | 120 | 550 | 82 | 5.39" | 6/24 Blister |
| 15 | E26/Med. | S6255* | EFR3015/DIM/30 | 3000K | 6000 | 120 | 525 | 82 | 6.10" | 6/24 Blister |
| 23 | E26/Med. | S6215* | EFPAR3823/30 | 3000K | 6000 | 120 | 960 | 82 | 6.50" | 6/24 Blister |

*Energy Star Certified

fluorescent lamps

Compact Fluorescent



R40 Reflectors

6000 Hours

Not Shown Actual Size



R40

Reflector

R40

Dimmable
Reflector

R E F L E C T O R S
Compact, sleek and efficient describe this latest series of energy saving reflectors.

- 3000K Color Temperatures
- 6000 Hours Lamp Life
- Energy Star Certified*



| Watts | Base | Satco Order No. | Lamp Code | Color Temp. | Avg. Rated Hours | Volts | Lumens | CRI | Length | Mst.Ctn./ Inner Pack |
|-------|----------|-----------------|----------------|-------------|------------------|-------|--------|-----|--------|----------------------|
| 23 | E26/Med. | S6214* | EFR4023/30 | 3000K | 6000 | 120 | 920 | 82 | 6.50" | 6/24 Blister |
| 23 | E26/Med. | S6256 | EFR4023/DIM/30 | 3000K | 6000 | 120 | 920 | 82 | 7.00" | 6/24 Blister |

*Energy Star Certified

fluorescent lamps



Compact Fluorescent

6000 Hours

A Type Household Bulbs



Not Shown Actual Size

| | | | |
|----------------|----------------|----------------|----------------|
| 15W | 11W | 9W | 7W |
| Household Bulb | Household Bulb | Household Bulb | Household Bulb |

A-TYPE BULBS This collection provides an aesthetic value to these functional products. The compact A-type lamp delivers impressive lumen performance for an enclosed lamp.

- 3000K Color Temperatures
- 6000 Hours Lamp Life
- Energy Star Certified*



| Watts | Base | Satco Order No. | Lamp Code | Color Temp. | Avg. Rated Hours | Volts | Lumens | CRI | Length | Mst.Ctn./ Inner Pack |
|-------|----------|-----------------|------------|-------------|------------------|-------|--------|-----|--------|----------------------|
| 7 | E26/Med. | S6233* | EF7A19/30 | 3000K | 6000 | 120 | 300 | 82 | 4.54" | 6/24 Blister |
| 9 | E26/Med. | S6239* | EF9A19/30 | 3000K | 6000 | 120 | 450 | 82 | 4.61" | 6/24 Blister |
| 11 | E26/Med. | S6246* | EF11A19/30 | 3000K | 6000 | 120 | 540 | 82 | 4.96" | 6/24 Blister |
| 15 | E26/Med. | S6216* | EF15A19/30 | 3000K | 6000 | 120 | 720 | 82 | 5.39" | 6/24 Blister |

*Energy Star Certified

fluorescent lamps

Compact Fluorescent Bulbs



fluorescent lamps



- 3000K & 5000K Color Temperatures
- 6000 Hours Lamp Life
- Energy Star Certified*



Not Shown Actual Size

| Watts | Base | Salco Order No. | Lamp Code | Color Temp. | Avg. Rated Hours | Volts | Lumens | CRI | Length | Mst. Ctn./ Inner Pack |
|-------|-----------|-----------------|--------------|-------------|------------------|-------|--------|-----|--------|-----------------------|
| 3 | E12/Cand. | S6219 | EFTOR3/30 | 3000K | 6000 | 120 | 120 | 82 | 4.96" | 6/24 Blister |
| 7 | E12/Cand. | S6220 | EFTOR7/30 | 3000K | 6000 | 120 | 280 | 82 | 4.96" | 6/24 Blister |
| 3 | E26/Med. | S6221 | EFTOR3/30 | 3000K | 6000 | 120 | 120 | 82 | 4.96" | 6/24 Blister |
| 7 | E26/Med. | S6222* | EFTOR7/30 | 3000K | 6000 | 120 | 280 | 82 | 4.96" | 6/24 Blister |
| 15 | E26/Med. | S6217 | EFT15/30 | 3000K | 6000 | 120 | 720 | 82 | 5.51" | 6/24 Blister |
| 15 | E26/Med. | S6241 | EFT15/50 | 5000K | 6000 | 120 | 720 | 82 | 5.51" | 6/24 Blister |
| 15 | E26/Med. | S6218* | EFG15/30 | 3000K | 6000 | 120 | 720 | 82 | 5.39" | 6/24 Blister |
| 15 | E26/Med. | S6242 | EFG15/50 | 5000K | 6000 | 120 | 720 | 82 | 5.39" | 6/24 Blister |
| 15 | E27/Med. | S6250 | EFG15/50/230 | 5000K | 6000 | 230 | 720 | 82 | 5.39" | 6/24 Blister |

*Energy Star Certified



23W
Spiral Bulb

with Dual Photocells



Mini Spiral

Bug Light

| Watts | Base | Satco Order No. | Lamp Code | Color Temp. | Avg. Rated Hours | Volts | Lumens | CRI | Length | Mst.Ctn./ Inner Pack |
|-------|----------|-----------------|-------------------|-------------|------------------|-------|--------|-----|--------|----------------------|
| 15 | E26/Med. | S6254 | EFMSP15/BUG | N/A | 10000 | 120 | N/A | N/A | 4.88" | 6/24 Blister |
| 23 | E26/Med. | S6257 | EF23/SPL/PHOTO/30 | 3000K | 6000 | 120 | 1060 | >75 | 2.5" | 6/24 Blister |

Not Shown Actual Size

Fluorescent *Specialty* Lamps



fluorescent lamps



22W

Circline Style

- 3000K & 6500K Color Temperatures
- 10000 Hours

Not Shown Actual Size

| Watts | Base | Satco Order No. | Lamp Code | Color Temp. | Avg. Rated Hours | Volts | Lumens | CRI | M.O.L. | Mst.Ctn./ Inner Pack |
|-------|----------|-----------------|--------------|-------------|------------------|-------|--------|-----|--------|----------------------|
| 22 | E26/Med. | S6259 | EF/FC8/T9/WW | 3000K | 10000 | 120 | 1060 | 52 | 3" | 6/24 Blister |
| 22 | E26/Med. | S6261 | EF/FC8/T9/D | 6500K | 10000 | 120 | 1060 | 76 | 3" | 6/24 Blister |