

R14 & R16

1500 Hours

Not Shown Actual Size



R14
Intermediate Base
120 Volt
S3205 25 Watt
S3215 40 Watt



R14
E14/Euro. (Mignon) Base
130 Volt
S3396 40 Watt



R16
Medium Base
120 Volt
S3214 40 Watt



Shortneck R14
Medium Base
120 Volt
S3601 25 Watt
S3602 40 Watt



R14
Medium Base
120 Volt
S3604 25 Watt
S3605 40 Watt

Packing:
Individually Boxed
500/Master, 25/Inner

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Finish	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack. Type	Mst.Ctn./Inner Pack
25	R14	Int.	S3205	25R14N	Lt. Frost	120V	1500	135	CC2V	2 5/8"	Box	500/25
25	R14	Med.	S3601	25R14	Lt. Frost	120V	1500	135	CC2V	2 1/4"	Box	500/25
25	R14	Med.	S3604	25R14	Lt. Frost	120V	1500	135	CC2V	2 5/8"	Box	500/25
40	R14	E14/Euro	S3396	40R14	Lt. Frost	130V	1500	280	CC2V	2 5/8"	Box	500/25
40	R14	Int.	S3215	40R14N	Lt. Frost	120V	1500	280	CC2V	2 5/8"	Box	500/25
40	R14	Med.	S3602	40R14	Lt. Frost	120V	1500	280	CC2V	2 1/4"	Box	500/25
40	R14	Med.	S3605	40R14	Lt. Frost	120V	1500	280	CC2V	2 5/8"	Box	500/25
40	R16	Med.	S3214	40R16	Frost	120V	1500	280	C-9	3 7/16"	Box	500/25

R20 & BR25

2000 Hours

Not Shown Actual Size

R20

Medium Base
120 Volt

S3210 30 Watt

S3204 50 Watt

S3211 75 Watt

S3226 100 Watt

S2810 30 Watt/130 Volt

S3804 50 Watt/130 Volt

S2811 75 Watt/130 Volt

Packing:
Individually Sleeved
96/Master
12/Inner



BR25

Medium Base
120 Volt

S2806 65 Watt

S2807 85 Watt

Packing:
Individually Sleeved
96/Master
12/Inner



Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Finish	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack. Type	Mst. Ctn./ Inner Pack
30	R20	Med.	S3210	30R20	Frost	120V	2000	185	CC-9	4"	Sleeve	96/12
30	R20	Med.	S2810	30R20/130	Frost	130V	2000	185	CC-9	4"	Sleeve	96/12
50	R20	Med.	S3204	50R20	Frost	120V	2000	375	CC-9	4"	Sleeve	96/12
50	R20	Med.	S3804	50R20/130	Frost	130V	2000	375	CC-9	4"	Sleeve	96/12
75	R20	Med.	S3211	75R20	Frost	120V	2000	690	CC-9	4"	Sleeve	96/12
75	R20	Med.	S2811	75R20/130	Frost	130V	2000	690	CC-9	4"	Sleeve	96/12
100	R20	Med.	S3226	100R20	Frost	120V	2000	925	CC-9	4"	Sleeve	96/12
65	BR25	Med.	S2806	65BR25/FL	Frost	120V	2000	600	CC-6	4 3/4"	Sleeve	96/12
85	BR25	Med.	S2807	85BR25/FL	Frost	120V	2000	800	CC-6	4 3/4"	Sleeve	96/12

BR30

2000 Hours

Not Shown Actual Size

BR30

Medium Base

S3259 50 Watt

S2808 65 Watt

S3408 65 Watt/130 Volt

S2809 85 Watt

S3409 85 Watt/130 Volt

Packing: Individually Sleeved
96/Master, 12/Inner



Colorful
Multi Pack
Inner Cartons

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Finish	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack Type	Mst.Ctn./ Inner Pack
50	BR30	Med.	S3259	50BR30/FL	Frost	120V	2000	550	CC-9	5 3/8"	Sleeve	96/12
65	BR30	Med.	S2808	65BR30/FL	Frost	120V	2000	685	CC-9	5 3/8"	Sleeve	96/12
65	BR30	Med.	S3408	65BR30/FL	Frost	130V	2000	685	CC-9	5 3/8"	Sleeve	96/12
85	BR30	Med.	S2809	85BR30/FL	Frost	120V	2000	925	CC-9	5 3/8"	Sleeve	96/12
85	BR30	Med.	S3409	85BR30/FL	Frost	130V	2000	925	CC-9	5 3/8"	Sleeve	96/12

2000 Hours

2 Pack **BR30**



Not Shown Actual Size

BR30/2 Pack

Medium Base

S2817 65 Watt

S3417 65 Watt/130 Volt

Packing: 2/Box

60 2-Packs /Master

Sold Per Pack

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Finish	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack. Type	Mst.Ctn.
65	BR30	Med.	S2817	65BR30/FL/2PK	Frost	120V	2000	685	CC-9	5 3/8"	Box/2	60/2
65	BR30	Med.	S3417	65BR30/FL/2PK	Frost	130V	2000	685	CC-9	5 3/8"	Box/2	60/2

BR30

5000 Hours

BR30
 Long Life
 Commercial Grade

Medium Base
 130 Volt

S6208 65 Watt/130 Volt
 Packing: Individually Sleeved
 24/Master



Not Shown Actual Size

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Finish	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack. Type	Mst. Ctn.
65	BR30	Med.	S6208	65BR30/FL/LL	Frost	130V	5000	532	CC-9	5 3/8"	Sleeve	24

2500 Hours

Not Shown Actual Size



LONGER LIFE!



BR40

Medium Base

S2853 65 Watt

S4453 65 Watt/130 Volt

S2854 85 Watt/120-130 Volt

S2855 120 Watt

S4455 120 Watt/130 Volt

Packing: Individually Sleeved
24/Master

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Finish	Avg. Rated		Lumens	Filament	M.O.L.	Pack. Type	Mst.Ctn.
						Volts	Hours					
65	BR40	Med.	S2853	65BR/FL	Frost	120V	2500	685	CC-6	6 1/2"	Sleeve	24
65	BR40	Med.	S4453	65BR/FL	Frost	130V	2500	685	CC-6	6 1/2"	Sleeve	24
85	BR40	Med.	S2854	85BR/FL	Frost	120-130V	2500	925	CC-6	6 1/2"	Sleeve	24
120	BR40	Med.	S2855	120BR/FL	Frost	120V	2500	1150	CC-6	6 1/2"	Sleeve	24
120	BR40	Med.	S4455	120BR/FL	Frost	130V	2500	1150	CC-6	6 1/2"	Sleeve	24

Halogen Reflectors



R20/BR30/BR40

2500 Hours

- Nickel Plated Brass Base
- High Lumen Output
- Brilliant White Light
- Better Color Rendering than Standard Floods
- 20% Brighter & Longer Lasting



reflectors

R20

Medium Base
120 Volt
S4500 50 Watt
Packing: Individually Sleeved
48/Master, 6/Inner

BR30

Medium Base
120 Volt/130Volt
S4501 60 Watt
S4401 60 Watt/130 Volt
S4502 75 Watt
S4402 75 Watt/130 Volt
Packing: Individually Sleeved
48/Master, 6/Inner

BR40

Medium Base
120 Volt
S4504 75 Watt
S4503 100 Watt
Packing: Individually Sleeved
24/Master, 6/Inner

Not Shown Actual Size

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Beam	Volts	Avg. Rated Hours	Lumens	Kelvin	M.O.L.	Pack. Type	Mst. Ctn./ Inner Pack
50	R20	Med.	S4500	50R20/FL/HAL	70°	120V	2500	480	3000K	4"	Sleeve	48/6
60	BR30	Med.	S4501	60BR30/FL/HAL	80°	120V	2500	730	3000K	5 3/8"	Sleeve	48/6
60	BR30	Med.	S4401	60BR30/FL/HAL	80°	130V	2500	730	3000K	5 3/8"	Sleeve	48/6
75	BR30	Med.	S4502	75BR30/FL/HAL	80°	120V	2500	900	3000K	5 3/8"	Sleeve	48/6
75	BR30	Med.	S4402	75BR30/FL/HAL	80°	130V	2500	900	3000K	5 3/8"	Sleeve	48/6
75	BR40	Med.	S4504	75BR40/FL/HAL	90°	120V	2500	900	3000K	6 1/2"	Sleeve	24/6
100	BR40	Med.	S4503	100BR40/FL/HAL	90°	120V	2500	1400	3000K	6 1/2"	Sleeve	24/6

1500 Hours

2 Pack **K19**



Satco **K19** directional reflector lamps are specifically designed to create a soft, glare free light source.

Not Shown Actual Size

Directional Reflectors

White

*Medium Base
120 Volt*

S4976 40 Watt

S4977 60 Watt

S4978 75 Watt

S4979 100 Watt

Packing: 2/Box, 12/2 Packs

Sold Per Pack

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Finish	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack. Type	Mst.Ctn.
40	K19	Med.	S4976	40K19/2PK	White	120	1500	260	C-9	4 1/8"	Box/2	12
60	K19	Med.	S4977	60K19/2PK	White	120	1500	520	C-9	4 1/8"	Box/2	12
75	K19	Med.	S4978	75K19/2PK	White	120	1500	680	C-9	4 1/8"	Box/2	12
100	K19	Med.	S4979	100K19/2PK	White	120	1500	1000	C-9	4 1/8"	Box/2	12

Reflectors *Brass Base*



R20 colors

130 Volt 2000 Hours

Not Shown Actual Size

Medium Base 130 Volt
Packing: Individually Sleeved
96/Master, 12/Inner



S3200 50 Watt Red



S3201 50 Watt Green



S3202 50 Watt Blue



S3203 50 Watt Amber



S3212 50 Watt Pink

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Finish	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack. Type	Mst. Ctn./ Inner Pack
50	R20	Med.	S3200	50R20/R	Red	130	2000	n/a	C-9	4"	Sleeve	96/12
50	R20	Med.	S3201	50R20/G	Green	130	2000	n/a	C-9	4"	Sleeve	96/12
50	R20	Med.	S3202	50R20/B	Blue	130	2000	n/a	C-9	4"	Sleeve	96/12
50	R20	Med.	S3203	50R20/A	Amber	130	2000	n/a	C-9	4"	Sleeve	96/12
50	R20	Med.	S3212	50R20/PK	Pink	130	2000	n/a	C-9	4"	Sleeve	96/12

reflectors

2000 Hours 130 Volt

BR30 colors



S3227 75 Watt Green



S3240 75 Watt Red

Not Shown Actual Size

*Medium Base 130 Volt
Packing: Individually Sleeved
96/Master, 12/Inner*



S3213 75 Watt Pink



S3239 75 Watt Amber



S3228 75 Watt Blue

reflectors

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Finish	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack. Type	Mst.Ctn./ Inner Pack
75	BR30	Med.	S3240	75BR30/R	Red	130	2000	n/a	C-9	5 3/8"	Sleeve	96/12
75	BR30	Med.	S3227	75BR30/G	Green	130	2000	n/a	C-9	5 3/8"	Sleeve	96/12
75	BR30	Med.	S3228	75BR30/B	Blue	130	2000	n/a	C-9	5 3/8"	Sleeve	96/12
75	BR30	Med.	S3239	75BR30/A	Amber	130	2000	n/a	C-9	5 3/8"	Sleeve	96/12
75	BR30	Med.	S3213	75BR30/PK	Pink	130	2000	n/a	C-9	5 3/8"	Sleeve	96/12

Plant Light *Brass Base*



Reflectors

120 Volt / 2000 Hours

Not Shown Actual Size



R20/R25/R30

Plant Lights

Medium Base

120 Volt

S2850 50 Watt/R20

S2851 75 Watt/R25

S2852 150 Watt/R30

Packing: Individually Boxed
96/Master, 12/Inner



Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack. Type	Mst. Ctn./ Inner Pack
50	R20	Med.	S2850	50R20/Plant	120V	2000	n/a	C-9	4"	Box	96/12
75	R25	Med.	S2851	75R25/Plant	120V	2000	n/a	C-9	4 3/4"	Box	96/12
150	R30	Med.	S2852	150R30/Plant	120V	2000	n/a	C-9	5 3/8"	Box	96/12

reflectors

2000 Hours

ER30 & ER40

Elliptical Reflectors produce more useable light beyond the lamp surface. They are perfect for use in deeply recessed fixtures.



ER30

Elliptical

Medium Base

130 Volt

S4956 50 Watt

S4957 75 Watt

Packing:

Individually Sleeved
24/Case

ER40

Elliptical

Medium Base

130 Volt

S4958 120 Watt

Packing:

Individually Sleeved
24/Case

Not Shown

Actual Size

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Finish	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack. Type	Mst.Ctn.
50	ER30	Med.	S4956	50ER30	Frost	130V	2000	310	CC6	6 1/8"	Sleeve	24
75	ER30	Med.	S4957	75ER30	Frost	130V	2000	620	CC6	6 1/8"	Sleeve	24
120	ER40	Med.	S4958	120ER40	Frost	130V	2000	1180	CC6	7 1/4"	Sleeve	24

Reflectors *Brass Base*



BR38 Weatherproof

2000 Hours

BR38 Medium Base
120 Volt /130 Volt

S4420 75 Watt

S4430 75 Watt/130 Volt

S4421 150 Watt

S4431 150 Watt/130 Volt

Packing: Individually Boxed
12/Master

S4422 75 Watt (2 Pack)

S4423 150 Watt (2 Pack)

Packing: 2 per Box

8 2pk/Master

Sold Per Pack



Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Finish	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack. Type	Mst.Ctn.
75	BR38	Med.	S4420	75BR38/FL	Clear	120V	2000	700	CC9	5 5/16"	Box	12
75	BR38	Med.	S4430	75BR38/FL	Clear	130V	2000	700	CC9	5 5/16"	Box	12
75	BR38	Med.	S4422	75BR38/FL/2PK	Clear	120V	2000	700	CC9	5 5/16"	Box/2	8
150	BR38	Med.	S4421	150BR38/FL	Clear	120V	2000	1550	CC9	5 5/16"	Box	12
150	BR38	Med.	S4431	150BR38/FL	Clear	130V	2000	1550	CC9	5 5/16"	Box	12
150	BR38	Med.	S4423	150BR38/FL/2PK	Clear	120V	2000	1550	CC9	5 5/16"	Box/2	8

2000 Hours

BR38 Weatherproof



S4424 100 Watt Red



S4425 100 Watt Amber

**BR38
Colors**

Medium Base
120 Volt
Packing:
Individually Boxed
6/Master



S4426 100 Watt Yellow



S4427 100 Watt Green



S4428 100 Watt Blue



S4429 100 Watt Pink

*Not Shown
Actual Size*

reflectors

Watts	Bulb Type	Base	Salco Order No.	Lamp Code	Finish	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack. Type	Mst. Ctn.
100	BR38	Med.	S4424	100BR38/R	Red	120V	2000	n/a	CC9	5 5/16"	Box	6
100	BR38	Med.	S4425	100BR38/A	Amber	120V	2000	n/a	CC9	5 5/16"	Box	6
100	BR38	Med.	S4426	100BR38/Y	Yellow	120V	2000	n/a	CC9	5 5/16"	Box	6
100	BR38	Med.	S4427	100BR38/G	Green	120V	2000	n/a	CC9	5 5/16"	Box	6
100	BR38	Med.	S4428	100BR38/B	Blue	120V	2000	n/a	CC9	5 5/16"	Box	6
100	BR38	Med.	S4429	100BR38/PK	Pink	120V	2000	n/a	CC9	5 5/16"	Box	6

Heat lamps

5000 Hours



R40/Clear

Infrared Heat Lamp

Medium Base (120 Volt)

S4999 250 Watt Clear

Packing: Individually Sleeved, 12/Master



R40/Red

Infrared Heat Lamp

Medium Base (120 Volt)

S4998 250 Watt Red

Packing: Individually Sleeved, 12/Master



BR38/Red

Infrared Heat Lamp

Medium Base (120 Volt)

S4751 175 Watt Red

Packing: Individually Boxed, 12/Master



R40/Clear

Infrared Heat Lamp

Medium Base (120 Volt)

S4750 125 Watt Clear

Packing: Individually Boxed, 12/Master

Not Shown Actual Size

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Finish	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack. Type	Mst. Ctn.
125	R40	Med.	S4750	125R40/1	Clear	120V	5000	n/a	C-9	6 1/2"	Box	12
175	BR38	Med.	S4751	175BR38/HR	Red	120V	5000	n/a	C-9	5 5/16"	Box	12
250	R40	Med.	S4999	250R40/1	Clear	120V	5000	n/a	C-9	6 1/2"	Sleeve	12
250	R40	Med.	S4998	250R40/HR	Red	120V	5000	n/a	C-9	6 1/2"	Sleeve	12

Brass Base Reflectors

PAR38

2 Piece Construction

Weatherproof



Shown Actual Size

PAR38

Medium Base,
2 Piece Construction

S4952 65 Watt Flood

S4953 65 Watt Flood/130 Volt

S4951 65 Watt Spot

S4954 150 Watt Flood/130 Volt

S4955 150 Watt Spot/130 Volt

Packing: Individually Boxed
15/Master

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Beam	Volts	Avg. Rated Hours	Lumens	CBCP	Filament	M.O.L.	Pack. Type	Mst.Ctn.
65	PAR38	Med. Skt.	S4952	65PAR/FL	Flood 30°	120V	1750	715	1700	CC-6	5 5/16"	Box	15
65	PAR38	Med. Skt.	S4953	65PAR/FL/130	Flood 30°	130V	1750	715	1700	CC-6	5 5/16"	Box	15
65	PAR38	Med. Skt.	S4951	65PAR/SP	Spot 12°	120V	1750	715	5500	CC-6	5 5/16"	Box	15
150	PAR38	Med. Skt.	S4954	150PAR/FL/130	Flood 30°	130V	750	2175	4500	CC-6	5 5/16"	Box	15
150	PAR38	Med. Skt.	S4955	150PAR/SP/130	Spot 12°	130V	750	2175	18000	CC-6	5 5/16"	Box	15

130 VOLT BULB SPECIFICATIONS ON 120 VOLT LINE

57	PAR38	Med. Skt.	S4953	65PAR/FL/130	Flood 30°	130V	4375	540	1285	CC-6	5 5/16"	Box	15
132	PAR38	Med. Skt.	S4954	150PAR/FL/130	Flood 30°	130V	1875	1660	3435	CC-6	5 5/16"	Box	15
132	PAR38	Med. Skt.	S4955	150PAR/SP/130	Spot 12°	130V	1875	1660	13735	CC-6	5 5/16"	Box	15

PAR Reflectors

PAR36/PAR38/PAR56

Not Shown Actual Size



PAR38 Side Prong

2 Piece Construction

- Side Prong Base,
- S4800** 75 Watt Flood
- S4801** 75 Watt Spot
- S4675*** 90 Watt Halogen Flood
- S4674*** 90 Watt Halogen Spot
- S4802** 150 Watt Flood
- S4803** 150 Watt Spot

Packing: Individually Boxed
12/Master
*15/Master



PAR36 12 Volt Screw Terminal

INCANDESCENT

- S4804** 50 Watt PAR36 Wide Flood
- S4805** 50 Watt PAR36 Narrow Spot

HALOGEN

- S4809** 36 Watt PAR36 Wide Flood
- S4808** 36 Watt PAR36 Narrow Spot
- S4807** 36 Watt PAR36 Very Narrow Spot
- S4806** 50 Watt PAR36 Narrow Spot

Packing: Individually Boxed
12/Master

PAR56 120 Volt Mogul Side Prong

INCANDESCENT

- S4810** 300 Watt PAR56 Medium Flood
- S4811** 300 Watt PAR56 Wide Flood
- S4963** 300 Watt PAR56 Narrow Spot

Packing: Individually Boxed
12/Master

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Beam	Volts	Avg. Rated Hours	CBCP	Lumens	Filament	M.O.L.	Pack. Type	Mst.Ctn.
75	PAR38	Side Prong	S4800	75PAR/3FL/MINE	Flood 30°	120V	2000	1750	765	CC-6	4 5/16"	Box	12
75	PAR38	Side Prong	S4801	75PAR/3SP/MINE	Spot 15°	120V	2000	5900	765	CC-6	4 5/16"	Box	12
90	PAR38	Side Prong	S4675	90PAR/CAP/3FL	Flood 30°	120V	2500	3500	1310	CC-8	4 5/16"	Box	15
90	PAR38	Side Prong	S4674	90PAR/CAP/3SP	Spot 12°	120V	2500	14300	1310	CC-8	4 5/16"	Box	15
150	PAR38	Side Prong	S4802	150PAR/3FL/MINE	Flood 30°	120V	2000	3600	1740	CC-6	4 5/16"	Box	12
150	PAR38	Side Prong	S4803	150PAR/3SP/MINE	Spot 18°	120V	2000	9200	1740	CC-6	4 5/16"	Box	12
50	PAR36	Screw Term.	S4804	50PAR36/WFL	Flood 35°	12V	2000	720	330	C-6	2 3/4"	Box	12
50	PAR36	Screw Term.	S4805	50PAR36/NSP	Spot 8°	12V	2000	11000	330	C-6	2 3/4"	Box	12
36	PAR36	Screw Term.	S4809	36PAR36/CAP/WFL	Flood 32°	12V	4000	1000	500	C-8	2 3/4"	Box	12
36	PAR36	Screw Term.	S4808	36PAR36/CAP/NSP	Spot 13°	12V	4000	3500	500	C-8	2 3/4"	Box	12
36	PAR36	Screw Term.	S4807	36PAR36/CAP/VNSP	Spot 5°	12V	4000	17000	500	C-8	2 3/4"	Box	12
50	PAR36	Screw Term.	S4806	50PAR36/CAP/NSP6	Spot 6°	12V	4000	25000	700	C-8	2 3/4"	Box	12
300	PAR56	Mog End Prong	S4810	300PAR56/MFL	Flood 23°	120V	2000	24000	3840	CC-13	5"	Box	12
300	PAR56	Mog End Prong	S4811	300PAR56/WFL	Flood 37°	120V	2000	11000	3840	CC-13	5"	Box	12
300	PAR36	Mog End Prong	S4963	300PAR56/NSP	Spot 10°	120V	2000	68000	3840	CC-13	5"	Box	12

Not Shown Actual Size

PAR16/PAR20/PAR30/PAR38

Frosted Halogen Lamps

S O F T - R A Y

Introducing - Soft Ray, a new concept in halogen lighting. Our new line of frosted MR16 and PAR lamps offer a simple, cost effective solution to problems normally associated with standard halogen reflectors.

It is known that many users of traditional MR16 & PAR lamps object to the "headlamp look" or glare appearance of these lamps. Soft Ray lamps solve these problems and more!

- Glare Free
- Does not create hot spots
- Eliminates shadows & striations
- Produces a smooth and even beam pattern



PAR16



PAR20



PAR30 Short Neck



PAR30 Long Neck



PAR38

Not Shown Actual Size

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Beam	Volts	Avg. Rated Hours	Lumens	Filament	M.O.L.	Pack. Type	Mst. Ctn.
60	PAR16	Med.	S4108	60PAR16/FL/FROST	Flood 38°	120V	2500	525	CC-8	3 3/16"	Box	15
75	PAR16	Med.	S4109	75PAR16/FL/FROST	Flood 38°	120V	2500	725	CC-8	3 3/8"	Box	15
50	PAR20	Med.	S4100	50PAR20/NFL/FROST	Flood 38°	120V	2500	450	CC-8	3 3/8"	Box	15
50	PAR20	Med.	S4200	50PAR20/NFL/FROST	Flood 38°	130V	2500	450	CC-8	3 3/8"	Box	15
50	PAR30	Med.	S4101	50PAR30/FL/FROST	Flood 38°	120V	2500	520	CC-8	3 5/8"	Box	15
50	PAR30	Med.	S4201	50PAR30/FL/FROST	Flood 38°	130V	2500	520	CC-8	3 5/8"	Box	15
75	PAR30	Med.	S4102	75PAR30/FL/FROST	Flood 38°	120V	2500	900	CC-8	3 5/8"	Box	15
75	PAR30	Med.	S4202	75PAR30/FL/FROST	Flood 38°	130V	2500	900	CC-8	5 5/16"	Box	15
50	PAR30/LN	Med.	S4103	50PAR30/LN/FL/FROST	Flood 38°	120V	2500	520	CC-8	4 1/2"	Box	15
50	PAR30/LN	Med.	S4203	50PAR30/LN/FL/FROST	Flood 38°	130V	2500	520	CC-8	4 1/2"	Box	15
75	PAR30/LN	Med.	S4104	75PAR30/LN/FL/FROST	Flood 38°	120V	2500	900	CC-8	4 1/2"	Box	15
75	PAR30/LN	Med.	S4204	75PAR30/LN/FL/FROST	Flood 38°	130V	2500	900	CC-8	4 1/2"	Box	15
45	PAR38	Med. Skt.	S4105	45PAR38/FL/FROST	Flood 38°	120V	2500	450	CC-8	5 5/16"	Box	15
45	PAR38	Med. Skt.	S4205	45PAR38/FL/FROST	Flood 38°	130V	2500	450	CC-8	5 5/16"	Box	15
60	PAR38	Med. Skt.	S4106	60PAR38/FL/FROST	Flood 38°	120V	2500	600	CC-8	5 5/16"	Box	15
60	PAR38	Med. Skt.	S4206	60PAR38/FL/FROST	Flood 38°	130V	2500	600	CC-8	5 5/16"	Box	15
90	PAR38	Med. Skt.	S4107	90PAR38/FL/FROST	Flood 38°	120V	2500	1150	CC-8	5 5/16"	Box	15
90	PAR38	Med. Skt.	S4207	90PAR38/FL/FROST	Flood 38°	130V	2500	1150	CC-8	5 5/16"	Box	15

PAR16/PAR20/PAR30

Whiter light, brighter colors, precise beam control.

Not Shown Actual Size



PAR16

PAR20

PAR30

SATCO PAR HALOGEN LAMPS QUALITY • VALUE • PERFORMANCE

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Beam	Avg. Rated			Filament	M.O.L.	Pack. Type	Mst. Ctn.
						Volts	Hours	CBCP				
45	PAR16	Med.	S2200	45PAR16/HAL/NFL	NFL 30°	120V	2500	1200	420	CC-8	3 3/16"	Box 15
45	PAR16	Med.	S2300	45PAR16/HAL/NFL	NFL 30°	130V	2500	1200	420	CC-8	3 3/16"	Box 15
60	PAR16	Med.	S2201	60PAR16/HAL/NFL	NFL 30°	120V	2500	1400	600	CC-8	3 3/16"	Box 15
60	PAR16	Med.	S2301	60PAR16/HAL/NFL	NFL 30°	130V	2500	1400	600	CC-8	3 3/16"	Box 15
60	PAR16	Med.	S2202	60PAR16/HAL/NSP	NSP 10°	120V	2500	4700	550	CC-8	3 3/16"	Box 15
60	PAR16	Med.	S2302	60PAR16/HAL/NSP	NSP 10°	130V	2500	4700	550	CC-8	3 3/16"	Box 15
75	PAR16	Med.	S2203	75PAR16/HAL/NFL	NFL 30°	120V	2500	1800	850	CC-8	3 3/16"	Box 15
75	PAR16	Med.	S2303	75PAR16/HAL/NFL	NFL 30°	130V	2500	1800	850	CC-8	3 3/16"	Box 15
75	PAR16	Med.	S2204	75PAR16/HAL/NSP	NSP 10°	120V	2500	7000	850	CC-8	3 3/16"	Box 15
75	PAR16	Med.	S2304	75PAR16/HAL/NSP	NSP 10°	130V	2500	7000	850	CC-8	3 3/16"	Box 15
50	PAR20	Med.	S2205	50PAR20/HAL/NFL	NFL 34°	120V	2500	1300	495	CC-8	3 1/4"	Box 15
50	PAR20	Med.	S2305	50PAR20/HAL/NFL	NFL 34°	130V	2500	1300	495	CC-8	3 1/4"	Box 15
50	PAR20	Med.	S2206	50PAR20/HAL/NSP	NSP 10°	120V	2500	4700	495	CC-8	3 1/4"	Box 15
50	PAR20	Med.	S2306	50PAR20/HAL/NSP	NSP 10°	130V	2500	4700	495	CC-8	3 1/4"	Box 15
50	PAR30	Med.	S2207	50PAR30/HAL/NFL	NFL 34°	120V	2500	1750	560	CC-8	3 5/8"	Box 15
50	PAR30	Med.	S2307	50PAR30/HAL/NFL	NFL 34°	130V	2500	1750	560	CC-8	3 5/8"	Box 15
50	PAR30	Med.	S2208	50PAR30/HAL/WFL	WFL 50°	120V	2500	460	560	CC-8	3 5/8"	Box 15
50	PAR30	Med.	S2308	50PAR30/HAL/WFL	WFL 50°	130V	2500	460	560	CC-8	3 5/8"	Box 15
50	PAR30	Med.	S2209	50PAR30/HAL/NSP	NSP 9°	120V	2500	7600	560	CC-8	3 5/8"	Box 15
50	PAR30	Med.	S2309	50PAR30/HAL/NSP	NSP 9°	130V	2500	7600	56+0	CC-8	3 5/8"	Box 15
75	PAR30	Med.	S2210	75PAR30/HAL/NFL	NFL 34°	120V	2500	3100	945	CC-8	3 5/8"	Box 15
75	PAR30	Med.	S2310	75PAR30/HAL/NFL	NFL 34°	130V	2500	3100	945	CC-8	3 5/8"	Box 15
75	PAR30	Med.	S2211	75PAR30/HAL/WFL	WFL 50°	120V	2500	770	945	CC-8	3 5/8"	Box 15
75	PAR30	Med.	S2311	75PAR30/HAL/WFL	WFL 50°	130V	2500	770	945	CC-8	3 5/8"	Box 15
75	PAR30	Med.	S2212	75PAR30/HAL/NSP	NSP 9°	120V	2500	13000	945	CC-8	3 5/8"	Box 15
75	PAR30	Med.	S2312	75PAR30/HAL/NSP	NSP 9°	130V	2500	13000	945	CC-8	3 5/8"	Box 15

Not Shown Actual Size



PAR38

PAR30LN

SATCO PAR HALOGEN LAMPS

QUALITY • VALUE • PERFORMANCE

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Beam	Avg. Rated				Filament	M.O.L.	Pack Type	Mst. Ctn.
						Volts	Hours	CBCP*	Lumens				
50	PAR30/LN	Med.	S2213	50PAR30/HAL/NFL	NFL 34°	120V	2500	1750	560	CC-8	4 1/2"	Box	15
50	PAR30/LN	Med.	S2313	50PAR30/HAL/NFL	NFL 34°	130V	2500	1750	560	CC-8	4 1/2"	Box	15
50	PAR30/LN	Med.	S2214	50PAR30/HAL/WFL	WFL 50°	120V	2500	460	560	CC-8	4 1/2"	Box	15
50	PAR30/LN	Med.	S2314	50PAR30/HAL/WFL	WFL 50°	130V	2500	460	560	CC-8	4 1/2"	Box	15
50	PAR30/LN	Med.	S2215	50PAR30/HAL/NSP	NSP 9°	120V	2500	7600	550	CC-8	4 1/2"	Box	15
50	PAR30/LN	Med.	S2315	50PAR30/HAL/NSP	NSP 9°	130V	2500	7600	550	CC-8	4 1/2"	Box	15
75	PAR30/LN	Med.	S2216	75PAR30/HAL/NFL	NFL 34°	120V	2500	3100	945	CC-8	4 1/2"	Box	15
75	PAR30/LN	Med.	S2316	75PAR30/HAL/NFL	NFL 34°	130V	2500	3100	945	CC-8	4 1/2"	Box	15
75	PAR30/LN	Med.	S2217	75PAR30/HAL/WFL	WFL 50°	120V	2500	770	945	CC-8	4 1/2"	Box	15
75	PAR30/LN	Med.	S2317	75PAR30/HAL/WFL	WFL 50°	130V	2500	770	945	CC-8	4 1/2"	Box	15
75	PAR30/LN	Med.	S2218	75PAR30/HAL/NSP	NSP 9°	120V	2500	13000	945	CC-8	4 1/2"	Box	15
75	PAR30/LN	Med.	S2318	75PAR30/HAL/NSP	NSP 9°	130V	2500	13000	945	CC-8	4 1/2"	Box	15
45	PAR38	Med.	S2219	45PAR38/HAL/FL	FL 30°	120V	2500	1380	465	CC-8	5 5/16"	Box	15
45	PAR38	Med.	S2319	45PAR38/HAL/FL	FL 30°	130V	2500	1380	465	CC-8	5 5/16"	Box	15
45	PAR38	Med.	S2220	45PAR38/HAL/NSP	NSP 9°	120V	2500	5000	465	CC-8	5 5/16"	Box	15
45	PAR38	Med.	S2320	45PAR38/HAL/NSP	NSP 9°	130V	2500	5000	465	CC-8	5 5/16"	Box	15
75	PAR38	Med.	S2221	75PAR38/HAL/FL	FL 30°	120V	2500	3200	960	CC-8	5 5/16"	Box	15
75	PAR38	Med.	S2321	75PAR38/HAL/FL	FL 30°	130V	2500	3200	960	CC-8	5 5/16"	Box	15
75	PAR38	Med.	S2222	75PAR38/HAL/NSP	NSP 9°	120V	2500	16000	960	CC-8	5 5/16"	Box	15
75	PAR38	Med.	S2322	75PAR38/HAL/NSP	NSP 9°	130V	2500	16000	960	CC-8	5 5/16"	Box	15
90	PAR38	Med.	S2223	90PAR38/HAL/FL	FL 30°	120V	2500	3800	1260	CC-8	5 5/16"	Box	15
90	PAR38	Med.	S2323	90PAR38/HAL/FL	FL 30°	130V	2500	3800	1260	CC-8	5 5/16"	Box	15
90	PAR38	Med.	S2224	90PAR38/HAL/NSP	NSP 9°	120V	2500	14000	1260	CC-8	5 5/16"	Box	15
90	PAR38	Med.	S2324	90PAR38/HAL/NSP	NSP 9°	130V	2500	14000	1260	CC-8	5 5/16"	Box	15
120	PAR38	Med.	S2225	120PAR38/HAL/FL	FL 30°	120V	2500	4700	1600	CC-8	5 5/16"	Box	15
120	PAR38	Med.	S2325	120PAR38/HAL/FL	FL 30°	130V	2500	4700	1600	CC-8	5 5/16"	Box	15
120	PAR38	Med.	S2226	120PAR38/HAL/NSP	NSP 9°	120V	2500	22000	1600	CC-8	5 5/16"	Box	15
120	PAR38	Med.	S2326	120PAR38/HAL/NSP	NSP 9°	130V	2500	22000	1600	CC-8	5 5/16"	Box	15

Halogen

PAR14/PAR16/PAR20

Whiter light, brighter colors, precise beam control.



PAR14

PAR16

PAR20

Not Shown Actual Size

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Beam	Avg. Rated		CBCP	Lumens	Filament	M.O.L.	Pack. Type	Mst. Ctn.
						Volts	Hours						
35	PAR14	Med.	S4658	35PAR14/CAP/WFL	WFL 50°	120V	2000	85	300	CC-8	2 7/16"	Box	6
60	PAR16	Med.	S4900	60PAR16/CAP/NFL	NFL 30°	120V	2000	1300	650	CC-8	2 7/8"	Box	15
60	PAR16	Med.	S4901	60PAR16/CAP/NFL	NFL 30°	130V	2000	1300	650	CC-8	2 7/8"	Box	15
60	PAR16	Med.	S4902	60PAR16/CAP/NSP	NSP 10°	120V	2000	5000	650	CC-8	2 7/8"	Box	15
60	PAR16	Med.	S4903	60PAR16/CAP/NSP	NSP 10°	130V	2000	5000	650	CC-8	2 7/8"	Box	15
75	PAR16	Med.	S4904	75PAR16/CAP/NFL	NFL 30°	120V	2000	1900	900	CC-8	2 7/8"	Box	15
75	PAR16	Med.	S4905	75PAR16/CAP/NFL	NFL 30°	130V	2000	1900	900	CC-8	2 7/8"	Box	15
75	PAR16	Med.	S4906	75PAR16/CAP/NSP	NSP 10°	120V	2000	7500	900	CC-8	2 7/8"	Box	15
75	PAR16	Med.	S4907	75PAR16/CAP/NSP	NSP 10°	130V	2000	7500	900	CC-8	2 7/8"	Box	15
35	PAR20	Med.	S4908	35PAR20/CAP/NFL	NFL 30°	120V	2500	800	360	CC-8	3 1/4"	Box	15
35	PAR20	Med.	S4663	35PAR20/CAP/NFL	NFL 30°	130V	2500	800	360	CC-8	3 1/4"	Box	15
35	PAR20	Med.	S4909	35PAR20/CAP/NSP	NSP 10°	120V	2500	3000	360	CC-8	3 1/4"	Box	15
35	PAR20	Med.	S4661	35PAR20/CAP/NSP	NSP 10°	130V	2500	3000	360	CC-8	3 1/4"	Box	15
35	PAR20	Med.	S4910	35PAR20/CAP/WFL	WFL 40°	120V	2500	500	360	CC-8	3 1/8"	Box	15
35	PAR20	Med.	S4665	35PAR20/CAP/WFL	WFL 40°	120V	2500	500	360	CC-8	3 1/8"	Box	15
50	PAR20	Med.	S4911	50PAR20/CAP/NFL	NFL 30°	120V	2500	1400	550	CC-8	3 1/4"	Box	15
50	PAR20	Med.	S4912	50PAR20/CAP/NFL	NFL 30°	130V	2500	1400	550	CC-8	3 1/4"	Box	15
50	PAR20	Med.	S4913	50PAR20/CAP/NSP	NSP 10°	120V	2500	6200	550	CC-8	3 1/4"	Box	15
50	PAR20	Med.	S4914	50PAR20/CAP/NSP	NSP 10°	130V	2500	6200	550	CC-8	3 1/4"	Box	15
50	PAR20	Med.	S4666	50PAR20/CAP/WFL	WFL 40°	120V	2500	900	550	CC-8	3 1/8"	Box	15

Halogen **PAR30** Short & Long Neck

Whiter light, brighter colors, precise beam control.

Not Shown Actual Size



PAR30 Short Neck



PAR30 Long Neck

reflectors

SHORT NECK

Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Beam	Volts	Avg. Rated Hours	CBCP*	Lumens	Filament	M.O.L.	Pack Type	Mst. Ctn.
50	PAR30	Med.	S4915	50PAR30/CAP/FL	FL 40°	120V	2500	1300	600	CC-8	3 5/8"	Box	15
50	PAR30	Med.	S4916	50PAR30/CAP/FL	FL 40°	130V	2500	1300	600	CC-8	3 5/8"	Box	15
50	PAR30	Med.	S4917	50PAR30/CAP/NFL	NFL 25°	120V	2500	2300	660	CC-8	3 5/8"	Box	15
50	PAR30	Med.	S4918	50PAR30/CAP/NFL	NFL 25°	130V	2500	2300	660	CC-8	3 5/8"	Box	15
50	PAR30	Med.	S4919	50PAR30/CAP/NSP	NSP 9°	120V	2500	8800	660	CC-8	3 5/8"	Box	15
50	PAR30	Med.	S4920	50PAR30/CAP/NSP	NSP 9°	130V	2500	8800	660	CC-8	3 5/8"	Box	15
75	PAR30	Med.	S4921	75PAR30/CAP/FL	FL 40°	120V	2500	2000	1130	CC-8	3 5/8"	Box	15
75	PAR30	Med.	S4922	75PAR30/CAP/FL	FL 40°	130V	2500	2000	1130	CC-8	3 5/8"	Box	15
75	PAR30	Med.	S4923	75PAR30/CAP/NFL	NFL 25°	120V	2500	4000	1130	CC-8	3 5/8"	Box	15
75	PAR30	Med.	S4924	75PAR30/CAP/NFL	NFL 25°	130V	2500	4000	1130	CC-8	3 5/8"	Box	15
75	PAR30	Med.	S4925	75PAR30/CAP/NSP	NSP 9°	120V	2500	15400	1130	CC-8	3 5/8"	Box	15
75	PAR30	Med.	S4926	75PAR30/CAP/NSP	NSP 9°	130V	2500	15400	1130	CC-8	3 5/8"	Box	15

LONG NECK

35	PAR30/LN	Med.	S2654	35PAR30LN/CAP/WFL	WFL 50°	120V	2500	450	450	CC-8	4 5/8"	Box	15
35	PAR30/LN	Med.	S2655	35PAR30LN/CAP/NSP	NSP 9°	120V	2500	5700	450	CC-8	4 5/8"	Box	15
50	PAR30/LN	Med.	S4927	50PAR30LN/CAP/WFL	WFL 50°	120V	2500	660	660	CC-8	4 5/8"	Box	15
50	PAR30/LN	Med.	S4928	50PAR30LN/CAP/WFL	WFL 50°	130V	2500	660	660	CC-8	4 5/8"	Box	15
50	PAR30/LN	Med.	S4929	50PAR30LN/CAP/NFL	NFL 25°	120V	2500	2300	660	CC-8	4 5/8"	Box	15
50	PAR30/LN	Med.	S4930	50PAR30LN/CAP/NFL	NFL 25°	130V	2500	2300	660	CC-8	4 5/8"	Box	15
50	PAR30/LN	Med.	S4931	50PAR30LN/CAP/NSP	NSP 9°	120V	2500	8800	660	CC-8	4 5/8"	Box	15
50	PAR30/LN	Med.	S4932	50PAR30LN/CAP/NSP	NSP 9°	130V	2500	8800	660	CC-8	4 5/8"	Box	15
75	PAR30/LN	Med.	S4933	75PAR30LN/CAP/WFL	WFL 50°	120V	2500	1100	1130	CC-8	4 5/8"	Box	15
75	PAR30/LN	Med.	S4934	75PAR30LN/CAP/WFL	WFL 50°	130V	2500	1100	1130	CC-8	4 5/8"	Box	15
75	PAR30/LN	Med.	S4935	75PAR30LN/CAP/NFL	NFL 25°	120V	2500	4000	1130	CC-8	4 5/8"	Box	15
75	PAR30/LN	Med.	S4936	75PAR30LN/CAP/NFL	NFL 25°	130V	2500	4000	1130	CC-8	4 5/8"	Box	15
75	PAR30/LN	Med.	S4937	75PAR30LN/CAP/NSP	NSP 9°	120V	2500	15400	1130	CC-8	4 5/8"	Box	15
75	PAR30/LN	Med.	S4938	75PAR30LN/CAP/NSP	NSP 9°	130V	2500	15400	1130	CC-8	4 5/8"	Box	15

Reflectors **PAR38**

Not Shown Actual Size

Whiter light,
brighter colors,
precise beam
control.



Watts	Bulb Type	Base	Satco Order No.	Lamp Code	Beam	Volts	Avg. Rated		CBCP*	Lumens	Filament	M.O.L.	Pack. Type	Mst. Ctn.
							Hours							
45	PAR38	Med. Skt.	S4939	45PAR/CAP/FL	FL 30°	120V	2500	1500	560	CC-8	5 5/16"	Box	15	
45	PAR38	Med. Skt.	S4940	45PAR/CAP/FL	FL 30°	130V	2500	1500	560	CC-8	5 5/16"	Box	15	
45	PAR38	Med. Skt.	S4941	45PAR/CAP/NSP	NSP 9°	120V	2500	10000	560	CC-8	5 5/16"	Box	15	
45	PAR38	Med. Skt.	S4942	45PAR/CAP/NSP	NSP 9°	130V	2500	10000	560	CC-8	5 5/16"	Box	15	
45	PAR38	Med. Skt.	S4630	45PAR/CAP/WFL	WFL 50°	130V	2500	700	560	CC-8	5 5/16"	Box	15	
60	PAR38	Med. Skt.	S4943	60PAR/CAP/FL	FL 30°	120V	3000	2500	850	CC-8	5 5/16"	Box	15	
60	PAR38	Med. Skt.	S4944	60PAR/CAP/FL	FL 30°	130V	3000	2500	850	CC-8	5 5/16"	Box	15	
60	PAR38	Med. Skt.	S4945	60PAR/CAP/NSP	NSP 9°	120V	3000	16000	850	CC-8	5 5/16"	Box	15	
60	PAR38	Med. Skt.	S4946	60PAR/CAP/NSP	NSP 9°	130V	3000	16000	850	CC-8	5 5/16"	Box	15	
75	PAR38	Med. Skt.	S4964	75PAR/CAP/FL	FL 30°	120V	2500	3150	1060	CC-8	5 5/16"	Box	15	
75	PAR38	Med. Skt.	S4965	75PAR/CAP/FL	FL 30°	130V	2500	3150	1060	CC-8	5 5/16"	Box	15	
75	PAR38	Med. Skt.	S4966	75PAR/CAP/NSP	NSP 9°	120V	2500	19200	1060	CC-8	5 5/16"	Box	15	
75	PAR38	Med. Skt.	S4967	75PAR/CAP/NSP	NSP 9°	130V	2500	19200	1060	CC-8	5 5/16"	Box	15	
75	PAR38	Med. Skt.	S4631	75PAR/CAP/WFL	WFL 50°	130V	2500	1300	1060	CC-8	5 5/16"	Box	15	
90	PAR38	Med. Skt.	S4968	90PAR/CAP/FL	FL 30°	120V	2500	3500	1310	CC-8	5 5/16"	Box	15	
90	PAR38	Med. Skt.	S4969	90PAR/CAP/FL	FL 30°	130V	2500	3500	1310	CC-8	5 5/16"	Box	15	
90	PAR38	Med. Skt.	S4970	90PAR/CAP/NSP	NSP 9°	120V	2500	19000	1310	CC-8	5 5/16"	Box	15	
90	PAR38	Med. Skt.	S4971	90PAR/CAP/NSP	NSP 9°	130V	2500	19000	1310	CC-8	5 5/16"	Box	15	
90	PAR38	Med. Skt.	S4950	90PAR/CAP/WSP	WSP 12°	120V	2500	14300	1310	CC-8	5 5/16"	Box	15	
90	PAR38	Med. Skt.	S4951	90PAR/CAP/WSP	WSP 12°	130V	2500	14300	1310	CC-8	5 5/16"	Box	15	
90	PAR38	Med. Skt.	S4632	90PAR/CAP/NFL	NFL 25°	130V	2500	4700	1310	CC-8	5 5/16"	Box	15	
90	PAR38	Med. Skt.	S4633	90PAR/CAP/WFL	WFL 50°	130V	2500	1600	1310	CC-8	5 5/16"	Box	15	
120	PAR38	Med. Skt.	S4972	120PAR/CAP/FL	FL 30°	120V	3000	4600	1800	CC-8	5 5/16"	Box	15	
120	PAR38	Med. Skt.	S4973	120PAR/CAP/FL	FL 30°	130V	3000	4600	1800	CC-8	5 5/16"	Box	15	
120	PAR38	Med. Skt.	S4974	120PAR/CAP/SP	SP 10°	120V	3000	22500	1800	CC-8	5 5/16"	Box	15	
120	PAR38	Med. Skt.	S4975	120PAR/CAP/SP	SP 10°	130V	3000	22500	1800	CC-8	5 5/16"	Box	15	
120	PAR38	Med. Skt.	S4634	120PAR/CAP/WFL	WFL 50°	130V	3000	2000	1800	CC-8	5 5/16"	Box	15	
250	PAR38	Med. Skt.	S4947	250PAR/CAP/FL	FL 30°	120V	4500	4500	3600	CC-8	5 5/16"	Box	6	
250	PAR38	Med. Skt.	S4948	250PAR/CAP/SP	SP 10°	120V	4500	46500	3600	CC-8	5 5/16"	Box	6	

reflectors